



# LED SPOTLIGHT

**High quality aluminum body with reflector.**

**Lighting source:energy saving COB LED can ensure The down lighting havelong life span,  
Highefficiency and It's environment protection.**

**High lumen for single ceiling light,It's better tobe used for lighting of higher and large areas.**



## Features :

- Extremely energy-efficient.
- Super long lifetime helping to decrease maintenance costs.
- Variety of designs, matching for various applications.
- UV free and no flickering.
- Higher CRI>90.
- IP54 Rang waterproof.

## Applications :

- Widely used for meeting room.
- Shoping mall.
- Showroom.
- Supermarket.
- Hotel.
- Restaurant and so on places.




## Round Series


### Dimension drawing:




**K-COB-R12W**




**K-COB-R15W**




**K-COB-R20W**



**K-COB-R24W**



**K-COB-R28W**



Reflector Cup Available Colors: Matte white, Matte black, Frosted silver, Frosted gold, Chrome, Gun black, Bright silver

Part No of LED King	Power	CCT	Lamp Size	Voltage	Lumen	CRI	Luminous Angle	IP Grade	Wrok Life
K-COB-R12W-27/30/40/50	12W	2700K 3000K 4000K 5000K	ø86x54mm	AC220V-240V	840Lm	≥90	15°、24° 38°、60°	IP54	30000h
K-COB-R15W-27/30/40/50	15W	2700K 3000K 4000K 5000K	ø100x64mm	AC220V-240V	1050Lm	≥90	15°、24° 38°、60°	IP54	30000h
K-COB-R20W-27/30/40/50	20W	2700K 3000K 4000K 5000K	ø136x83mm	AC220V-240V	1400Lm	≥90	15°、24° 38°、60°	IP54	30000h
K-COB-R24W-27/30/40/50	24W	2700K 3000K 4000K 5000K	ø158x96mm	AC220V-240V	1680Lm	≥90	15°、24° 38°、60°	IP54	30000h
K-COB-R28W-27/30/40/50	28W	2700K 3000K 4000K 5000K	ø180x109mm	AC220V-240V	1960Lm	≥90	15°、24° 38°、60°	IP54	30000h