WiFi & RF 3-Button LED Dimmer

Model No.: VD1(WT)

Tuya APP cloud control / Voice control / 3-button / Wireless remote control / Step-less dimming

Features

- WiFi & RF 1 channel constant voltage single color LED dimmer.
- 5A output, connect with 5 meters single color LED strip.
- Tuya APP cloud control, support on/off, brightness adjust, delay turn on/off light, timer run, scene edit function.
- Voice control, support for Amazon Alexa, Google Assistant, Tmall Genie and Xiaodu smart speakers.
- 3 button operation with on/off and dimming.
- Match with 2.4G single zone or multiple zone single color remote control optional.
- 4096 levels 0-100% dimming smoothly without any flash.



CE RoHS emc RED


Technical Parameters

| Input and Output | |
|-------------------------|-------------------------------|
| Input voltage | 5-24VDC |
| Output voltage | 5-24VDC |
| Output current | Max. 5A |
| Output power | 25W@5V 60W@12V 120W@24V |
| Environment | |
| Operation temperature | Ta: -30°C ~ +50°C |
| Case temperature (Max.) | Tc: +85°C |

| Dimming data | | |
|------------------|---------------------------------|--|
| Input signal | Tuya APP + RF 2.4GHz + 3 button | |
| Control distance | 30m(Barrier-free space) | |
| Dimming level | 4096 (2^12) levels | |
| Dimming range | 0-100% | |
| Dimming curve | Logarithmic | |
| PWM Frequency | 2KHz (default) | |
| Warranty | 5 years | |
| Protection | Over-heat, Short circuit | |

| Safety and EMC | |
|----------------------|---|
| EMC standard (EMC) | ETSI EN 301 489-1 V2.2.3 ETSI EN 301 489-17 V3.2.4 |
| Safety standard | EN 62368-1:2020+A11:2020 |
| Radio Equipment(RED) | ETSI EN 300 328 V2.2.2 |
| Certification | CE,EMC,RED |
| Package | |
| Size | W120 x L43 x H27mm |
| Gross weight | 0.013kg |


Dimension








Dimming remote



Note: Press and hold the (*) and (*) (Brightness-) button for 2s, output LED flashes 3 times, the light on/off fade time will change between 3s and 0.5s.

User Manual Ver 1.0.1

System Wiring



Note:

- 1. The above distance is measured in spacious (no obstacle) environment, Please refer to the actual test distance before installation.
- 2. Please check if the WiFi router net in 2.4G band, the 5G band is not available, and do not hide your router network.
- 3. Please keep the distance between VD1 (WT) devices and router close, and check the WiFi signals.
- 4. WiFi signal strength detection: open the main interface of social security, click denter the device interface, click "check device network" for testing.

Button function



: Turn on or off light.



: Brightness +, short press 10 levels, long press 1-6s for continuous 256 levels adjustment.



: Brightness -, short press 10 levels, long press 1-6s for continuous 256 levels adjustment.

Tuya APP network connection

Please download the corresponding tuya/smart life app according to your region.

Press and hold (6) and (*) (Brightness+) button for 2s: clear previous network connection, enter Smart config mode, the output LED will flash 10 times.

Press and hold (*) and (*) (Brightness+) button for 5s: Clear previous network connection, enter AP config mode, the output LED will flash 5 times. If smart config failed, please try AP config.

Repeat power on and off for 5 consecutive times, also clear previous network connection, enter Smart config mode, the output LED will flash 10 times.

If Tuya APP network connection succeed, the output LED will stop flash, and in Tuya APP, you can find DIMc device .





Smart life APP

Tuya APP

User Manual Ver 1.0.1 —

Tuya APP interface



White interface

Touch brightness slide to adjust brightness.



Scene interface

The 1-4 scene is static color. the inner color of these scene can be editable.



Timer, Schedule

The Schedule key can add multiple timers to turn on or turn off light according to different time periods.

The Timer key can turn on or turn off light in the next $24\ \text{hours}.$

Match Remote Control (optional)

End user can choose the suitable match/delete ways. Two options are offered for selection:



Match:

Long press * and * button 2s, the output LED blinks 2 times, immediately press on/off key (single zone remote) or zone key (multiple zone remote) of the remote.

The output LED blinks 3 times means match is successful.

Delete:

Press and hold (*) and (*) button for 5s to delete all match,
The output LED blinks 5 times means all matched remotes were deleted.

Use Power Restart

Match:


Switch off the power, then switch on power again, immediately short press on/off key (single zone remote) or zone key (multiple zone remote) 3 times on the remote. The output LED blinks 3 times means match is successful.

Delete:

Switch off the power, then switch on power again, immediately short press on/off key (single zone remote) or zone key (multiple zone remote) 5 times on the remote.

The output LED blinks 5 times means all matched remotes were deleted.

Dimming Curve



Packing list



LED Dimmer 1 pcs



User Manual 1 pcs



DC Extension Cable (12cm) 1 pcs

User Manual Ver 1.0.1 _______ 3