



Model NO.		IN-PFD1-IP (4MP)	IN-PFD1IP (5MP)	IN-PFD1-IPS (5MP)	IN-PFD1-IP (8MP)
Main feature	Fixed 1.7mm Fisheye 360 Lens				
	ø 5X3PCS IR LEDs, 5m Night Vision				
	Resolution: 4K/5Mp/4Mp/2Mp				
	ONVIF Support				
	POE Optional				
Video	Chipset	SC401AI + NT98562	SC5239S + GK7605V100	SONY335 + GK7605V300	SC8239 + NT98566
	Resolution	4MP	5MP	5MP	8MP/4K
	Main stream	4MP@25fps 3MP@25fps 1080P@25fps	5MP@20fps 4MP/3MP@25fps 1080P@25fps	5MP@20fps 4MP/3MP@25fps 1080P@25fps	8MP@15fps 5MP/4MP25fps 1080P@25fps
	Compression	H.264/H.265			
	Lens	Fixed 1.7mm Fisheye 360 Lens			
	Night Vision	5 meters			
	IR LED	ø 5X3PCS IR			
Audio	-	Audio input/output Optional (RCA port)			
Weatherproof	-	YES, IP66			
Pan & Tilt	-	N/A			
Network	Ethernet	RJ45			
	Protocols	TCP/IP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP, NTP,UPnP,SMTP,IPv6,etc			
	ONVIF Protocol	YES			
Compatiable with	-	XMEYE APP, NVR, NAS, Live Stream to 3rd party Using RTSP			
Additional Features	Motion Detecion	YES			
	Human Detection	YES			
	Mobile Alert Notification	YES			
Others	Power	12V DC			
	POE	Optional			
	Housing	Metal			
	Humidity	10-85% RH			
	Operating Conditions:	±30 °C ~ 60 °C (-22 °F ~ 140 °F)			
	Weight	650g			
Product Size	ø 120 x 70(H) mm				
www.innotronik.com					