

Selection and ordering data

Series Ev5R-D thermal relay matched with contactor Ev5N

	Rated frame current (A)	Current setting range (A)	Matched fuse aM (A)	type gG (A)	Matched AC contactor	Type code
	25	0.1~0.16	0.25	2	Ev5D-09	Ev5R 25/0.16
		0.16~0.25	0.25	2	Ev5D-09	Ev5R 25/0.25
		0.25~0.4	1	2	Ev5D-09	Ev5R 25/0.40
		0.4~0.63	1	2	Ev5D-09	Ev5R 25/0.63
		0.63~1	2	4	Ev5D-09	Ev5R 25/1
		1~1.6	2	4	Ev5D-09	Ev5R 25/1.6
		1.25~2	4	6	Ev5D-09	Ev5R 25/2
		1.6~2.5	4	6	Ev5D-09	Ev5R 25/2.5
		2.5~4	6	10	Ev5D-09	Ev5R 25/4
		4~6	8	16	Ev5D-09	Ev5R 25/6
		5.5~8	12	20	Ev5D-09	Ev5R 25/8
		7~10	12	20	Ev5D-12	Ev5R 25/10
		9~13	16	25	Ev5D-12	Ev5R 25/13
		12~18	20	35	Ev5D-18	Ev5R 25/18
		17~25	25	50	Ev5D-25	Ev5R 25/25
	36	23~32	40	63	Ev5D-32	Ev5R 36/32
		28~36	40	80	Ev5D-32	Ev5R 36/36
	93	23~32	40	63	Ev5D-40	Ev5R 93/32
		30~40	40	100	Ev5D-40	Ev5R 93/40
		37~50	63	100	Ev5D-50	Ev5R 93/50
		48~65	63	100	Ev5D-65	Ev5R 93/65
		55~70	80	125	Ev5D-80	Ev5R 93/70
		63~80	80	125	Ev5D-80	Ev5R 93/80
		80~93	100	160	Ev5D-95	Ev5R 93/93

Outline and installation dimensions(Series Ev5R-D)

