

Sungreen Water Pure Technology Co., Ltd

factory address: No.25 Guanfu Road,Fuhai Town,Cixi, Ningbo City
export address:No.19 Juxiang the 3rd Road , Dalang Town, Dongguan City, Guangdong Province, China
TEL:15377700152 Email: winnie@dgsungreen.com

QUOTATION SHEET

QUOTATION TIME :2025/5/11

PS: Due to the raw material price and exchange rate of dollar is constantly changing , this quotation is valid for one month.

Payment Term :TT 30% For Deposit In Advance,the rest will be paid on the delivery date

Delivery Time : 25-30 Days After Receive Deposit

Certificate : CE and CB

MOQ :100pcs (For each model)

	Water Dispenser (SL-718-A)	/	Electronic cooling	
	Rated Voltage/Frequency	550W	550W /75W	220V-240V 50/60Hz
	Function	5L/H 85-95°C	5L/H 85-95°C	Hot & Cold
	Cooling method	/	0.8L/H 10-15°C	Compressor cooling
	Heating/Cooling power			550W /90W
	Heating capacity			5L/H 85-95°C
	Cooling capacity	390*325*550mm	390*325*550mm	2L/H 5-10°C
	NW/GW			12KGS/13KGS
	Product size	1035PCS/40HQ	1035PCS/40HQ	
	Package size	/	/	390*325*550mm
	Loading Qty			450台/20FT
	EXW Price			1035PCS/40HQ
	Water Dispenser (SL-2718-D)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm	Hot & Cold	Hot & Cold
	Cooling method	/	Electronic cooling	Compressor cooling
	Heating/Cooling power	550W	550W /75W	550W /90W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	/	0.8L/H 10-15°C	2L/H 5-10°C
	NW/GW			
	Product size			
	Package size	35. 5*31. 5*53cm	35. 5*31. 5*53cm	35. 5*31. 5*53cm
	Loading Qty	480pcs/20ft	480pcs/20ft	480pcs/20ft
	EXW Price			
	Water Dispenser (SL-203-D)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm	Hot & Cold	Hot & Cold
	Cooling method	/	Electronic cooling	Compressor cooling
	Heating/Cooling power	550W	550W /75W	550W /90W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	/	0.8L/H 10-15°C	2L/H 5-10°C
	NW/GW		5.5/6.5KGS	10.0/11.0, 实际10KG
	Product size			
	Package size	390*315*530mm 准	390*315*530mm	390*315*530mm
	Loading Qty	1055PCS/40HQ	1055PCS/40HQ	1055PCS/40HQ
	EXW Price			
	Water Dispenser (SL-213-D)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm	Hot & Cold	Hot & Cold
	Cooling method	/	Electronic cooling	Compressor cooling
	Heating/Cooling power	550W	550W /75W	550W /90W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	/	0.8L/H 10-15°C	2L/H 5-10°C
	NW/GW		5.5/6.5KGS	10.0/11.0, 实际9.25KG
	Product size			
	Package size	31. 5*34*52 准	31. 5*34*52	31. 5*34*52
	Loading Qty	1055PCS/40HQ	1055PCS/40HQ	1055PCS/40HQ
	EXW Price			
	Water Dispenser (SL-202-D)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm	Hot & Cold	Hot & Cold
	Cooling method	/	Electronic cooling	Compressor cooling
	Heating/Cooling power	550W	550W /75W	550W /90W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	/	0.8L/H 10-15°C	2L/H 5-10°C
	NW/GW		5.5/6.5KGS	10.0/11.0
	Product size			
	Package size	电子: 315*315*540mm	电子: 315*315*540mm	电子: 315*315*540mm
	Loading Qty	1055PCS/40HQ	1055PCS/40HQ	1055PCS/40HQ
	EXW Price			

	Water Dispenser (SL-203-D)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm	Hot & Cold	Hot & Cold
	Cooling method	/	Electronic cooling	Compressor cooling
	Heating/Cooling power	550W	550W /75W	550W /90W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	/	0.8L/H 10-15°C	2L/H 5-10°C
	NW/GW		5.5/6.5KGS	10.0/11.0
	Product size			
	Package size	电子: 315*315*540mm	电子: 315*315*540mm	电子: 315*315*540mm
	Loading Qty	1055PCS/40HQ	1055PCS/40HQ	1055PCS/40HQ
	EXW Price			

	Water Dispenser (SL-209-D)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm	Hot & Cold	Hot & Cold
	Cooling method	/	Electronic cooling	Compressor cooling
	Heating/Cooling power	550W	550W /75W	550W /90W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	/	0.8L/H 10-15°C	2L/H 5-10°C
	NW/GW		5.5/6.5KGS	10.0/11.0
	Product size			
	Package size	电子: 315*315*540mm	电子: 315*315*540mm	电子: 315*315*540mm
	Loading Qty	1055PCS/40HQ	1055PCS/40HQ	1055PCS/40HQ
	EXW Price			

	Water Dispenser (SL-215-D)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm	Hot & Cold	Hot & Cold
	Cooling method	/	Electronic cooling	Compressor cooling
	Heating/Cooling power	550W	550W /75W	550W /90W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	/	0.8L/H 10-15°C	2L/H 5-10°C
	NW/GW		5.5/6.5KGS	10.0/11.0
	Product size			
	Package size	电子: 315*315*540mm	电子: 315*315*540mm	电子: 315*315*540mm
	Loading Qty	1055PCS/40HQ	1055PCS/40HQ	1055PCS/40HQ
	EXW Price			

	Water Dispenser (SL-890LB-D)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm	Hot & Cold	Hot & Cold
	Cooling method	/	Electronic cooling	Compressor cooling
	Heating/Cooling power	550W	550W /75W	550W /90W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	/	0.8L/H 10-15°C	2L/H 5-10°C
	NW/GW		5.5/6.5KGS	9.5KG/ 10.5kg
	Product size			
	Package size	325x320x520mm	325x320x520mm	325x320x520mm
	Loading Qty	1295PCS/40HQ	1295PCS/40HQ	1295PCS/40HQ
	EXW Price			

	Water Dispenser (SL-880LB-D)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm	Hot & Cold	Hot & Cold
	Cooling method	/	Electronic cooling	Compressor cooling
	Heating/Cooling power	550W	550W /75W	550W /90W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	/	0.8L/H 10-15°C	2L/H 5-10°C
	NW/GW		5.5/6.5KGS	10.0/11.0
	Product size			
	Package size	360x320x520mm	360x320x520mm	360x320x520mm
	Loading Qty	1120PCS/40HQ	1120PCS/40HQ	1120PCS/40HQ
	EXW Price			

	Water Dispenser (SL-901LB-D)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm	Hot & Cold	Hot & Cold
	Cooling method	/	Electronic cooling	Compressor cooling
	Heating/Cooling power	550W	550W /75W	550W /90W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	/	0.8L/H 10-15°C	2L/H 5-10°C
	NW/GW		5.5/6.5KGS	10.0/11.0
	Product size			
	Package size	360x320x520mm	360x320x520mm	360x320x520mm
	Loading Qty	1120PCS/40HQ	1120PCS/40HQ	1120PCS/40HQ
	EXW Price			

	Water Dispenser (SL-808LB-D)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm	Hot & Cold	Hot & Cold
	Cooling method	/	Electronic cooling	Compressor cooling
	Heating/Cooling power	550W	550W /75W	550W /90W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	/	0.8L/H 10-15°C	2L/H 5-10°C
	NW/GW		5.5/6.5KGS	10.0/11.0
	Product size			
	Package size	360x320x520mm	360x320x520mm	360x320x520mm
	Loading Qty	1120PCS/40HQ	1120PCS/40HQ	1120PCS/40HQ
	EXW Price			

	Water Dispenser (SL-802LB-D)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm	Hot & Cold	Hot & Cold
	Cooling method	/	Electronic cooling	Compressor cooling
	Heating/Cooling power	550W	550W /75W	550W /90W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	/	0.8L/H 10-15°C	2L/H 5-10°C
	NW/GW		5.5/6.5KGS	10.0/11.0
	Product size			
	Package size	360x320x520mm	360x320x520mm	360x320x520mm
	Loading Qty	1120PCS/40HQ	1120PCS/40HQ	1120PCS/40HQ
	EXW Price			

	Water Dispenser (SL-828LB-D)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm	Hot & Cold	Hot & Cold
	Cooling method	/	Electronic cooling	Compressor cooling
	Heating/Cooling power	550W	550W /75W	550W /90W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	/	0.8L/H 10-15°C	2L/H 5-10°C
	NW/GW		5.5/6.5KGS	10.0/11.0
	Product size			
	Package size	340x320x520mm	340x320x520mm	340x320x520mm
	Loading Qty	1120PCS/40HQ	1120PCS/40HQ	1120PCS/40HQ
	EXW Price			

	Water Dispenser (SL-805LB-D)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm	Hot & Cold	Hot & Cold
	Cooling method	/	Electronic cooling	Compressor cooling
	Heating/Cooling power	550W	550W /75W	550W /90W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	/	0.8L/H 10-15°C	2L/H 5-10°C
	NW/GW		5.5/6.5KGS	9.5KG/ 10.5kg
	Product size			
	Package size	325x320x520mm	325x320x520mm	325x320x520mm
	Loading Qty	1295PCS/40HQ	1295PCS/40HQ	1295PCS/40HQ
	EXW Price			

	Water Dispenser (SL-806LB-D)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm	Hot & Cold	Hot & Cold
	Cooling method	/	Electronic cooling	Compressor cooling
	Heating/Cooling power	550W	550W /75W	550W /90W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	/	0.8L/H 10-15°C	2L/H 5-10°C
	NW/GW		5.5/6.5KGS	9.5KG/ 10.5kg
	Product size			
	Package size	325x320x520mm	325x320x520mm	325x320x520mm
	Loading Qty	1295PCS/40HQ	1295PCS/40HQ	1295PCS/40HQ
	EXW Price			

	Water Dispenser (SL-16LB-D)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm	Hot & Cold	Hot & Cold
	Cooling method	/	Electronic cooling	Compressor cooling
	Heating/Cooling power	550W	550W /75W	550W /90W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	/	0.8L/H 10-15°C	2L/H 5-10°C
	NW/GW		5.5/6.5KGS, 实际4.5KG	9.5KG/ 10.5kg
	Product size			
	Package size	315*315*520(ok)	315*315*520(ok)	360x320x520mm
	Loading Qty	1120PCS/40HQ	1120PCS/40HQ	1120PCS/40HQ
	EXW Price			

	Water Dispenser (SL-800LB-D)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm	Hot & Cold	Hot & Cold
	Cooling method	/	Electronic cooling	Compressor cooling
	Heating/Cooling power	550W	550W /75W	550W /90W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	/	0.8L/H 10-15°C	2L/H 5-10°C
	NW/GW		5.5/6.5KGS	10.0/11.0
	Product size			
	Package size	360x320x520mm	360x320x520mm	360x320x520mm
	Loading Qty	1120PCS/40HQ	1120PCS/40HQ	1120PCS/40HQ
	EXW Price			

	Water Dispenser (SL-827LB-D)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm	Hot & Cold	Hot & Cold
	Cooling method	/	Electronic cooling	Compressor cooling
	Heating/Cooling power	550W	550W /75W	550W /90W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	/	0.8L/H 10-15°C	2L/H 5-10°C
	NW/GW		5.5/6.5KGS	9.5KG/ 10.5kg
	Product size			
	Package size	360x320x520mm	360x320x520mm	360x320x520mm
	Loading Qty	1120PCS/40HQ	1120PCS/40HQ	1120PCS/40HQ
	EXW Price			

	Water Dispenser (SL-08L-D)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm	Hot & Cold	Hot & Cold
	Cooling method	/	Electronic cooling	Compressor cooling
	Heating/Cooling power	550W	550W /75W	550W /90W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	/	0.8L/H 10-15°C	2L/H 5-10°C
	NW/GW		5.5/6.5KGS	9.5KG/ 10.5kg
	Product size			
	Package size	325*320*520mm	325*320*520mm	325*320*520mm
	Loading Qty	1295PCS/40HQ	1295PCS/40HQ	1295PCS/40HQ
	EXW Price			

	Water Dispenser (SL-818L-D)	/	Electronic cooling	
	Rated Voltage/Frequency	550W	550W /75W	220V-240V 50/60Hz
	Function	5L/H 85-95°C	5L/H 85-95°C	Hot & Cold
	Cooling method	/	0.8L/H 10-15°C	Compressor cooling
	Heating/Cooling power		5.5/6.5KGS	550W /90W
	Heating capacity			5L/H 85-95°C
	Cooling capacity	340*320*450	340*320*450	2L/H 5-10°C
	NW/GW	570PCS/20GP	570PCS/20GP	9.5KG/ 10.5kg
	Product size	1380PCS/40HQ	1380PCS/40HQ	
	Package size			340*320*450
	Loading Qty			570PCS/20GP
				1380PCS/40HQ
	EXW Price	220V-240V 50/60Hz	220V-240V 50/60Hz	
	Water Dispenser (SL-108BRW)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	/	Electronic cooling	Compressor cooling
	Heating/Cooling power	550W	550W /75W	550W /90W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	/	0.8L/H 10-15°C	2L/H 5-10°C
	NW/GW	3.5/4.5KGS	5.5/6.5KGS	9.5/10.5KGS
	Product size	310*315*510MM	310*315*510MM	310*315*510MM
	Package size	330*340*540MM	330*340*540MM	330*340*540MM
	Loading Qty	476PCS/20GP	476PCS/20GP	476PCS/20GP
		1099PCS/40HQ	1099PCS/40HQ	1099PCS/40HQ
	EXW Price			
	Water Dispenser (SL-26BA)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm	Hot & Cold	Hot & Cold
	Cooling method	/	Electronic cooling	Compressor cooling
	Heating/Cooling power	550W	550W /75W	550W /90W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	/	0.8L/H 10-15°C	2L/H 5-10°C
	NW/GW	3.5/4.5KGS	5.5/6.5KGS	9.5/10.5KGS
	Product size	310*315*510MM	310*315*510MM	310*315*510MM
	Package size	330*340*540MM	330*340*540MM	330*340*540MM
	Loading Qty	476PCS/20GP	476PCS/20GP	476PCS/20GP
		1099PCS/40HQ	1099PCS/40HQ	1099PCS/40HQ
	EXW Price			
	Water Dispenser (SL-21B)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	
	Function	Hot & Warm	Hot & Cold	
	Cooling method	/	Electronic cooling	
	Heating/Cooling power	550W	550W /75W	
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	
	Cooling capacity	/	0.8L/H 10-15°C	
	NW/GW	2.5/3.5KGS	3.5/4.5KGS, 实际3.5KG	
	Product size	290*305*410MM	290*305*410MM	
	Package size	310*310*420MM	310*310*420MM	
	Loading Qty	686PCS/20GP	686PCS/20GP	
		1596PCS/40HQ	1596PCS/40HQ	
	EXW Price			
	Water Dispenser (SL-40BBW)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	
	Function	Hot & Warm	Hot & Cold	
	Cooling method	/	Electronic cooling	
	Heating/Cooling power	550W	550W /75W	
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	
	Cooling capacity	/	0.8L/H 10-15°C	
	NW/GW	2.5/3.5KGS	3.5/4.5KGS	
	Product size	290*300*410MM	290*300*410MM	
	Package size	310*310*420MM	310*310*420MM	
	Loading Qty	686PCS/20GP	686PCS/20GP	
		1596PCS/40HQ	1596PCS/40HQ	
	EXW Price			

	Water Dispenser (SL-25)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	
	Function	Hot & Warm	Hot & Cold	
	Cooling method	/	Electronic cooling	
	Heating/Cooling power	550W	550W /75W	
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	
	Cooling capacity	/	0.8L/H 10-15°C	
	NW/GW	2.5/3.5KGS	3.5/4.5KGS	
	Product size	290*300*410MM	290*300*410MM	
	Package size	310*310*420MM	310*310*420MM	
	Loading Qty	686PCS/20GP	686PCS/20GP	
	EXW Price	1596PCS/40HQ	1596PCS/40HQ	

	Water Dispenser (SL-1022WG)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	
	Function	Hot & Warm	Hot & Cold	
	Cooling method	/	Electronic cooling	
	Heating/Cooling power	550W	550W /75W	
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	
	Cooling capacity	/	0.8L/H 10-15°C	
	NW/GW	2.5/3.5KGS	3.5/4.5KGS	
	Product size	290*300*410MM	290*300*410MM	
	Package size	310*310*420MM	310*310*420MM	
	Loading Qty	686PCS/20GP	686PCS/20GP	
	EXW Price	1596PCS/40HQ	1596PCS/40HQ	

	Water Dispenser (SL-T15)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	
	Function	Hot & Warm	Hot & Cold	
	Cooling method	/	Electronic cooling	
	Heating/Cooling power	550W	550W /75W	
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	
	Cooling capacity	/	0.8L/H 10-15°C	
	NW/GW	3.65KG/4.15kG	3.65KG/4.15kG	
	Product size	290*300*410MM	290*300*410MM	
	Package size	30*29*42CM	30*29*42CM	
	Loading Qty	750PCS/20FT	750PCS/20FT	
	EXW Price	1800PCS/40HQ	1800PCS/40HQ	

	Water Dispenser (SL-1911LB-D) /		Electronic cooling	
	Rated Voltage/Frequency	550W	550W /75W	220V-240V 50/60Hz
	Function	5L/H 85-95°C	5L/H 85-95°C	Hot & Cold
	Cooling method	/	0.8L/H 10-15°C	Compressor cooling
	Heating/Cooling power		7.5/8.5KGS	550W /90W
	Heating capacity			5L/H 85-95°C
	Cooling capacity	325x320x520mm	325x320x520mm	2L/H 5-10°C
	NW/GW			12.0/13.0(Kgs)
	Product size	1295PCS/40HQ	1295PCS/40HQ	
	Package size			325x320x520mm
	Loading Qty			1295PCS/40HQ
	EXW Price	220V-240V 50/60Hz	220V-240V 50/60Hz	

	Water Dispenser (SL-1811L-D) /		Electronic cooling	
	Rated Voltage/Frequency	550W	550W /75W	220V-240V 50/60Hz
	Function	5L/H 85-95°C	5L/H 85-95°C	Hot & Cold
	Cooling method	/	0.8L/H 10-15°C	Compressor cooling
	Heating/Cooling power		7.5/8.5KGS	550W /90W
	Heating capacity			5L/H 85-95°C
	Cooling capacity	325x320x520mm	325x320x520mm	2L/H 5-10°C
	NW/GW			12.0/13.0(Kgs)
	Product size	1295PCS/40HQ	1295PCS/40HQ	
	Package size	?	?	325x320x520mm
	Loading Qty			1295PCS/40HQ
	EXW Price	220V-240V 50/60Hz	220V-240V 50/60Hz	

	Water Dispenser (SL-37T-D)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	
	Function	Hot & Warm	Hot & Cold	
	Cooling method	/	Electronic cooling	
	Heating/Cooling power	550W	550W /75W	
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	
	Cooling capacity	/	0.8L/H 10-15°C	
	NW/GW	2.75kg	2.75kg	
	Product size			
	Package size	280*300*400mm	280*300*400mm	
	Loading Qty	980PCS/20FT	980PCS/20FT	
		2300PCS/40HQ	2300PCS/40HQ	
	EXW Price			

	Water Dispenser (SL-36T-D)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	
	Function	Hot & Warm	Hot & Cold	
	Cooling method	/	Electronic cooling	
	Heating/Cooling power	550W	550W /75W	
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	
	Cooling capacity	/	0.8L/H 10-15°C	
	NW/GW	3.05KG/3.55KG	3.05KG/3.55KG	
	Product size			
	Package size	280*300*400mm	280*300*400mm	
	Loading Qty	980PCS/20FT	980PCS/20FT	
		2300PCS/40HQ	2300PCS/40HQ	
	EXW Price			

	Water Dispenser (SL-11D)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	
	Function	Hot & Warm	Hot & Cold	
	Cooling method	/	Electronic cooling	
	Heating/Cooling power	550W	550W /75W	
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	
	Cooling capacity	/	0.8L/H 10-15°C	
	NW/GW	2.75kg	2.75kg	
	Product size			
	Package size	28*27.5*38CM	28*27.5*38CM	
	Loading Qty	980PCS/20FT	980PCS/20FT	
		2300PCS/40HQ	2300PCS/40HQ	
	EXW Price			

	Water Dispenser (SL-TY1)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	
	Function	Hot & Warm	Hot & Cold	
	Cooling method	/	Electronic cooling	
	Heating/Cooling power	550W	550W /75W	
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	
	Cooling capacity	/	0.8L/H 10-15°C	
	NW/GW	2.05KG/2.55KG	2.05KG/2.55KG	
	Product size			
	Package size	28*27.5*38CM	28*27.5*38CM	
	Loading Qty	980PCS/20FT	980PCS/20FT	
		2300PCS/40HQ	2300PCS/40HQ	
	EXW Price			

	Water Dispenser (SL-T1)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	
	Function	Hot & Warm	Hot & Cold	
	Cooling method	/	Electronic cooling	
	Heating/Cooling power	550W	550W /75W	
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	
	Cooling capacity	/	0.8L/H 10-15°C	
	NW/GW	3.05KG/3.55KG	3.05KG/3.55KG	
	Product size			
	Package size	30*29*42CM	30*29*42CM	
	Loading Qty	750PCS/20FT	750PCS/20FT	
		1800PCS/40HQ	1800PCS/40HQ	
	EXW Price			

 	Water Dispenser (SL-TY2)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	
	Function	Hot & Warm	Hot & Cold	
	Cooling method	/	Electronic cooling	
	Heating/Cooling power	550W	550W /75W	
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	
	Cooling capacity	/	0.8L/H 10-15°C	
	NW/GW	2.05KG/2.55KG	2.05KG/2.55KG	
	Product size			
	Package size	28*27.5*38CM(28*28*37英寸)	30*29*42CM	
	Loading Qty	980PCS/20FT	980PCS/20FT	
		2300PCS/40HQ	2300PCS/40HQ	
	EXW Price			

	Water Dispenser (SL-T8)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	
	Function	Hot & Warm	Hot & Cold	
	Cooling method	/	Electronic cooling	
	Heating/Cooling power	550W	550W /75W	
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	
	Cooling capacity	/	0.8L/H 10-15°C	
	NW/GW	3.05KG/3.55KG	3.05KG/3.55KG	
	Product size			
	Package size	31*31*42CM	31*31*42CM	
	Loading Qty	750PCS/20FT	750PCS/20FT	
		1800PCS/40HQ	1800PCS/40HQ	
	EXW Price			

	Water Dispenser (SL-18)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	
	Function	Hot & Warm	Hot & Cold	
	Cooling method	/	Electronic cooling	
	Heating/Cooling power	550W	550W /75W	
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	
	Cooling capacity	/	0.8L/H 10-15°C	
	NW/GW	3.05KG/3.55KG	3.05KG/3.55KG	
	Product size			
	Package size	30*29*42CM	30*29*42CM	
	Loading Qty	750PCS/20FT	750PCS/20FT	
		1800PCS/40HQ	1800PCS/40HQ	
	EXW Price			

	Water Dispenser (SL-T11)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	
	Function	Hot & Warm	Hot & Cold	
	Cooling method	/	Electronic cooling	
	Heating/Cooling power	550W	550W /75W	
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	
	Cooling capacity	/	0.8L/H 10-15°C	
	NW/GW	3.65KG/4.15kg	3.65KG/4.15kg	
	Product size			
	Package size	30*29*42CM	30*29*42CM	
	Loading Qty	750PCS/20FT	750PCS/20FT	
		1800PCS/40HQ	1800PCS/40HQ	
	EXW Price			

	Water Dispenser (SL-T16)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	
	Function	Hot & Warm	Hot & Cold	
	Cooling method	/	Electronic cooling	
	Heating/Cooling power	550W	550W /75W	
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	
	Cooling capacity	/	0.8L/H 10-15°C	
	NW/GW	2.05KG2.55KG	2.05KG2.55KG	
	Product size			
	Package size	28*27.5*38CM	28*27.5*38CM	
	Loading Qty	980PCS/20FT	980PCS/20FT	
		2300PCS/40HQ	2300PCS/40HQ	
	EXW Price			

	Water Dispenser (SL-T4)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	
	Function	Hot & Warm	Hot & Cold	
	Cooling method	/	Electronic cooling	
	Heating/Cooling power	550W	550W /75W	
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	
	Cooling capacity	/	0.8L/H 10-15°C	
	NW/GW	2.35KG/2.85KG	2.35KG/2.85KG	
	Product size			
	Package size	28*27.5*38CM	28*27.5*38CM	
	Loading Qty	980PCS/20FT	980PCS/20FT	
		2300PCS/40HQ	2300PCS/40HQ	
	EXW Price			

	Water Dispenser (SL-TY26)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm	Hot & Cold	Hot & Cold
	Cooling method	/	Electronic cooling	Compressor cooling
	Heating/Cooling power	550W	550W /75W	550W /90W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	/	0.8L/H 10-15°C	2L/H 5-10°C
	NW/GW		5.5/6.5KGS	11.0/12.5
	Product size			
	Package size	360*330*520(mm)	360*330*520(mm)	360*330*520(mm)
	Loading Qty	448PCS/20FT	448PCS/20FT	448PCS/20FT
		1100PCS/40HQ	1100PCS/40HQ	1100PCS/40HQ
	EXW Price			

	Water Dispenser (SL-T012)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	
	Function	Hot & Warm	Hot & Cold	
	Cooling method	/	Electronic cooling	
	Heating/Cooling power	550W	550W /75W	
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	
	Cooling capacity	/	0.8L/H 10-15°C	
	NW/GW	2.35KG/2.85KG	2.35KG/2.85KG	
	Product size			
	Package size	25*25*34	25*25*34	
	Loading Qty	1300PCS/20FT	1300PCS/20FT	
		3200PCS/40HQ	3200PCS/40HQ	
	EXW Price			

	Water Dispenser (SL-TY36)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	
	Function	Hot & Warm	Hot & Cold	
	Cooling method	/	Electronic cooling	
	Heating/Cooling power	550W	550W /75W	
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	
	Cooling capacity	/	0.8L/H 10-15°C	
	NW/GW	2.43 / 3.2 + 0.625	2.43 / 3.2 + 0.625	
	Product size			
	Package size	310*310*420(mm)	310*310*420(mm)	
	Loading Qty	650PCS/20FT	650PCS/20FT	
		1650PCS/40HQ	1650PCS/40HQ	
	EXW Price			

	Water Dispenser (SL-YT38)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	
	Function	Hot & Warm	Hot & Cold	
	Cooling method	/	Electronic cooling	
	Heating/Cooling power	550W	550W /75W	
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	
	Cooling capacity	/	0.8L/H 10-15°C	
	NW/GW	2.43 / 3.2 + 0.625	2.43 / 3.2 + 0.625	
	Product size			
	Package size	310*310*420(mm)	310*310*420(mm)	
	Loading Qty	650PCS/20FT	650PCS/20FT	
		1650PCS/40HQ	1650PCS/40HQ	
	EXW Price			

	Water Dispenser (SL-YT32)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm	Hot & Cold	Hot & Cold
	Cooling method	/	Electronic cooling	Compressor cooling
	Heating/Cooling power	550W	550W /75W	550W /90W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	/	0.8L/H 10-15°C	2L/H 5-10°C
	NW/GW		5.5/6.5KGS	11.0/12.5
	Product size			
	Package size	360*330*520(mm)	360*330*520(mm)	360*330*520(mm)
	Loading Qty	448PCS/20FT 1100PCS/40HQ	448PCS/20FT 1100PCS/40HQ	448PCS/20FT 1100PCS/40HQ
	EXW Price			

	Water Dispenser (SL-YT27)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm	Hot & Cold	Hot & Cold
	Cooling method	/	Electronic cooling	Compressor cooling
	Heating/Cooling power	550W	550W /75W	550W /90W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	/	0.8L/H 10-15°C	2L/H 5-10°C
	NW/GW		5.5/6.5KGS	11.0/12.5
	Product size			
	Package size	360*330*520(mm)	360*330*520(mm)	360*330*520(mm)
	Loading Qty	448PCS/20FT 1100PCS/40HQ	448PCS/20FT 1100PCS/40HQ	448PCS/20FT 1100PCS/40HQ
	EXW Price			

	Water Dispenser (SL-YT29)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm	Hot & Cold	Hot & Cold
	Cooling method	/	Electronic cooling	Compressor cooling
	Heating/Cooling power	550W	550W /75W	550W /90W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	/	0.8L/H 10-15°C	2L/H 5-10°C
	NW/GW		5.5/6.5KGS	11.0/12.5
	Product size			
	Package size	360*330*520(mm)	360*330*520(mm)	360*330*520(mm)
	Loading Qty	448PCS/20FT 1100PCS/40HQ	448PCS/20FT 1100PCS/40HQ	448PCS/20FT 1100PCS/40HQ
	EXW Price			

	Water Dispenser (SL-YT34)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm	Hot & Cold	Hot & Cold
	Cooling method	/	Electronic cooling	Compressor cooling
	Heating/Cooling power	550W	550W /75W	550W /90W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	/	0.8L/H 10-15°C	2L/H 5-10°C
	NW/GW		5.5/6.5KGS	11.0/12.5
	Product size			
	Package size	360*330*520(mm)	360*330*520(mm)	360*330*520(mm)
	Loading Qty	448PCS/20FT 1100PCS/40HQ	448PCS/20FT 1100PCS/40HQ	448PCS/20FT 1100PCS/40HQ
	EXW Price			

	Water Dispenser (SL-YT35)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm	Hot & Cold	Hot & Cold
	Cooling method	/	Electronic cooling	Compressor cooling
	Heating/Cooling power	550W	550W /75W	550W /90W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	/	0.8L/H 10-15°C	2L/H 5-10°C
	NW/GW		5.5/6.5KGS	11.0/12.5
	Product size			
	Package size	360*330*520(mm)	360*330*520(mm)	360*330*520(mm)
	Loading Qty	448PCS/20FT 1100PCS/40HQ	448PCS/20FT 1100PCS/40HQ	448PCS/20FT 1100PCS/40HQ
	EXW Price			

	Water Dispenser (SL-YT43)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm	Hot & Cold	Hot & Cold
	Cooling method	/	Electronic cooling	Compressor cooling
	Heating/Cooling power	550W	550W /75W	550W /90W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	/	0.8L/H 10-15°C	2L/H 5-10°C
	NW/GW		5.5/6.5KGS	11.0/12.5
	Product size			
	Package size	360*330*520(mm)	360*330*520(mm)	360*330*520(mm)
	Loading Qty	448PCS/20FT 1100PCS/40HQ	448PCS/20FT 1100PCS/40HQ	448PCS/20FT 1100PCS/40HQ
	EXW Price			

	Water Dispenser (SL-YT431)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm	Hot & Cold	Hot & Cold
	Cooling method	/	Electronic cooling	Compressor cooling
	Heating/Cooling power	550W	550W /75W	550W /90W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	/	0.8L/H 10-15°C	2L/H 5-10°C
	NW/GW		5.5/6.5KGS	11.0/12.5
	Product size			
	Package size	360*330*520(mm)	360*330*520(mm)	360*330*520(mm)
	Loading Qty	448PCS/20FT 1100PCS/40HQ	448PCS/20FT 1100PCS/40HQ	448PCS/20FT 1100PCS/40HQ
	EXW Price			

	Water Dispenser (SL-178T)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm	Hot & Cold	Hot & Cold
	Cooling method	/	Electronic cooling	Compressor cooling
	Heating/Cooling power	550W	550W /75W	550W /90W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	/	0.8L/H 10-15°C	2L/H 5-10°C
	NW/GW		5.5/6.5KGS	9/10.1
	Product size			
	Package size	345*315*520	345*315*520	345*315*520
	Loading Qty	476PCS/20FT 1260PCS/40HQ	476PCS/20FT 1260PCS/40HQ	476PCS/20FT 1260PCS/40HQ
	EXW Price			

	Water Dispenser (SL-1003T)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm	Hot & Cold	Hot & Cold
	Cooling method	/	Electronic cooling	Compressor cooling
	Heating/Cooling power	550W	550W /75W	550W /90W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	/	0.8L/H 10-15°C	2L/H 5-10°C
	NW/GW		5.5/6.5KGS	8/8.75
	Product size	270*295*450MM	270*295*450MM	270*295*450MM
	Package size	295*355*475MM	295*355*475MM	295*355*475MM
	Loading Qty	600PCS/20FT 1400PCS/40HQ	600PCS/20FT 1400PCS/40HQ	600PCS/20FT 1400PCS/40HQ
	EXW Price			

	Water Dispenser (SL-1004T)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm	Hot & Cold	Hot & Cold
	Cooling method	/	Electronic cooling	Compressor cooling
	Heating/Cooling power	550W	550W /75W	550W /90W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	/	0.8L/H 10-15°C	2L/H 5-10°C
	NW/GW		5.5/6.5KGS	8/8.75
	Product size	270*295*450MM	270*295*450MM	270*295*450MM
	Package size	295*355*475MM	295*355*475MM	295*355*475MM
	Loading Qty	600PCS/20FT 1400PCS/40HQ	600PCS/20FT 1400PCS/40HQ	600PCS/20FT 1400PCS/40HQ
	EXW Price			

	Water Dispenser (SL-1005T)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm	Hot & Cold	Hot & Cold
	Cooling method	/	Electronic cooling	Compressor cooling
	Heating/Cooling power	550W	550W /75W	550W /90W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	/	0.8L/H 10-15°C	2L/H 5-10°C
	NW/GW		5.5/6.5KGS	8/8.75
	Product size	270*295*450MM	270*295*450MM	270*295*450MM
	Package size	295*355*475MM	295*355*475MM	295*355*475MM
	Loading Qty	600PCS/20FT	600PCS/20FT	600PCS/20FT
		1400PCS/40HQ	1400PCS/40HQ	1400PCS/40HQ
	EXW Price			

	Water Dispenser (SL-1006T)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm	Hot & Cold	Hot & Cold
	Cooling method	/	Electronic cooling	Compressor cooling
	Heating/Cooling power	550W	550W /75W	550W /90W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	/	0.8L/H 10-15°C	2L/H 5-10°C
	NW/GW		5.5/6.5KGS	8/8.75
	Product size	270*295*450MM	270*295*450MM	270*295*450MM
	Package size	295*355*475MM	295*355*475MM	295*355*475MM
	Loading Qty	600PCS/20FT	600PCS/20FT	600PCS/20FT
		1400PCS/40HQ	1400PCS/40HQ	1400PCS/40HQ
	EXW Price			

	Water Dispenser (SL-1007T)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm	Hot & Cold	Hot & Cold
	Cooling method	/	Electronic cooling	Compressor cooling
	Heating/Cooling power	550W	550W /75W	550W /90W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	/	0.8L/H 10-15°C	2L/H 5-10°C
	NW/GW		5.5/6.5KGS	8/8.75
	Product size	270*295*450MM	270*295*450MM	270*295*450MM
	Package size	295*355*475MM	295*355*475MM	295*355*475MM
	Loading Qty	600PCS/20FT	600PCS/20FT	600PCS/20FT
		1400PCS/40HQ	1400PCS/40HQ	1400PCS/40HQ
	EXW Price			

	Water Dispenser (SL-1008T)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm	Hot & Cold	Hot & Cold
	Cooling method	/	Electronic cooling	Compressor cooling
	Heating/Cooling power	550W	550W /75W	550W /90W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	/	0.8L/H 10-15°C	2L/H 5-10°C
	NW/GW		5.5/6.5KGS	8kg/9kg
	Product size	310*320*530MM	310*320*530MM	310*320*530MM
	Package size	348*385*580MM	348*385*580MM	348*385*580MM
	Loading Qty	420PCS/20FT	420PCS/20FT	420PCS/20FT
		940PCS/40HQ	940PCS/40HQ	940PCS/40HQ
	EXW Price			

	Water Dispenser (SL-1011T)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm	Hot & Cold	Hot & Cold
	Cooling method	/	Electronic cooling	Compressor cooling
	Heating/Cooling power	550W	550W /75W	550W /90W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	/	0.8L/H 10-15°C	2L/H 5-10°C
	NW/GW		5.5/6.5KGS	8.6/9.7
	Product size	310*310*520MM	310*310*520MM	310*310*520MM
	Package size	320*370*555MM	320*370*555MM	320*370*555MM
	Loading Qty	435PCS/20FT	435PCS/20FT	435PCS/20FT
		1040PCS/40HQ	1040PCS/40HQ	1040PCS/40HQ
	EXW Price			



Water Dispenser (SL-1011T-X3)			
Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
Function	Hot & Warm	Hot & Cold	Hot & Cold
Cooling method	/	Electronic cooling	Compressor cooling
Heating/Cooling power	550W	550W /75W	550W /90W
Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
Cooling capacity	/	0.8L/H 10-15°C	2L/H 5-10°C
NW/GW		5.5/6.5KGS	9/10.1
Product size	310*310*520MM	310*310*520MM	310*310*520MM
Package size	320*370*555MM	320*370*555MM	320*370*555MM
Loading Qty	435PCS/20FT	435PCS/20FT	435PCS/20FT
	1040PCS/40HQ	1040PCS/40HQ	1040PCS/40HQ
EXW Price			



Water Dispenser (SL-3001T)			
Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	
Function	Hot & Warm	Hot & Cold	
Cooling method	/	Electronic cooling	
Heating/Cooling power	550W	550W /75W	
Heating capacity	5L/H 85-95°C	5L/H 85-95°C	
Cooling capacity	/	0.8L/H 10-15°C	
NW/GW	3/3.6	3/3.6	
Product size	320*302*395MM	320*302*395MM	
Package size	320*370*555MM	320*370*555MM	
	700PCS/20FT	700PCS/20FT	
Loading Qty	1596PCS/40HQ	1596PCS/40HQ	
EXW Price			



Water Dispenser (SL-3007T)			
Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	
Function	Hot & Warm	Hot & Cold	
Cooling method	/	Electronic cooling	
Heating/Cooling power	550W	550W /75W	
Heating capacity	5L/H 85-95°C	5L/H 85-95°C	
Cooling capacity	/	0.8L/H 10-15°C	
NW/GW	3/3.6	3/3.6	
Product size	:330*270*400MM	:330*270*400MM	
Package size	:320*370*555MM	:320*370*555MM	
	700PCS/20FT	700PCS/20FT	
Loading Qty	1600PCS/40HQ	1600PCS/40HQ	
EXW Price			



Water Dispenser (SL-2004T)			
Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	
Function	Hot & Warm	Hot & Cold	
Cooling method	/	Electronic cooling	
Heating/Cooling power	550W	550W /75W	
Heating capacity	5L/H 85-95°C	5L/H 85-95°C	
Cooling capacity	/	0.8L/H 10-15°C	
NW/GW	3/3.6	3/3.6	
Product size	:330*270*400MM	:330*270*400MM	
Package size	:320*370*555MM	:320*370*555MM	
	700PCS/20FT	700PCS/20FT	
Loading Qty	1600PCS/40HQ	1600PCS/40HQ	
EXW Price			



Water Dispenser (SL-2001T)			
Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	
Function	Hot & Warm	Hot & Cold	
Cooling method	/	Electronic cooling	
Heating/Cooling power	550W	550W /75W	
Heating capacity	5L/H 85-95°C	5L/H 85-95°C	
Cooling capacity	/	0.8L/H 10-15°C	
NW/GW	2.6/3.2	2.6/3.2	
Product size	250*270*360MM	250*270*360MM	
Package size	320*370*555MM	320*370*555MM	
	1000PCS/20FT	1000PCS/20FT	
Loading Qty	2200PCS/40HQ	2200PCS/40HQ	
EXW Price			



Water Dispenser (SL-2002T)			
Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	
Function	Hot & Warm	Hot & Cold	
Cooling method	/	Electronic cooling	
Heating/Cooling power	550W	550W /75W	
Heating capacity	5L/H 85-95°C	5L/H 85-95°C	
Cooling capacity	/	0.8L/H 10-15°C	
NW/GW	2.6/3.2	2.6/3.2	
Product size	250*270*360MM	250*270*360MM	
Package size	320*370*555MM	320*370*555MM	
	1000PCS/20FT	1000PCS/20FT	
Loading Qty	2200PCS/40HQ	2200PCS/40HQ	
EXW Price			