

Sungreen Water Pure Technology Co., Ltd

factory address: No.25 Guanfu Road,Fuhai Town,Cixi, Ningbo City
 export address:No.19 Juxiang the 3rd Road , Dalang Town, Dongguan City, Guangdong Province, China
 TEL:15377700152 Email: winnie@dgsungreen.com

QUOTATION SHEET

QUOTATION TIME :2025/5/11

PS: Due to the raw material price and exchange rate of dollar is constantly changing , this quotation is valid for one month.

Payment Term :TT 30% For Deposit In Advance,the rest will be paid on the delivery date

Delivery Time : 25-30 Days After Receive Deposit

Certificate : CE and CB

MOQ :100pcs (For each model)

	Water Dispenser (SL-8816)		
	Item No.	Ro System	UF System
	Filter Method	PP+UDF+CTO+RO+T33	PP+UDF+CTO+UF+T33
	Filter Capacity	75GPD	62.5L/H
	Cooling method	Compressor cooling	Electronic cooling
	Heating power	1350W	1350W
	Cooling power	90W	75W
	Heating capacity	8L/H 50-100°C	8L/H 50-100°C
	Cooling capacity	2L/H 5-10°C	0.8L/H 10-15°C
	NW/GW	18/19KGS	12/13KGS
	Package size	380*410*860mm	380*410*860mm
	Loading Qty	504PCS/40HQ	504PCS/40HQ
	EXW Price		

	Water Dispenser (SL-8816)		
	Item No.	Ro System	UF System
	Filter Method	PP+UDF+CTO+RO+T33	PP+UDF+CTO+UF+T33
	Filter Capacity	75GPD	62.5L/H
	Cooling method	Compressor cooling	Electronic cooling
	Heating power	1350W	1350W
	Cooling power	90W	75W
	Heating capacity	8L/H 50-100°C	8L/H 50-100°C
	Cooling capacity	2L/H 5-10°C	0.8L/H 10-15°C
	NW/GW	18/19KGS	12/13KGS
	Package size	380*410*860mm	380*410*860mm
	Loading Qty	504PCS/40HQ	504PCS/40HQ
	EXW Price		

	Water Dispenser (SL-880LB)		
	Item No.	Ro System	UF System
	Filter Method	PP+UDF+CTO+RO+T33	PP+UDF+CTO+UF+T33
	Filter Capacity	75GPD	62.5L/H
	Cooling method	Compressor cooling	Compressor cooling
	Heating power	550W	550W
	Cooling power	90W	75W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	2L/H 5-10°C	0.8L/H 10-15°C
	NW/GW		
	Package size	325x320x980mm	325x320x980mm
	Loading Qty	650PCS/40HQ/ 277PCS/20GP	650PCS/40HQ/ 277PCS/20GP
	EXW Price		

	Water Dispenser (SL-880LB-D)		
	Item No.	Ro System	UF System
	Filter Method	PP+CTO+RO+T33	PP++CTO+UF+T33
	Filter Capacity	75GPD	62.5L/H
	Cooling method	Compressor cooling	Compressor cooling
	Heating power	550W	550W
	Cooling power	90W	75W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	2L/H 5-10°C	0.8L/H 10-15°C
	NW/GW		
	Package size	535*355*525 确定	535*355*525
	Loading Qty	840PCS/40HQ, 336PCS/20GP	840PCS/40HQ, 336PCS/20GP
	EXW Price		

	Water Dispenser (SL-901LB)		
	Item No.	Ro System	UF System
	Filter Method	PP+UDF+CTO+RO+T33	PP+UDF+CTO+UF+T33
	Filter Capacity	75GPD	62.5L/H
	Cooling method	Compressor cooling	Compressor cooling
	Heating power	550W	550W
	Cooling power	90W	75W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	2L/H 5-10°C	0.8L/H 10-15°C
	NW/GW		
	Package size	325x320x980mm	325x320x980mm
	Loading Qty	650PCS/40HQ/ 277PCS/20GP	650PCS/40HQ/ 277PCS/20GP
	EXW Price		

	Water Dispenser (SL-901LB-D)		
	Item No.	Ro System	UF System
	Filter Method	PP+CTO+RO+T33	PP+CTO+UF+T33
	Filter Capacity	75GPD	62.5L/H
	Cooling method	Compressor cooling	Compressor cooling
	Heating power	550W	550W
	Cooling power	90W	75W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	2L/H 5-10°C	0.8L/H 10-15°C
	NW/GW		
	Package size	535*355*525 确定	535*355*525
	Loading Qty	840PCS/40HQ, 336PCS/20GP	840PCS/40HQ, 336PCS/20GP
	EXW Price		

	Water Dispenser (SL-808LB)		
	Item No.	Ro System	UF System
	Filter Method	PP+UDF+CTO+RO+T33	PP+UDF+CTO+UF+T33
	Filter Capacity	75GPD	62.5L/H
	Cooling method	Compressor cooling	Compressor cooling
	Heating power	550W	550W
	Cooling power	90W	75W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	2L/H 5-10°C	0.8L/H 10-15°C
	NW/GW		
	Package size	340x320x990mm	340x320x990mm
	Loading Qty	650PCS/40HQ/ 277PCS/20GP	650PCS/40HQ/ 277PCS/20GP
	EXW Price		

	Water Dispenser (SL-808LB-D)		
	Item No.	Ro System	UF System
	Filter Method	PP+UDF+CTO+RO+T33	PP+UDF+CTO+UF+T33
	Filter Capacity	75GPD	62.5L/H
	Cooling method	Compressor cooling	Compressor cooling
	Heating power	550W	550W
	Cooling power	90W	75W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	2L/H 5-10°C	0.8L/H 10-15°C
	NW/GW		
	Package size	535*355*525 确定	535*355*525
	Loading Qty	840PCS/40HQ, 336PCS/20GP	840PCS/40HQ, 336PCS/20GP
	EXW Price		

	Water Dispenser (SL-802LB)		
	Item No.	Ro System	UF System
	Filter Method	PP+UDF+CTO+RO+T33	PP+UDF+CTO+UF+T33
	Filter Capacity	75GPD	62.5L/H
	Cooling method	Compressor cooling	Compressor cooling
	Heating power	550W	550W
	Cooling power	90W	75W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	2L/H 5-10°C	0.8L/H 10-15°C
	NW/GW		
	Package size	340x320x990mm	340x320x990mm
	Loading Qty	650PCS/40HQ/ 277PCS/20GP	650PCS/40HQ/ 277PCS/20GP
	EXW Price		

	Water Dispenser (SL-802LB-D)		
	Item No.	Ro System	UF System
	Filter Method	PP+UDF+CTO+RO+T33	PP+UDF+CTO+UF+T33
	Filter Capacity	75GPD	62.5L/H
	Cooling method	Compressor cooling	Compressor cooling
	Heating power	550W	550W
	Cooling power	90W	75W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	2L/H 5-10°C	0.8L/H 10-15°C
	NW/GW		
	Package size	535*355*525 确定	535*355*525
	Loading Qty	840PCS/40HQ, 336PCS/20GP	840PCS/40HQ, 336PCS/20GP
	EXW Price		

	Water Dispenser (SL-805LB)		
	Item No.	Ro System	UF System
	Filter Method	PP+UDF+CTO+RO+T33	PP+UDF+CTO+UF+T33
	Filter Capacity	75GPD	62.5L/H
	Cooling method	Compressor cooling	Compressor cooling
	Heating power	550W	550W
	Cooling power	90W	75W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	2L/H 5-10°C	0.8L/H 10-15°C
	NW/GW		
	Package size	320x320x980mm	320x320x980mm
	Loading Qty	680PCS/40HQ/ 291PCS/20GP	680PCS/40HQ/ 291PCS/20GP
	EXW Price		

	Water Dispenser (SL-800LB)		
	Item No.	Ro System	UF System
	Filter Method	PP+UDF+CTO+RO+T33	PP+UDF+CTO+UF+T33
	Filter Capacity	75GPD	62.5L/H
	Cooling method	Compressor cooling	Compressor cooling
	Heating power	550W	550W
	Cooling power	90W	75W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	2L/H 5-10°C	0.8L/H 10-15°C
	NW/GW		
	Package size	325x320x990mm	325x320x990mm
	Loading Qty	650PCS/40HQ/ 277PCS/20GP	650PCS/40HQ/ 277PCS/20GP
	EXW Price		

	Water Dispenser (SL-800LB-D)		
	Item No.	Ro System	UF System
	Filter Method	PP+UDF+CTO+RO+T33	PP+UDF+CTO+UF+T33
	Filter Capacity	75GPD	62.5L/H
	Cooling method	Compressor cooling	Compressor cooling
	Heating power	550W	550W
	Cooling power	90W	75W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	2L/H 5-10°C	0.8L/H 10-15°C
	NW/GW		
	Package size	535*355*525 确定	535*355*525
	Loading Qty	840PCS/40HQ, 336PCS/20GP	840PCS/40HQ, 336PCS/20GP
	EXW Price		

	Water Dispenser (SL-828LB-D)		
	Item No.	Ro System	UF System
	Filter Method	PP+UDF+CTO+RO+T33	PP+UDF+CTO+UF+T33
	Filter Capacity	75GPD	62.5L/H
	Cooling method	Compressor cooling	Compressor cooling
	Heating power	550W	550W
	Cooling power	90W	75W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	2L/H 5-10°C	0.8L/H 10-15°C
	NW/GW		
	Package size	535*355*525 确定	535*355*525
	Loading Qty	840PCS/40HQ, 336PCS/20GP	840PCS/40HQ, 336PCS/20GP
	EXW Price		

	Water Dispenser (SL-718-A)		
	Item No.	Ro System	UF System
	Filter Method	PP+UDF+CTO+RO+T33	PP+UDF+CTO+UF+T33
	Filter Capacity	75GPD	62.5L/H
	Cooling method	Compressor cooling	Compressor cooling
	Heating power	550W	550W
	Cooling power	90W	75W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	2L/H 5-10°C	0.8L/H 10-15°C
	NW/GW		
	Package size	390*325*550mm	390*325*550mm
	Loading Qty	780PCS/40HQ	780PCS/40HQ
	EXW Price		
	Water Dispenser (SL-RO2910TB)		
	Item No.	Ro System	UF System
	Filter Method	PP+UDF+CTO+RO+T33	PP+UDF+CTO+UF+T33
	Filter Capacity	75GPD	62.5L/H
	Cooling method	Compressor cooling	Compressor cooling
	Heating power	550W	550W
	Cooling power	90W	75W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	2L/H 5-10°C	0.8L/H 10-15°C
	NW/GW	14KGS/15KGS	14KGS/15KGS
	Package size	505x325x552mm	505x325x552mm
	Loading Qty	308PCS/20FT	308PCS/20FT
		644PCS/40HQ	644PCS/40HQ
	EXW Price		
	Water Dispenser (SL-2088-3-RO)		
	Item No.	Ro System	UF System
	Filter Method	PP+UDF+CTO+RO+T33	PP+UDF+CTO+UF+T33
	Filter Capacity	75GPD	62.5L/H
	Cooling method	Compressor cooling	Compressor cooling
	Heating power	550W	550W
	Cooling power	90W	75W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	2L/H 5-10°C	0.8L/H 10-15°C
	NW/GW		
	Package size	350*340*1060MM	350*340*1060MM
	Loading Qty	474PCS/40HQ/ 192PCS/20GP	474PCS/40HQ/ 192PCS/20GP
	EXW Price		
	Water Dispenser (SL-1038WG-RO)		
	Item No.	Ro System	UF System
	Filter Method	PP+UDF+CTO+RO+T33	PP+UDF+CTO+UF+T33
	Filter Capacity	75GPD	62.5L/H
	Cooling method	Compressor cooling	Compressor cooling
	Heating power	550W	550W
	Cooling power	90W	75W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	2L/H 5-10°C	0.8L/H 10-15°C
	NW/GW	15.9KG	
	Package size	330*340*980MM	330*340*980MM
	Loading Qty	630PCS/40HQ/ 273PCS/20GP	630PCS/40HQ/ 273PCS/20GP
	EXW Price		
	Water Dispenser (SL-801L-RO)		
	Item No.	Ro System	UF System
	Filter Method	PP+UDF+CTO+RO+T33	PP+UDF+CTO+UF+T33
	Filter Capacity	75GPD	62.5L/H
	Cooling method	Compressor cooling	Compressor cooling
	Heating power	550W	550W
	Cooling power	90W	75W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	2L/H 5-10°C	0.8L/H 10-15°C
	NW/GW		
	Package size	340*320*980MM	340*320*980MM
	Loading Qty	650PCS/40HQ/ 277PCS/20GP	650PCS/40HQ/ 277PCS/20GP
	EXW Price		