

Sungreen Water Pure Technology Co., Ltd

factory address: No.25 Guanfu Road,Fuhai Town,Cixi, Ningbo City
 export address:No.19 Juxiang the 3rd Road , Dalang Town, Dongguan City, Guangdong Province, China
 TEL:15377700152 Email: winnie@dgsungreen.com

QUOTATION SHEET

QUOTATION TIME :2025/5/11

PS: Due to the raw material price and exchange rate of dollar is constantly changing , this quotation is valid for one month.

Payment Term :TT 30% For Deposit In Advance,the rest will be paid on the delivery date

Delivery Time : 25-30 Days After Receive Deposit

Certificate : CE and CB

MOQ :100pcs (For each model)

	Water Dispenser (SL-2718)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W /75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95℃	5L/H 85-95℃	5L/H 85-95℃
	Cooling capacity	0.8L/H 10-15℃	2L/H 5-10℃	2L/H 5-10℃
	NW/GW		11KG/12.5kg	14Kg
	Product size			
	Package size	315*325*1000MM	315*325*1000MM	315*325*1000MM
	Loading Qty			
		680PCS/40HQ	680PCS/40HQ	680PCS/40HQ
	Water Dispenser (SL-202)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W /75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95℃	5L/H 85-95℃	5L/H 85-95℃
	Cooling capacity	0.8L/H 10-15℃	2L/H 5-10℃	2L/H 5-10℃
	NW/GW	6.2KG/7.2kg	13.0/14.0	;15.0/16.0
	Product size			
	Package size	315*315*1000MM	315*315*1000MM	315*315*1000MM
	Loading Qty			
		680PCS/40HQ	680PCS/40HQ	680PCS/40HQ
	Water Dispenser (SL-206)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W /75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95℃	5L/H 85-95℃	5L/H 85-95℃
	Cooling capacity	0.8L/H 10-15℃	2L/H 5-10℃	2L/H 5-10℃
	NW/GW	6.2KG/7.2kg (实际7.6KG)	13.0/14.0	;15.0/16.0
	Product size			
	Package size	315*315*1000MM	315*315*1000MM	315*315*1000MM
	Loading Qty			
		680PCS/40HQ	680PCS/40HQ	680PCS/40HQ

	Water Dispenser (SL-209)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W /75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95℃	5L/H 85-95℃	5L/H 85-95℃
	Cooling capacity	0.8L/H 10-15℃	2L/H 5-10℃	2L/H 5-10℃
	NW/GW	6.2KG/7.2kG	13.0/14.0	;15.0/16.0
	Product size			
	Package size	315*315*1000MM	315*315*1000MM	315*315*1000MM
	Loading Qty	680PCS/40HQ	680PCS/40HQ	680PCS/40HQ
	Water Dispenser (SL-208)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W /75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95℃	5L/H 85-95℃	5L/H 85-95℃
	Cooling capacity	0.8L/H 10-15℃	2L/H 5-10℃	2L/H 5-10℃
	NW/GW	8.6kg /10.5KG	14/15	
	Product size	310*320*960MM	310*320*960MM	310*320*960MM
	Package size	325*335*1000MM	315*315*1000MM	315*315*1000MM
	Loading Qty	680PCS/40HQ	680PCS/40HQ	680PCS/40HQ
	Water Dispenser (SL-213)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W /75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95℃	5L/H 85-95℃	5L/H 85-95℃
	Cooling capacity	0.8L/H 10-15℃	2L/H 5-10℃	2L/H 5-10℃
	NW/GW	6.2KG/7.2kG	13.0/14.0 实际14.1KG	;15.0/16.0
	Product size			
	Package size	315*315*1000MM	315*315*1000MM	315*315*1000MM
	Loading Qty	680PCS/40HQ	680PCS/40HQ	680PCS/40HQ
	Water Dispenser (SL-215)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W /75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95℃	5L/H 85-95℃	5L/H 85-95℃
	Cooling capacity	0.8L/H 10-15℃	2L/H 5-10℃	2L/H 5-10℃
	NW/GW	6.2KG/7.2kG	13.0/14.0	;15.0/16.0
	Product size			
	Package size	315*315*1000MM	315*315*1000MM	315*315*1000MM
	Loading Qty	680PCS/40HQ	680PCS/40HQ	680PCS/40HQ
		\$28.65	\$43.75	\$49.25

	Water Dispenser (SL-85)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W /75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95℃	5L/H 85-95℃	5L/H 85-95℃
	Cooling capacity	0.8L/H 10-15℃	2L/H 5-10℃	2L/H 5-10℃
	NW/GW	5.55/ 6.05KG	5.55/ 6.05KG	
	Product size	271*276*823 (ok)	271*276*823	
	Package size	285*290*870mm	285*290*870mm	285*290*870mm
	Loading Qty	彩包960PCS/40HQ	彩包960PCS/40HQ	彩包960PCS/40HQ
	Water Dispenser (SL-201W)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W /75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95℃	5L/H 85-95℃	5L/H 85-95℃
	Cooling capacity	0.8L/H 10-15℃	2L/H 5-10℃	2L/H 5-10℃
	NW/GW	7.5/8.5KGS	12/13KGS	14/15KGS
	Product size	310*320*960MM	310*320*960MM	310*320*960MM
	Package size	330*340*980MM	330*340*980MM	330*340*980MM
	Loading Qty	273PCS/20GP	273PCS/20GP	273PCS/20GP
		630PCS/40HQ	630PCS/40HQ	630PCS/40HQ
	Water Dispenser (SL-1596LB)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W /75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95℃	5L/H 85-95℃	5L/H 85-95℃
	Cooling capacity	0.8L/H 10-15℃	2L/H 5-10℃	2L/H 5-10℃
	NW/GW			
	Product size	325*305*970mm	325*305*970mm	325*305*970mm
	Package size	340*325*1010mm	340*325*1010mm	340*325*1010mm
	Loading Qty	270pcs/20GP	270pcs/20GP	270pcs/20GP
		638PCS/40HQ	638PCS/40HQ	638PCS/40HQ
	Water Dispenser (SL-1592L)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W /75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95℃	5L/H 85-95℃	5L/H 85-95℃
	Cooling capacity	0.8L/H 10-15℃	2L/H 5-10℃	2L/H 5-10℃
	NW/GW			
	Product size	320*310*970mm	320*310*970mm	320*310*970mm
	Package size	330*320*1000mm	330*320*1000mm	330*320*1000mm
	Loading Qty	277PCS/20GP	277PCS/20GP	277PCS/20GP
		650PCS/40HQ,600-660之间吧	650PCS/40HQ	650PCS/40HQ

	Water Dispenser (SL-901L)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W /75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95℃	5L/H 85-95℃	5L/H 85-95℃
	Cooling capacity	0.8L/H 10-15℃	2L/H 5-10℃	2L/H 5-10℃
	NW/GW	8.6kg /10.5KG	13.5/14	
	Product size	325*310*105mm	325*310*105mm	325*310*105mm
	Package size	340x320x1080mm	340x320x1080mm	340x320x1080mm
	Loading Qty	238PCS/20GP	238PCS/20GP	238PCS/20GP
		560PCS/40HQ	560PCS/40HQ	560PCS/40HQ
	Water Dispenser (SL-901LB)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W /75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95℃	5L/H 85-95℃	5L/H 85-95℃
	Cooling capacity	0.8L/H 10-15℃	2L/H 5-10℃	2L/H 5-10℃
	NW/GW	7.5/8.5KGS	12/13KGS	14/15KGS
	Product size	315*310*960mm	315*310*960mm	315*310*960mm
	Package size	325x320x980mm	325x320x980mm	325x320x980mm
	Loading Qty	277PCS/20GP	277PCS/20GP	277PCS/20GP
		650PCS/40HQ	650PCS/40HQ	650PCS/40HQ
	Water Dispenser (SL-8800L)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W /75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95℃	5L/H 85-95℃	5L/H 85-95℃
	Cooling capacity	0.8L/H 10-15℃	2L/H 5-10℃	2L/H 5-10℃
	NW/GW	8.6kg /10.5KG	13.5/14	
	Product size	325*310*105mm	325*310*105mm	325*310*105mm
	Package size	340x320x1080mm	340x320x1080mm	340x320x1080mm
	Loading Qty	238PCS/20GP	238PCS/20GP	238PCS/20GP
		560PCS/40HQ	560PCS/40HQ	560PCS/40HQ
	Water Dispenser (SL-880LB)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W /75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95℃	5L/H 85-95℃	5L/H 85-95℃
	Cooling capacity	0.8L/H 10-15℃	2L/H 5-10℃	2L/H 5-10℃
	NW/GW	7.5/8.5KGS	12/13KGS	14/15KGS
	Product size	315*310*960mm	315*310*960mm	315*310*960mm
	Package size	325x320x980mm	325x320x980mm	325x320x980mm
	Loading Qty	277PCS/20GP	277PCS/20GP	277PCS/20GP
		650PCS/40HQ	650PCS/40HQ	650PCS/40HQ

	Water Dispenser (SL-811L)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W /75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95℃	5L/H 85-95℃	5L/H 85-95℃
	Cooling capacity	0.8L/H 10-15℃	2L/H 5-10℃	2L/H 5-10℃
	NW/GW	8.6kg /10.5KG	13.5/14 (13.75KG)	
	Product size	325*310*105mm	325*310*105mm	325*310*105mm
	Package size	340x325x1080mm	340x325x1080mm	340x325x1080mm
	Loading Qty	238PCS/20GP	238PCS/20GP	238PCS/20GP
		560PCS/40HQ, 说装565台	560PCS/40HQ	560PCS/40HQ

	Water Dispenser (SL-802LB)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W /75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95℃	5L/H 85-95℃	5L/H 85-95℃
	Cooling capacity	0.8L/H 10-15℃	2L/H 5-10℃	2L/H 5-10℃
	NW/GW	7.5/8.5KGS	12/13KGS	14/15KGS
	Product size	325*310*960mm	325*310*960mm	325*310*960mm
	Package size	340x320x990mm	340x320x990mm	340x320x990mm
	Loading Qty	277PCS/20GP	277PCS/20GP	277PCS/20GP
		650PCS/40HQ	650PCS/40HQ	650PCS/40HQ

	Water Dispenser (SL-807L)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W /75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95℃	5L/H 85-95℃	5L/H 85-95℃
	Cooling capacity	0.8L/H 10-15℃	2L/H 5-10℃	2L/H 5-10℃
	NW/GW	8.6kg /10.5KG	13.5/14	
	Product size	325*310*105mm	325*310*105mm	325*310*105mm
	Package size	340x325x1080mm	340x325x1080mm	340x325x1080mm
	Loading Qty	238PCS/20GP	238PCS/20GP	238PCS/20GP
		560PCS/40HQ	560PCS/40HQ	560PCS/40HQ

	Water Dispenser (SL-828LB)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W /75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95℃	5L/H 85-95℃	5L/H 85-95℃
	Cooling capacity	0.8L/H 10-15℃	2L/H 5-10℃	2L/H 5-10℃
	NW/GW	7.5/8.5KGS	12/13KGS	14/15KGS
	Product size	325*310*960mm	325*310*960mm	325*310*960mm
	Package size	340x320x990mm	340x320x990mm	340x320x990mm
	Loading Qty	277PCS/20GP	277PCS/20GP	277PCS/20GP
		650PCS/40HQ	650PCS/40HQ	650PCS/40HQ

	Water Dispenser (SL-809L)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W /75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95℃	5L/H 85-95℃	5L/H 85-95℃
	Cooling capacity	0.8L/H 10-15℃	2L/H 5-10℃	2L/H 5-10℃
	NW/GW	8.6kg /10.5KG (电子实际9.1	13.5/14	
	Product size	325*310*105mm	325*310*105mm	325*310*105mm
	Package size	340x325x1080mm	340x325x1080mm	340x325x1080mm
	Loading Qty	238PCS/20GP	238PCS/20GP	238PCS/20GP
		560PCS/40HQ, 说装565台	560PCS/40HQ	560PCS/40HQ
	Water Dispenser (SL-808LB)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W /75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95℃	5L/H 85-95℃	5L/H 85-95℃
	Cooling capacity	0.8L/H 10-15℃	2L/H 5-10℃	2L/H 5-10℃
	NW/GW	7.5/8.5KGS, 实际9.04	12/13KGS	14/15KGS
	Product size	325*310*960mm	325*310*960mm	325*310*960mm
	Package size	340x320x990mm	340x320x990mm	340x320x990mm
	Loading Qty	277PCS/20GP	277PCS/20GP	277PCS/20GP
		650PCS/40HQ	650PCS/40HQ	650PCS/40HQ
	Water Dispenser (SL-810L)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W /75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95℃	5L/H 85-95℃	5L/H 85-95℃
	Cooling capacity	0.8L/H 10-15℃	2L/H 5-10℃	2L/H 5-10℃
	NW/GW	8.6kg /10.5KG	13.5/14	
	Product size	325*310*105mm	325*310*105mm	325*310*105mm
	Package size	340x325x1080mm	340x325x1080mm	340x325x1080mm
	Loading Qty	238PCS/20GP	238PCS/20GP	238PCS/20GP
		560PCS/40HQ	560PCS/40HQ	560PCS/40HQ
	Water Dispenser (SL-800LB)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W /75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95℃	5L/H 85-95℃	5L/H 85-95℃
	Cooling capacity	0.8L/H 10-15℃	2L/H 5-10℃	2L/H 5-10℃
	NW/GW	7.5/8.5KGS	12/13KGS	14/15KGS, 实际14.25
	Product size	315*310*960mm	315*310*960mm	315*310*960mm
	Package size	325x320x990mm	325x320x990mm	325x320x990mm
	Loading Qty	277PCS/20GP	277PCS/20GP	277PCS/20GP
		650PCS/40HQ	650PCS/40HQ	650PCS/40HQ

	Water Dispenser (SL-890LB)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W /75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95℃	5L/H 85-95℃	5L/H 85-95℃
	Cooling capacity	0.8L/H 10-15℃	2L/H 5-10℃	2L/H 5-10℃
	NW/GW	7.5/8.5KGS	12/13KGS	14/15KGS，实际14.25
	Product size	315*310*960mm	315*310*960mm	315*310*960mm
	Package size	330x325x990mm	330x325x990mm	330x325x990mm
	Loading Qty	660PCS/40HQ	660PCS/40HQ	660PCS/40HQ
	Water Dispenser (SL-988L)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W /75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95℃	5L/H 85-95℃	5L/H 85-95℃
	Cooling capacity	0.8L/H 10-15℃	2L/H 5-10℃	2L/H 5-10℃
	NW/GW			
	Product size			
	Package size	295*285*870	295*285*870	295*285*870
	Loading Qty	984PCS/40HQ	984PCS/40HQ	984PCS/40HQ
	Water Dispenser (SL-801LB)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W /75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95℃	5L/H 85-95℃	5L/H 85-95℃
	Cooling capacity	0.8L/H 10-15℃	2L/H 5-10℃	2L/H 5-10℃
	NW/GW	7.5/8.5KGS	12/13KGS	
	Product size	310*320*960MM	310*320*960MM	310*320*960MM
	Package size	330*340*980MM	330*340*980MM	330*340*980MM
	Loading Qty	273PCS/20GP	273PCS/20GP	273PCS/20GP
		630PCS/40HQ	630PCS/40HQ	630PCS/40HQ
	Water Dispenser (SL-805LB)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W /75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95℃	5L/H 85-95℃	5L/H 85-95℃
	Cooling capacity	0.8L/H 10-15℃	2L/H 5-10℃	2L/H 5-10℃
	NW/GW	7.5/8.5KGS	12/13KGS	14/15KGS
	Product size	300*280*950mm	300*280*950mm	300*280*950mm
	Package size	320x320x980mm	320x320x980mm	320x320x980mm
	Loading Qty	291PCS/20GP	291PCS/20GP	291PCS/20GP
		680PCS/40HQ	680PCS/40HQ	680PCS/40HQ

	Water Dispenser (SL-806LB)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W /75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95℃	5L/H 85-95℃	5L/H 85-95℃
	Cooling capacity	0.8L/H 10-15℃	2L/H 5-10℃	2L/H 5-10℃
	NW/GW	7.5/8.5KGS	11.5/12KGS (实际12KG)	14/15KGS
	Product size	300*280*950mm	300*280*950mm	300*280*950mm
	Package size	320x320x980mm	320x320x980mm	320x320x980mm
	Loading Qty	291PCS/20GP	291PCS/20GP	291PCS/20GP
		680PCS/40HQ	680PCS/40HQ	680PCS/40HQ

	Water Dispenser (SL-16LB)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W /75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95℃	5L/H 85-95℃	5L/H 85-95℃
	Cooling capacity	0.8L/H 10-15℃	2L/H 5-10℃	2L/H 5-10℃
	NW/GW	7.5/8.5KGS	11.5/12KGS	14/15KGS
	Product size	315*310*960mm	315*310*960mm	315*310*960mm
	Package size	31.5*31.5*100 确定	31.5*31.5*100	31.5*31.5*100
	Loading Qty	291PCS/20GP	291PCS/20GP	291PCS/20GP
		670PCS/40HQ 650台确定	670PCS/40HQ	670PCS/40HQ

	Water Dispenser (SL-16D)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W /75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95℃	5L/H 85-95℃	5L/H 85-95℃
	Cooling capacity	0.8L/H 10-15℃	2L/H 5-10℃	2L/H 5-10℃
	NW/GW			
	Product size			
	Package size	310*340*970	310*340*970	310*340*970
	Loading Qty	270PCS/20GP	270PCS/20GP	270PCS/20GP
		650PCS/40HQ 650台确定	650PCS/40HQ 650台确定	650PCS/40HQ 650台确定

	Water Dispenser (SL-178LB)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W /75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95℃	5L/H 85-95℃	5L/H 85-95℃
	Cooling capacity	0.8L/H 10-15℃	2L/H 5-10℃	2L/H 5-10℃
	NW/GW	7.5/8.5KGS	12/13KGS	14/15KGS
	Product size	315*310*960mm	315*310*960mm	315*310*960mm
	Package size	320x320x980mm	320x320x980mm	320x320x980mm
	Loading Qty	291PCS/20GP	291PCS/20GP	291PCS/20GP
		670PCS/40HQ	670PCS/40HQ	670PCS/40HQ

	Water Dispenser (SL-827LB)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W /75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	0.8L/H 10-15°C	2L/H 5-10°C	2L/H 5-10°C
	NW/GW	6.2KG/7.2kg	12/12.3 ok	17.0/18.0
	Product size	325*310*960mm	325*310*960mm	325*310*960mm
	Package size	340x320x980mm	340x320x980mm	340x320x980mm
	Loading Qty	277PCS/20GP	277PCS/20GP	277PCS/20GP
		650PCS/40HQ	650PCS/40HQ	650PCS/40HQ
	Water Dispenser (SL-1708WG)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W /75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	0.8L/H 10-15°C	2L/H 5-10°C	2L/H 5-10°C
	NW/GW	7.5/8.5KGS	12/13KGS	14/15KGS
	Product size	310*320*960MM	310*320*960MM	310*320*960MM
	Package size	330*340*980MM	330*340*980MM	330*340*980MM
	Loading Qty	273PCS/20GP	273PCS/20GP	273PCS/20GP
		630PCS/40HQ	630PCS/40HQ	630PCS/40HQ
	Water Dispenser (SL-89L)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W /75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	0.8L/H 10-15°C	2L/H 5-10°C	2L/H 5-10°C
	NW/GW	6.2KG/7.2kg	16.0/17.0	17.0/18.0
	Product size	325*310*960mm	325*310*960mm	325*310*960mm
	Package size	340*320*990mm	340*320*990mm	340*320*990mm
	Loading Qty	277PCS/20GP	277PCS/20GP	277PCS/20GP
		650PCS/40HQ	650PCS/40HQ	650PCS/40HQ
	Water Dispenser (SL-26L)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W /75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	0.8L/H 10-15°C	2L/H 5-10°C	2L/H 5-10°C
	NW/GW	6.2KG/7.2kg	16.0/17.0	17.0/18.0
	Product size	325*310*960mm	325*310*960mm	325*310*960mm
	Package size	340x320x980mm	340x320x980mm	340x320x980mm
	Loading Qty	277PCS/20GP	277PCS/20GP	277PCS/20GP
		650PCS/40HQ	650PCS/40HQ	650PCS/40HQ

	Water Dispenser (SL-801L)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W /75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	0.8L/H 10-15°C	2L/H 5-10°C	2L/H 5-10°C
	NW/GW	6.2KG/7.2kG	15.5KG/ 16.5kG	15.5KG/ 16.5kG
	Product size	325*310*960mm	325*310*960mm	325*310*960mm
	Package size	340x320x980mm	340x320x980mm	340x320x980mm
	Loading Qty	277PCS/20GP	277PCS/20GP	277PCS/20GP
		650PCS/40HQ	650PCS/40HQ	650PCS/40HQ

	Water Dispenser (SL-812L)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W /75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	0.8L/H 10-15°C	2L/H 5-10°C	2L/H 5-10°C
	NW/GW	6.2KG/7.2kG	13.0/14.0	15.0/16.0
	Product size	325*310*960mm	325*310*960mm	325*310*960mm
	Package size	340x320x990mm	340x320x990mm	340x320x990mm
	Loading Qty	277PCS/20GP	277PCS/20GP	277PCS/20GP
		650PCS/40HQ	650PCS/40HQ	650PCS/40HQ

	Water Dispenser (SL-818L)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W /75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	0.8L/H 10-15°C	2L/H 5-10°C	2L/H 5-10°C
	NW/GW	7.5/8.5KGS	12/13KGS	14/15KGS
	Product size	305*300*846mm	305*300*846mm	305*300*846mm
	Package size	325*315*870mm	325*315*870mm	325*315*870mm
	Loading Qty			
		770PCS/40HQ	770PCS/40HQ	770PCS/40HQ

	Water Dispenser (SL-1416)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal		With fridge
	Heating/Cooling power	550W /75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	0.8L/H 10-15°C	2L/H 5-10°C	2L/H 5-10°C
	NW/GW	7.5/8.5KGS	12/13KGS	14/15KGS
	Product size	310*320*960MM	310*320*960MM	310*320*960MM
	Package size	330*340*980MM	330*340*980MM	330*340*980MM
	Loading Qty	273PCS/20GP	273PCS/20GP	273PCS/20GP
		630PCS/40HQ	630PCS/40HQ	630PCS/40HQ

	Water Dispenser (SL-1526)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W /75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95℃	5L/H 85-95℃	5L/H 85-95℃
	Cooling capacity	0.8L/H 10-15℃	2L/H 5-10℃	2L/H 5-10℃
	NW/GW	7.5/8.5KGS	12/13KGS	14/15KGS
	Product size	310*320*960MM	310*320*960MM	310*320*960MM
	Package size	330*340*980MM	330*340*980MM	330*340*980MM
	Loading Qty	273PCS/20GP	273PCS/20GP	273PCS/20GP
		630PCS/40HQ	630PCS/40HQ	630PCS/40HQ
	Water Dispenser (SL-1512)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W /75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95℃	5L/H 85-95℃	5L/H 85-95℃
	Cooling capacity	0.8L/H 10-15℃	2L/H 5-10℃	2L/H 5-10℃
	NW/GW	7.5/8.5KGS	12/13KGS	14/15KGS (实际13.25)
	Product size	310*320*960MM	310*320*960MM	310*320*960MM
	Package size	330*340*980MM	330*340*980MM	330*340*980MM
	Loading Qty	273PCS/20GP	273PCS/20GP	273PCS/20GP
		630PCS/40HQ	630PCS/40HQ	630PCS/40HQ
	Water Dispenser (SL-1038WG)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W /75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95℃	5L/H 85-95℃	5L/H 85-95℃
	Cooling capacity	0.8L/H 10-15℃	2L/H 5-10℃	2L/H 5-10℃
	NW/GW	7.5/8.5KGS	12/13KGS	14/15KGS
	Product size	310*320*960MM	310*320*960MM	310*320*960MM
	Package size	330*340*980MM	330*340*980MM	330*340*980MM
	Loading Qty	273PCS/20GP	273PCS/20GP	273PCS/20GP
		630PCS/40HQ	630PCS/40HQ	630PCS/40HQ
	Water Dispenser (SL-1026W)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W /75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95℃	5L/H 85-95℃	5L/H 85-95℃
	Cooling capacity	0.8L/H 10-15℃	2L/H 5-10℃	2L/H 5-10℃
	NW/GW	7.5/8.5KGS	12/13KGS	14/15KGS
	Product size	310*320*960MM	310*320*960MM	310*320*960MM
	Package size	330*340*980MM	330*340*980MM	330*340*980MM
	Loading Qty	273PCS/20GP	273PCS/20GP	273PCS/20GP
		630PCS/40HQ	630PCS/40HQ	630PCS/40HQ

	Water Dispenser (SL-16L/H)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W /75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	0.8L/H 10-15°C	2L/H 5-10°C	2L/H 5-10°C
	NW/GW	7.5/8.5KGS	12/13KGS	14/15KGS
	Product size	310*320*960MM	310*320*960MM	310*320*960MM
	Package size	330*340*980MM	330*340*980MM	330*340*980MM
	Loading Qty	273PCS/20GP	273PCS/20GP	273PCS/20GP
		630PCS/40HQ	630PCS/40HQ	630PCS/40HQ
	Water Dispenser (SL-W27)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W /75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	0.8L/H 10-15°C	2L/H 5-10°C	2L/H 5-10°C
	NW/GW	7.5/8.5KGS	12/13KGS	14/15KGS
	Product size	310*320*960MM	310*320*960MM	310*320*960MM
	Package size	330*340*980MM	330*340*980MM	330*340*980MM
	Loading Qty	273PCS/20GP	273PCS/20GP	273PCS/20GP
		630PCS/40HQ	630PCS/40HQ	630PCS/40HQ
	Water Dispenser (SL-W28)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W /75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	0.8L/H 10-15°C	2L/H 5-10°C	2L/H 5-10°C
	NW/GW	7.5/8.5KGS	12/13KGS	14/15KGS
	Product size	310*320*960MM	310*320*960MM	310*320*960MM
	Package size	330*340*980MM	330*340*980MM	330*340*980MM
	Loading Qty	273PCS/20GP	273PCS/20GP	273PCS/20GP
		630PCS/40HQ	630PCS/40HQ	630PCS/40HQ
	Water Dispenser (SL-W35)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W /75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	0.8L/H 10-15°C	2L/H 5-10°C	2L/H 5-10°C
	NW/GW	7.5/8.5KGS	12/13KGS	14/15KGS
	Product size	310*320*960MM	310*320*960MM	310*320*960MM
	Package size	330*340*980MM	330*340*980MM	330*340*980MM
	Loading Qty	273PCS/20GP	273PCS/20GP	273PCS/20GP
		630PCS/40HQ	630PCS/40HQ	630PCS/40HQ

	Water Dispenser (SL-301)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm	Hot & Cold	Hot & Cold
	Cooling method	/	Electronic cooling	Compressor cooling
	Cabinet	Normal	Normal	Normal
	Heating/Cooling power	550W	550W /75W	550W /90W
	Heating capacity	5L/H 85-95℃	5L/H 85-95℃	5L/H 85-95℃
	Cooling capacity	/	0.8 L/H 10-15℃	2L/H 5-10℃
	NW/GW	5KG/5.5KG	5KG/5.5KG	
	Product size			
	Package size	320*345*945mm	320*345*945mm	320*345*945mm
	Loading Qty	665PCS/40HQ	665PCS/40HQ	665PCS/40HQ
	Water Dispenser (SL-F900)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm	Hot & Cold	Hot & Cold
	Cooling method	/	Electronic cooling	Compressor cooling
	Cabinet	Normal	Normal	Normal
	Heating/Cooling power	550W	550W /65W	550W /90W
	Heating capacity	5L/H 85-95℃	5L/H 85-95℃	5L/H 85-95℃
	Cooling capacity	/	0.8 L/H 10-15℃	2L/H 5-10℃
	NW/GW	11.3 (kg) /12.5 (kg)	11.3 (kg) /12.5 (kg)	
	Product size			
	Package size	上置式370*320*1060/下置	370*320*1060/370*320*1	370*320*1060/370*320*1
	Loading Qty	550PCS/40HQ	550PCS/40HQ	
	Water Dispenser (SL-3012)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm	Hot & Cold	Hot & Cold
	Cooling method	/	Electronic cooling	Compressor cooling
	Cabinet	Normal	Normal	Normal
	Heating/Cooling power	550W	550W /75W	550W /90W
	Heating capacity	5L/H 85-95℃	5L/H 85-95℃	5L/H 85-95℃
	Cooling capacity	/	0.8 L/H 10-15℃	2L/H 5-10℃
	NW/GW	4.3kgs/5.3kgs	5KG/5.5KG	
	Product size			
	Package size	320*320*850mm	320*345*945mm	320*345*945mm
	Loading Qty			
	Water Dispenser (SL-TY9)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm	Hot & Cold	Hot & Cold
	Cooling method	/	Electronic cooling	Compressor cooling
	Cabinet	Normal	Normal	Normal
	Heating/Cooling power	550W	550W /75W	550W /90W
	Heating capacity	5L/H 85-95℃	5L/H 85-95℃	5L/H 85-95℃
	Cooling capacity	/	0.8 L/H 10-15℃	2L/H 5-10℃
	NW/GW	4.6KG5.6kG	4.6KG5.6kG	
	Product size			
	Package size	32*32*96CM	32*32*96CM	32*32*96CM
	Loading Qty	280PCS/20FT	280PCS/20FT	280PCS/20FT
		676PCS/40HQ	676PCS/40HQ	676PCS/40HQ

	Water Dispenser (SL-TY8)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm	Hot & Cold	Hot & Cold
	Cooling method	/	Electronic cooling	Compressor cooling
	Cabinet	Normal	Normal	Normal
	Heating/Cooling power	550W	550W /75W	550W /90W
	Heating capacity	5L/H 85-95℃	5L/H 85-95℃	5L/H 85-95℃
	Cooling capacity	/	0.8 L/H 10-15℃	2L/H 5-10℃
	NW/GW	4.3KG/5.3kG	4.3KG/5.3kG	
	Product size			
	Package size	32*32*85CM	32*32*85CM	32*32*85CM
	Loading Qty	360PCS/20FT	360PCS/20FT	360PCS/20FT
		850PCS/40HQ	850PCS/40HQ	850PCS/40HQ

	Water Dispenser (SL-TY6)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm	Hot & Cold	Hot & Cold
	Cooling method	/	Electronic cooling	Compressor cooling
	Cabinet	Normal	Normal	Normal
	Heating/Cooling power	550W	550W /75W	550W /90W
	Heating capacity	5L/H 85-95℃	5L/H 85-95℃	5L/H 85-95℃
	Cooling capacity	/	0.8 L/H 10-15℃	2L/H 5-10℃
	NW/GW	4.6KG5.6kG	4.6KG5.6kG	
	Product size			
	Package size	32*32*96CM	32*32*96CM	32*32*96CM
	Loading Qty	280PCS/20FT	280PCS/20FT	280PCS/20FT
		676PCS/40HQ	676PCS/40HQ	676PCS/40HQ

	Water Dispenser (SL-TY101)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm	Hot & Cold	Hot & Cold
	Cooling method	/	Electronic cooling	Compressor cooling
	Cabinet	Normal	Normal	Normal
	Heating/Cooling power	550W	550W /75W	550W /90W
	Heating capacity	5L/H 85-95℃	5L/H 85-95℃	5L/H 85-95℃
	Cooling capacity	/	0.8 L/H 10-15℃	2L/H 5-10℃
	NW/GW	6.2KG/7.2kG, 实际8.5kg	6.2KG/7.2kG	
	Product size			
	Package size	33*34*98CM ok	33*34*98CM	33*34*98CM
	Loading Qty	280PCS/20FT	280PCS/20FT	280PCS/20FT
		650PCS/40HQ	650PCS/40HQ	650PCS/40HQ

	Water Dispenser (SL-TY226)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm	Hot & Cold	Hot & Cold
	Cooling method	/	Electronic cooling	Compressor cooling
	Cabinet	Normal	Normal	Normal
	Heating/Cooling power	550W	550W /75W	550W /90W
	Heating capacity	5L/H 85-95℃	5L/H 85-95℃	5L/H 85-95℃
	Cooling capacity	/	0.8 L/H 10-15℃	2L/H 5-10℃
	NW/GW	5.3KG/6.3kG 实际毛重5.3KG	5.3KG/6.3kG	
	Product size			
	Package size	32*32*96CM	32*32*96CM	32*32*96CM
	Loading Qty	280PCS/20FT	280PCS/20FT	280PCS/20FT
		676PCS/40HQ	676PCS/40HQ	676PCS/40HQ

	Water Dispenser (SL-TY227)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm	Hot & Cold	Hot & Cold
	Cooling method	/	Electronic cooling	Compressor cooling
	Cabinet	Normal	Normal	Normal
	Heating/Cooling power	550W	550W /75W	550W /90W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	/	0.8 L/H 10-15°C	2L/H 5-10°C
	NW/GW	4.3KG/5.3kG	4.3KG/5.3kG	
	Product size			
	Package size	32*32*85CM	32*32*85CM	32*32*85CM
	Loading Qty	360PCS/20FT	360PCS/20FT	360PCS/20FT
		960PCS/40HQ	960PCS/40HQ	960PCS/40HQ
	Water Dispenser (SL-W42B)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W /75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	0.8L/H 10-15°C	2L/H 5-10°C	2L/H 5-10°C
	NW/GW		16.0/17.0;17.0/18.0	16.0/17.0;17.0/18.0
	Product size	31*32*96	31*32*96	31*32*96
	Package size	330*340*980(mm)	330*340*980(mm)	330*340*980(mm)
	Loading Qty	238PCS/20FT	238PCS/20FT	238PCS/20FT
		630PCS/40HQ	630PCS/40HQ	630PCS/40HQ
	Water Dispenser (SL-W42)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W /75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	0.8L/H 10-15°C	2L/H 5-10°C	2L/H 5-10°C
	NW/GW		16.0/17.0;17.0/18.0	16.0/17.0;17.0/18.0
	Product size	31*32*96	31*32*96	31*32*96
	Package size	330*340*980(mm)	330*340*980(mm)	330*340*980(mm)
	Loading Qty	238PCS/20FT	238PCS/20FT	238PCS/20FT
		630PCS/40HQ	630PCS/40HQ	630PCS/40HQ
	Water Dispenser (SL-1131)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W /75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	0.8L/H 10-15°C	2L/H 5-10°C	2L/H 5-10°C
	NW/GW	6.2KG/7.2kG	13.0/14.0	;15.0/16.0
	Product size	310*310*950(mm)	310*310*950(mm)	310*310*950(mm)
	Package size	340*330*980(mm)	340*330*980(mm)	340*330*980(mm)
	Loading Qty	260PCS/20FT	260PCS/20FT	260PCS/20FT
		620PCS/40HQ	620PCS/40HQ	620PCS/40HQ

	Water Dispenser (SL-1132)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W /75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95℃	5L/H 85-95℃	5L/H 85-95℃
	Cooling capacity	0.8L/H 10-15℃	2L/H 5-10℃	2L/H 5-10℃
	NW/GW		13.0/14.0	;15.0/16.0(Kgs)
	Product size	310*310*950(mm)	310*310*950(mm)	310*310*950(mm)
	Package size	330*320*980(mm)	330*320*980(mm)	330*320*980(mm)
	Loading Qty	260PCS/20FT	260PCS/20FT	260PCS/20FT
		650PCS/40HQ	650PCS/40HQ	650PCS/40HQ

	Water Dispenser (SL-304)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm	Hot & Cold	Hot & Cold
	Cooling method	/	Electronic cooling	Compressor cooling
	Cabinet	Normal	Normal	Normal
	Heating/Cooling power	550W	550W /75W	550W /90W
	Heating capacity	5L/H 85-95℃	5L/H 85-95℃	5L/H 85-95℃
	Cooling capacity	/	0.8 L/H 10-15℃	2L/H 5-10℃
	NW/GW	4.6KG5.6kG	4.6KG5.6kG	
	Product size	270*230*820cm	270*230*820cm	270*230*820cm
	Package size	30*26*85CM	30*26*85CM	30*26*85CM
	Loading Qty	420PCS/20FT	420PCS/20FT	420PCS/20FT
		1025PCS/40HQ	1025PCS/40HQ	1025PCS/40HQ

	Water Dispenser (SL-1199-2)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm	Hot & Cold	Hot & Cold
	Cooling method	/	Electronic cooling	Compressor cooling
	Cabinet	Normal	Normal	Normal
	Heating/Cooling power	550W	550W /75W	550W /90W
	Heating capacity	5L/H 85-95℃	5L/H 85-95℃	5L/H 85-95℃
	Cooling capacity	/	0.8 L/H 10-15℃	2L/H 5-10℃
	NW/GW	6.5/7.5KGS	7.5/8.5KGS	12/13KGS
	Product size	300*290*960MM	300*290*960MM	300*290*960MM
	Package size	330*330*980MM	330*330*980MM	330*330*980MM
	Loading Qty	280PCS/20GP	280PCS/20GP	280PCS/20GP
		658PCS/40HQ	658PCS/40HQ	658PCS/40HQ

	Water Dispenser (SL-1199-3)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Cold	Hot & Cold	Hot & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W/75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95℃	5L/H 85-95℃	5L/H 85-95℃
	Cooling capacity	0.8 L/H 10-15℃	2L/H 5-10℃	2L/H 5-10℃
	NW/GW	9.5/10.5KGS, 实际9.2kg	14/15KGS	15/16KGS
	Product size	310*305*1000MM	310*305*1000MM	310*305*1000MM
	Package size	340*330*1020MM	340*330*1020MM	340*330*1020MM
	Loading Qty	238PCS/20GP	238PCS/20GP	238PCS/20GP
		558PCS/40HQ	558PCS/40HQ	558PCS/40HQ

	Water Dispenser (SL-2088-3)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm	Hot & Cold	Hot & Cold
	Cooling method	/	Electronic cooling	Compressor cooling
	Cabinet	Normal	Normal	Normal
	Heating/Cooling power	550W	550W /75W	550W /90W
	Heating capacity	5L/H 85-95℃	5L/H 85-95℃	5L/H 85-95℃
	Cooling capacity	/	0.8 L/H 10-15℃	2L/H 5-10℃
	NW/GW	8.5/9.5KGS	9.5/10.5KGS （实际10.4）	14/15KGS
	Product size	320*315*1005MM	320*315*1005MM	320*315*1005MM
	Package size	36.5*36.5*106 (ok)	36.5*36.5*106	36.5*36.5*106
	Loading Qty	192PCS/20GP	192PCS/20GP	192PCS/20GP
		474PCS/40HQ， 现在装箱460	474PCS/40HQ	474PCS/40HQ
	Water Dispenser (SL-1176)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Cold	Hot & Cold	Hot & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W/75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95℃	5L/H 85-95℃	5L/H 85-95℃
	Cooling capacity	0.8 L/H 10-15℃	2L/H 5-10℃	2L/H 5-10℃
	NW/GW	9.5/10.5KGS	14/15KGS	15/16KGS
	Product size	310*305*1000MM	310*305*1000MM	310*305*1000MM
	Package size	340*330*1020MM	340*330*1020MM	340*330*1020MM
	Loading Qty	238PCS/20GP	238PCS/20GP	238PCS/20GP
			558PCS/40HQ	558PCS/40HQ
	Water Dispenser (SL-1196)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Cold	Hot & Cold	Hot & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W/75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95℃	5L/H 85-95℃	5L/H 85-95℃
	Cooling capacity	0.8 L/H 10-15℃	2L/H 5-10℃	2L/H 5-10℃
	NW/GW	9.5/10.5KGS	14/15KGS	15/16KGS
	Product size	310*305*1000MM	310*305*1000MM	310*305*1000MM
	Package size	340*330*1020MM	340*330*1020MM	340*330*1020MM
	Loading Qty	238PCS/20GP	238PCS/20GP	238PCS/20GP
		558PCS/40HQ	558PCS/40HQ	558PCS/40HQ
	Water Dispenser (SL-1911LB)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W /75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95℃	5L/H 85-95℃	5L/H 85-95℃
	Cooling capacity	0.8L/H 10-15℃	2L/H 5-10℃	2L/H 5-10℃
	NW/GW	6.8KG/7.8kG	12/13KGS	14/15KGS
	Product size	300*280*950mm	300*280*950mm	300*280*950mm
	Package size	320x320x980mm	320x320x980mm	320x320x980mm
	Loading Qty	291PCS/20GP	291PCS/20GP	291PCS/20GP
		680PCS/40HQ	680PCS/40HQ	680PCS/40HQ

	Water Dispenser (SL-1711LB)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W /75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	0.8L/H 10-15°C	2L/H 5-10°C	2L/H 5-10°C
	NW/GW			
	Product size	300*280*950mm	300*280*950mm	300*280*950mm
	Package size	320x320x980mm	320x320x980mm	320x320x980mm
	Loading Qty	291PCS/20GP	291PCS/20GP	291PCS/20GP
		680PCS/40HQ	680PCS/40HQ	680PCS/40HQ

	Water Dispenser (SL-1811L)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W /75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	0.8L/H 10-15°C	2L/H 5-10°C	2L/H 5-10°C
	NW/GW		17.6/18.5(Kgs)	17.6/18.5(Kgs)
	Product size	300*280*950mm	300*280*950mm	300*280*950mm
	Package size	320x320x980mm	320x320x980mm	320x320x980mm
	Loading Qty	291PCS/20GP	291PCS/20GP	291PCS/20GP
		680PCS/40HQ	680PCS/40HQ	680PCS/40HQ

	Water Dispenser (SL-197L)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W /75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	0.8L/H 10-15°C	2L/H 5-10°C	2L/H 5-10°C
	NW/GW		17.6/18.5(Kgs)	17.6/18.5(Kgs)
	Product size	350*335*107mm	350*335*107mm	350*335*107mm
	Package size	385*370*1120mm	385*370*1120mm	385*370*1120mm
	Loading Qty			
		446PCS/40HQ	446PCS/40HQ	446PCS/40HQ

	Water Dispenser (SL-1971L)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W /75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	0.8L/H 10-15°C	2L/H 5-10°C	2L/H 5-10°C
	NW/GW		17.6/18.5(Kgs)	17.6/18.5(Kgs)
	Product size	350*335*107mm	350*335*107mm	350*335*107mm
	Package size	385*370*1120mm	385*370*1120mm	385*370*1120mm
	Loading Qty			
		446PCS/40HQ	446PCS/40HQ	446PCS/40HQ

	Water Dispenser (SL-1972L)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W /75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	0.8L/H 10-15°C	2L/H 5-10°C	2L/H 5-10°C
	NW/GW		17.6/18.5(Kgs)	17.6/18.5(Kgs)
	Product size	350*335*107mm	350*335*107mm	350*335*107mm
	Package size	385*370*1120mm 确定	385*370*1120mm	385*370*1120mm
	Loading Qty			
		446PCS/40HQ 确定	446PCS/40HQ	446PCS/40HQ
	Water Dispenser (SL-)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W /75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	0.8L/H 10-15°C	2L/H 5-10°C	2L/H 5-10°C
	NW/GW		17.6/18.5(Kgs)	17.6/18.5(Kgs)
	Product size	300*280*950mm	300*280*950mm	300*280*950mm
	Package size			
	Loading Qty			
	Water Dispenser (SL-201)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W /75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	0.8L/H 10-15°C	2L/H 5-10°C	2L/H 5-10°C
	NW/GW	6.2KG/7.2kG	15.5KG/ 16.5kG	
	Product size			
	Package size	315*315*1000MM	315*315*1000MM	315*315*1000MM
	Loading Qty			
		680PCS/40HQ	680PCS/40HQ	680PCS/40HQ
	Water Dispenser (SL-)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W /75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	0.8L/H 10-15°C	2L/H 5-10°C	2L/H 5-10°C
	NW/GW			
	Product size			
	Package size			
	Loading Qty			

	Water Dispenser (SL-TY126)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm	Hot & Cold	Hot & Cold
	Cooling method	/	Electronic cooling	Compressor cooling
	Cabinet	Normal	Normal	Normal
	Heating/Cooling power	550W	550W /75W	550W /90W
	Heating capacity	5L/H 85-95℃	5L/H 85-95℃	5L/H 85-95℃
	Cooling capacity	/	0.8 L/H 10-15℃	2L/H 5-10℃
	NW/GW	6.5KG/7.5kG	6.5KG/7.5kG	
	Product size			
	Package size	33*33*99CM	33*33*99CM	33*33*99CM
	Loading Qty	280PCS/20FT	280PCS/20FT	280PCS/20FT
		650PCS/40HQ	650PCS/40HQ	650PCS/40HQ
	Water Dispenser (SL-TY125)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm	Hot & Cold	Hot & Cold
	Cooling method	/	Electronic cooling	Compressor cooling
	Cabinet	Normal	Normal	Normal
	Heating/Cooling power	550W	550W /75W	550W /90W
	Heating capacity	5L/H 85-95℃	5L/H 85-95℃	5L/H 85-95℃
	Cooling capacity	/	0.8 L/H 10-15℃	2L/H 5-10℃
	NW/GW	6.5KG/7.5kG	6.5KG/7.5kG	
	Product size			
	Package size	33*33*99CM	33*33*99CM	33*33*99CM
	Loading Qty	280PCS/20FT	280PCS/20FT	280PCS/20FT
		650PCS/40HQ	650PCS/40HQ	650PCS/40HQ
	Water Dispenser (SL-TY128)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W /75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95℃	5L/H 85-95℃	5L/H 85-95℃
	Cooling capacity	0.8L/H 10-15℃	2L/H 5-10℃	2L/H 5-10℃
	NW/GW	6.8KG/7.8kG (实际7.8)	6.8KG/7.8kG	14/15KGS
	Product size	31*30.5*97	31*30.5*97	31*30.5*97
	Package size	33*33*100CM (ok)	33*33*100CM	33*33*100CM
	Loading Qty	280PCS/20FT	280PCS/20FT	280PCS/20FT
		650PCS/40HQ	650PCS/40HQ	650PCS/40HQ
	Water Dispenser (SL-TY109)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W /75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95℃	5L/H 85-95℃	5L/H 85-95℃
	Cooling capacity	0.8L/H 10-15℃	2L/H 5-10℃	2L/H 5-10℃
	NW/GW	6. 15KG/7.15kG	6. 15KG/7.15kG	14/15KGS
	Product size			
	Package size	33*33*100CM	33*33*100CM	33*33*100CM
	Loading Qty	280PCS/20FT	280PCS/20FT	280PCS/20FT
		650PCS/40HQ	650PCS/40HQ	650PCS/40HQ

	Water Dispenser (SL-TY228)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W /75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	0.8L/H 10-15°C	2L/H 5-10°C	2L/H 5-10°C
	NW/GW	5.8KG/6.8kG	5.8KG/6.8kG	14/15KGS
	Product size	33*32*100	33*32*100	33*32*100
	Package size	33*33*99CM	33*33*99CM	33*33*99CM
	Loading Qty	280PCS/20FT	280PCS/20FT	280PCS/20FT
		650PCS/40HQ	650PCS/40HQ	650PCS/40HQ
	Water Dispenser (SL-TY329)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W /75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	0.8L/H 10-15°C	2L/H 5-10°C	2L/H 5-10°C
	NW/GW	6.2KG/7.2kG	6.2KG/7.2kG	
	Product size			
	Package size	35*36*101CM	35*36*101CM	35*36*101CM
	Loading Qty	200PCS/20FT	200PCS/20FT	200PCS/20FT
		650PCS/40HQ	650PCS/40HQ	650PCS/40HQ
	Water Dispenser (SL-568L)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	
	Function	Hot & Warm & Cold	Hot & Warm & Cold	
	Cooling method	Electronic cooling	Compressor cooling	
	Cabinet	Normal	Normal	
	Heating/Cooling power	550W /75W	550W /90W	
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	
	Cooling capacity	0.8L/H 10-15°C	2L/H 5-10°C	
	NW/GW	6.2KG/7.2kG	6.2KG/7.2kG	
	Product size	320*315*1000	320*315*1000	
	Package size			
	Loading Qty			
	Water Dispenser (SL-1719)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W /75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	0.8L/H 10-15°C	2L/H 5-10°C	2L/H 5-10°C
	NW/GW	6.2KG/7.2kG	6.2KG/7.2kG	
	Product size			
	Package size	32*33*98CM	32*33*98CM	32*33*98CM
	Loading Qty			
		466PCS/40HQ	466PCS/40HQ	466PCS/40HQ

	Water Dispenser (SL-828)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm	Hot & Cold	Hot & Cold
	Cooling method	/	Electronic cooling	Compressor cooling
	Cabinet	Normal	Normal	Normal
	Heating/Cooling power	550W	550W /75W	550W /90W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	/	0.8 L/H 10-15°C	2L/H 5-10°C
	NW/GW	6.8KG/7.8kG	6.8KG/7.8kG	
	Product size	310*280*850	310*280*850	310*280*850
	Package size	32*32*87CM	32*32*87CM	32*32*87CM
	Loading Qty	360PCS/20FT	360PCS/20FT	360PCS/20FT
		850PCS/40HQ	850PCS/40HQ	850PCS/40HQ
	Water Dispenser (SL-1003S)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W /75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	0.8L/H 10-15°C	2L/H 5-10°C	2L/H 5-10°C
	NW/GW	6.7KG/ OK	11/12KGS	11/12KGS
	Product size			
	Package size	295*320*875mm	295*320*875mm	295*320*875mm
	Loading Qty	350PCS/20FT	350PCS/20FT	350PCS/20FT
		818PCS/40HQ	818PCS/40HQ	818PCS/40HQ
	Water Dispenser (SL-1004S)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W /75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	0.8L/H 10-15°C	2L/H 5-10°C	2L/H 5-10°C
	NW/GW	6.5KG/6.7KG	11/12KGS	11/12KGS
	Product size			
	Package size	295*320*875mm	295*320*875mm	295*320*875mm
	Loading Qty	350PCS/20FT	350PCS/20FT	350PCS/20FT
		818PCS/40HQ	818PCS/40HQ	818PCS/40HQ
	Water Dispenser (SL-1005S)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W /75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	0.8L/H 10-15°C	2L/H 5-10°C	2L/H 5-10°C
	NW/GW		11/12KGS	11/12KGS
	Product size			
	Package size	295*320*875mm	295*320*875mm	295*320*875mm
	Loading Qty	350PCS/20FT	350PCS/20FT	350PCS/20FT
		818PCS/40HQ	818PCS/40HQ	818PCS/40HQ

	Water Dispenser (SL-1006S)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W /75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	0.8L/H 10-15°C	2L/H 5-10°C	2L/H 5-10°C
	NW/GW		11/12KGS	11/12KGS
	Product size			
	Package size	295*320*875mm	295*320*875mm	295*320*875mm
	Loading Qty	350PCS/20FT	350PCS/20FT	350PCS/20FT
		818PCS/40HQ	818PCS/40HQ	818PCS/40HQ

	Water Dispenser (SL-1007S)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W /75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	0.8L/H 10-15°C	2L/H 5-10°C	2L/H 5-10°C
	NW/GW		11/12KGS	11/12KGS
	Product size			
	Package size	295*320*875mm	295*320*875mm	295*320*875mm
	Loading Qty	350PCS/20FT	350PCS/20FT	350PCS/20FT
		818PCS/40HQ	818PCS/40HQ	818PCS/40HQ

	Water Dispenser (SL-1011S/SL-1011S-X3)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W /75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	0.8L/H 10-15°C	2L/H 5-10°C	2L/H 5-10°C
	NW/GW		12/13KGS	12/13KGS
	Product size			
	Package size	320*330*990mm	320*330*990mm	320*330*990mm
	Loading Qty	272PCS/20FT	272PCS/20FT	272PCS/20FT
		665PCS/40HQ	665PCS/40HQ	665PCS/40HQ

	Water Dispenser (SL-1013S)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W /75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	0.8L/H 10-15°C	2L/H 5-10°C	2L/H 5-10°C
	NW/GW		12/13KGS	12/13KGS
	Product size			
	Package size	320*330*990mm	320*330*990mm	320*330*990mm
	Loading Qty	272PCS/20FT	272PCS/20FT	272PCS/20FT
		665PCS/40HQ	665PCS/40HQ	665PCS/40HQ

	Water Dispenser (SL-1014S)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W /75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	0.8L/H 10-15°C	2L/H 5-10°C	2L/H 5-10°C
	NW/GW		12/13KGS	12/13KGS
	Product size			
	Package size	320*330*990mm	320*330*990mm	320*330*990mm
	Loading Qty	272PCS/20FT	272PCS/20FT	272PCS/20FT
		665PCS/40HQ	665PCS/40HQ	665PCS/40HQ

	Water Dispenser (SL-1012S)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W /75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	0.8L/H 10-15°C	2L/H 5-10°C	2L/H 5-10°C
	NW/GW		12.3/14.2KGS	12.3/14.2KGS
	Product size			
	Package size	360*370*1040mm	360*370*1040mm	360*370*1040mm
	Loading Qty	200PCS/20FT	200PCS/20FT	200PCS/20FT
		456PCS/40HQ	456PCS/40HQ	456PCS/40HQ

	Water Dispenser (SL-1017S)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W /75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	0.8L/H 10-15°C	2L/H 5-10°C	2L/H 5-10°C
	NW/GW	11.5/12.5KGS	11.5/12.5KGS	11.5/12.5KGS
	Product size			
	Package size	330*320*990	330*320*990	330*320*990
	Loading Qty	272PCS/20FT	272PCS/20FT	272PCS/20FT
		665PCS/40HQ	665PCS/40HQ	665PCS/40HQ

	Water Dispenser (SL-1018S)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W /75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	0.8L/H 10-15°C	2L/H 5-10°C	2L/H 5-10°C
	NW/GW	11.5/12.5KGS	11.5/12.5KGS	11.5/12.5KGS
	Product size			
	Package size	330*320*990	330*320*990	330*320*990
	Loading Qty	272PCS/20FT	272PCS/20FT	272PCS/20FT
		665PCS/40HQ	665PCS/40HQ	665PCS/40HQ

	Water Dispenser (SL-1019S)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W /75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	0.8L/H 10-15°C	2L/H 5-10°C	2L/H 5-10°C
	NW/GW	11.5/12.5KGS	11.5/12.5KGS	11.5/12.5KGS
	Product size			
	Package size	330*320*990	330*320*990	330*320*990
	Loading Qty	272PCS/20FT	272PCS/20FT	272PCS/20FT
		665PCS/40HQ	665PCS/40HQ	665PCS/40HQ

	Water Dispenser (SL-1001S)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W /75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	0.8L/H 10-15°C	2L/H 5-10°C	2L/H 5-10°C
	NW/GW		12.5/14KGS	12.5/14KGS
	Product size			
	Package size	360*345*1065mm	360*345*1065mm	360*345*1065mm
	Loading Qty	200PCS/20FT	200PCS/20FT	200PCS/20FT
		462PCS/40HQ	462PCS/40HQ	462PCS/40HQ

	Water Dispenser (SL-1020S)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W /75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	0.8L/H 10-15°C	2L/H 5-10°C	2L/H 5-10°C
	NW/GW		12.3/14.2KGS	12.3/14.2KGS
	Product size			
	Package size	360*370*1040mm	360*370*1040mm	360*370*1040mm
	Loading Qty	200PCS/20FT	200PCS/20FT	200PCS/20FT
		456PCS/40HQ	456PCS/40HQ	456PCS/40HQ

	Water Dispenser (SL-1015S)			
	Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
	Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
	Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
	Cabinet	Normal	Normal	With fridge
	Heating/Cooling power	550W /75W	550W /90W	550W /90W
	Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
	Cooling capacity	0.8L/H 10-15°C	2L/H 5-10°C	2L/H 5-10°C
	NW/GW		12.3/14.2KGS	12.3/14.2KGS
	Product size			
	Package size	340*365*1082mm	340*365*1082mm	340*365*1082mm
	Loading Qty	210PCS/20FT	210PCS/20FT	210PCS/20FT
		446PCS/40HQ	446PCS/40HQ	446PCS/40HQ



Water Dispenser (SL-1016S)			
Rated Voltage/Frequency	220V-240V 50/60Hz	220V-240V 50/60Hz	220V-240V 50/60Hz
Function	Hot & Warm & Cold	Hot & Warm & Cold	Hot & Warm & Cold
Cooling method	Electronic cooling	Compressor cooling	Compressor cooling
Cabinet	Normal	Normal	With fridge
Heating/Cooling power	550W /75W	550W /90W	550W /90W
Heating capacity	5L/H 85-95°C	5L/H 85-95°C	5L/H 85-95°C
Cooling capacity	0.8L/H 10-15°C	2L/H 5-10°C	2L/H 5-10°C
NW/GW		12.3/14.2KGS	12.3/14.2KGS
Product size			
Package size	340*365*1082mm	340*365*1082mm	340*365*1082mm
Loading Qty	210PCS/20FT	210PCS/20FT	210PCS/20FT
	446PCS/40HQ	446PCS/40HQ	446PCS/40HQ