



## Dongguan Sungreen Water Pure Technology Co., Ltd

Address: Room 1012, No.19 Juxiang the 3rd Road, Dalang Town, Dongguan City, Guangdong Province, China  
 TEL: 15377700152 Email: winnie@dgsungreen.com

### CATALOGUE

MOQ: 100sets

|  |                             |                   |                    |                    |
|--|-----------------------------|-------------------|--------------------|--------------------|
|  | Water Dispenser (SL-1708AB) |                   |                    |                    |
|  | Rated Voltage/Frequency     | 220V-240V 50/60Hz | 220V-240V 50/60Hz  | 220V-240V 50/60Hz  |
|  | Function                    | Hot & Warm        | Hot & Warm & Cold  | Hot & Warm & Cold  |
|  | Cooling method              | /                 | Electronic cooling | Compressor cooling |
|  | Heating/Cooling power       | 1350W             | 1350W/75W          | 1350W/90W          |
|  | Heating capacity            | 8L/H 50-100°C     | 8L/H 50-100°C      | 8L/H 50-100°C      |
|  | Cooling capacity            | /                 | 0.8L/H 10-15°C     | 2L/H 5-10°C        |
|  | NW/GW                       | 6.5/7.5KGS        | 9/10KGS            | 14.5KG             |
|  | Product size                | 320*330*900mm     | 320*330*900mm      |                    |
|  | Package size                | 355*345*790mm     | 355*345*790mm      | 40*38*86cm         |
|  | Loading Qty                 | 678PCS/40HQ       | 678PCS/40HQ        |                    |

|  |                           |                   |                    |                    |
|--|---------------------------|-------------------|--------------------|--------------------|
|  | Water Dispenser (SL-8816) |                   |                    |                    |
|  | Rated Voltage/Frequency   | 220V-240V 50/60Hz | 220V-240V 50/60Hz  | 220V-240V 50/60Hz  |
|  | Function                  | Hot & Warm        | Hot & Warm & Cold  | Hot & Warm & Cold  |
|  | Cooling method            | /                 | Electronic cooling | Compressor cooling |
|  | Heating/Cooling power     | 1350W             | 1350W/75W          | 1350W/90W          |
|  | Heating capacity          | 8L/H 50-100°C     | 8L/H 50-100°C      | 8L/H 50-100°C      |
|  | Cooling capacity          | /                 | 0.8L/H 10-15°C     | 2L/H 5-10°C        |
|  | NW/GW                     | 8.5/9.5KGS        | 9.5/10.5KGS        | 15/16KGS           |
|  | Product size              | 375*345*1150MM    | 375*345*1150MM     | 375*345*1150MM     |
|  | Package size              | 410*380*860MM     | 410*380*860MM      | 410*380*860MM      |
|  | Loading Qty               | 205PCS/20GP       | 205PCS/20GP        | 205PCS/20GP        |

|  |                           |                   |                    |                    |
|--|---------------------------|-------------------|--------------------|--------------------|
|  | Water Dispenser (SL-8859) |                   |                    |                    |
|  | Rated Voltage/Frequency   | 220V-240V 50/60Hz | 220V-240V 50/60Hz  | 220V-240V 50/60Hz  |
|  | Function                  | Hot & Warm        | Hot & Warm & Cold  | Hot & Warm & Cold  |
|  | Cooling method            | /                 | Electronic cooling | Compressor cooling |
|  | Heating/Cooling power     | 1350W             | 1350W/75W          | 1350W/90W          |
|  | Heating capacity          | 8L/H 50-100°C     | 8L/H 50-100°C      | 8L/H 50-100°C      |
|  | Cooling capacity          | /                 | 0.8L/H 10-15°C     | 2L/H 5-10°C        |
|  | NW/GW                     | 8.5/9.5KGS        | 9.5/10.5KGS        | 15/16KGS           |
|  | Product size              | 375*345*1150MM    | 375*345*1150MM     | 375*345*1150MM     |
|  | Package size              | 410*380*860MM     | 410*380*860MM      | 410*380*860MM      |
|  | Loading Qty               | 205PCS/20GP       | 205PCS/20GP        | 205PCS/20GP        |

|  |                           |                   |                    |  |
|--|---------------------------|-------------------|--------------------|--|
|  | Water Dispenser (SL-8848) |                   |                    |  |
|  | Rated Voltage/Frequency   | 220V-240V 50/60Hz | 220V-240V 50/60Hz  |  |
|  | Function                  | Hot & Warm        | Hot & Warm & Cold  |  |
|  | Cooling method            | /                 | Electronic cooling |  |
|  | Heating/Cooling power     | 1350W             | 1350W/75W          |  |
|  | Heating capacity          | 8L/H 50-100°C     | 8L/H 50-100°C      |  |
|  | Cooling capacity          | /                 | 0.8L/H 10-15°C     |  |
|  | NW/GW                     | 8.5/9.5KGS        | 9.5/10.5KGS        |  |
|  | Product size              | 355*330*1100MM    | 355*330*1100MM     |  |
|  | Package size              | 395*375*840MM     | 395*375*840MM      |  |
|  | Loading Qty               | 245PCS/20GP       | 245PCS/20GP        |  |

|  |                           |                   |                    |  |
|--|---------------------------|-------------------|--------------------|--|
|  | Water Dispenser (SL-TB01) |                   |                    |  |
|  | Rated Voltage/Frequency   | 220V-240V 50/60Hz | 220V-240V 50/60Hz  |  |
|  | Function                  | Hot & Warm        | Hot & Warm & Cold  |  |
|  | Cooling method            | /                 | Electronic cooling |  |
|  | Heating/Cooling power     | 1350W             | 1350W/75W          |  |
|  | Heating capacity          | 8L/H 50-100°C     | 8L/H 50-100°C      |  |
|  | Cooling capacity          | /                 | 0.8L/H 10-15°C     |  |
|  | NW/GW                     | 8.5/8.9KGS        | 8.5/8.9KGS         |  |
|  | Product size              | 32*33*102cm       | 32*33*102cm        |  |
|  | Package size              | 380*370*790MM     | 380*370*790MM      |  |
|  | Loading Qty               | 269PCS/20GP       | 269PCS/20GP        |  |

|  |                             |                   |                    |                    |
|--|-----------------------------|-------------------|--------------------|--------------------|
|  |                             |                   |                    |                    |
|  | Water Dispenser (SL-TB08-S) |                   |                    |                    |
|  | Rated Voltage/Frequency     | 220V-240V 50/60Hz | 220V-240V 50/60Hz  |                    |
|  | Function                    | Hot & Warm        | Hot & Warm & Cold  |                    |
|  | Cooling method              | /                 | Electronic cooling |                    |
|  | Heating/Cooling power       | 1350W             | 1350W/75W          |                    |
|  | Heating capacity            | 8L/H 50-100°C     | 8L/H 50-100°C      |                    |
|  | Cooling capacity            | /                 | 0.8L/H 10-15°C     |                    |
|  | NW/GW                       | 8.5/8.9KGS        | 8.5/8.9KGS         |                    |
|  | Product size                |                   |                    |                    |
|  | Package size                | 36.5*37.5*78      | 36.5*37.5*78       |                    |
|  | Loading Qty                 | 660PCS/40HQ       | 660PCS/40HQ        |                    |
|  |                             |                   |                    |                    |
|  | Water Dispenser (SL-TB08-B) |                   |                    |                    |
|  | Rated Voltage/Frequency     | 220V-240V 50/60Hz | 220V-240V 50/60Hz  | 220V-240V 50/60Hz  |
|  | Function                    | Hot & Warm        | Hot & Warm & Cold  | Hot & Warm & Cold  |
|  | Cooling method              | /                 | Electronic cooling | Compressor cooling |
|  | Heating/Cooling power       | 1350W             | 1350W/75W          | 1350W/90W          |
|  | Heating capacity            | 8L/H 50-100°C     | 8L/H 50-100°C      | 8L/H 50-100°C      |
|  | Cooling capacity            | /                 | 0.8L/H 10-15°C     | 2L/H 5-10°C        |
|  | NW/GW                       | 9.8KG/ 10.8kG     | 9.8KG/ 10.8kG      | 15KG/ 15.8kG       |
|  | Product size                |                   |                    |                    |
|  | Package size                | 42x39x86CM        | 42x39x86CM         | 42x39x86CM         |
|  | Loading Qty                 | 550PCS/40HQ       | 550PCS/40HQ        | 508pcs/40hq        |
|  |                             |                   |                    |                    |
|  | Water Dispenser (SL-TB06-S) |                   |                    |                    |
|  | Rated Voltage/Frequency     | 220V-240V 50/60Hz | 220V-240V 50/60Hz  |                    |
|  | Function                    | Hot & Warm        | Hot & Warm & Cold  |                    |
|  | Cooling method              | /                 | Electronic cooling |                    |
|  | Heating/Cooling power       | 1350W             | 1350W/75W          |                    |
|  | Heating capacity            | 8L/H 50-100°C     | 8L/H 50-100°C      |                    |
|  | Cooling capacity            | /                 | 0.8L/H 10-15°C     |                    |
|  | NW/GW                       | 8.5/8.9KGS        | 8.5/8.9KGS         |                    |
|  | Product size                |                   |                    |                    |
|  | Package size                | 36.5*37.5*78      | 36.5*37.5*78       |                    |
|  | Loading Qty                 | 660PCS/40HQ       | 660PCS/40HQ        |                    |
|  |                             |                   |                    |                    |
|  | Water Dispenser (SL-TB06-B) |                   |                    |                    |
|  | Rated Voltage/Frequency     | 220V-240V 50/60Hz | 220V-240V 50/60Hz  | 220V-240V 50/60Hz  |
|  | Function                    | Hot & Warm        | Hot & Warm & Cold  | Hot & Warm & Cold  |
|  | Cooling method              | /                 | Electronic cooling | Compressor cooling |
|  | Heating/Cooling power       | 1350W             | 1350W/75W          | 1350W/90W          |
|  | Heating capacity            | 8L/H 50-100°C     | 8L/H 50-100°C      | 8L/H 50-100°C      |
|  | Cooling capacity            | /                 | 0.8L/H 10-15°C     | 2L/H 5-10°C        |
|  | NW/GW                       | 9.8KG/ 10.8kG     | 9.8KG/ 10.8kG      | 15KG/ 15.8kG       |
|  | Product size                |                   |                    |                    |
|  | Package size                | 42x39x86CM        | 42x39x86CM         | 42x39x86CM         |
|  | Loading Qty                 | 550PCS/40HQ       | 550PCS/40HQ        | 508pcs/40hq        |
|  |                             |                   |                    |                    |
|  | Water Dispenser (SL-TY520)  |                   |                    |                    |
|  | Rated Voltage/Frequency     | 220V-240V 50/60Hz | 220V-240V 50/60Hz  |                    |
|  | Function                    | Hot & Warm        | Hot & Warm & Cold  |                    |
|  | Cooling method              | /                 | Electronic cooling |                    |
|  | Heating/Cooling power       | 1350W             | 1350W/75W          |                    |
|  | Heating capacity            | 8L/H 50-100°C     | 8L/H 50-100°C      |                    |
|  | Cooling capacity            | /                 | 0.8L/H 10-15°C     |                    |
|  | NW/GW                       | 9.3KGS            | 9.3KGS             |                    |
|  | Product size                | 32*36*110         | 32*36*110          |                    |
|  | Package size                | 40.5*35.5*86      | 40.5*35.5*86       |                    |
|  | Loading Qty                 | 575PCS/40HQ       | 575PCS/40HQ        |                    |
|  |                             |                   |                    |                    |