



Features

- *Intel Baytrail Platform, J1900 CPU, 2.24GHz, 4* Cores
- *Supports 2 independent Display
- *Supports 2 X 10/100/1000M LAN adapter
- *Supports 1 X USB3.0, 2 X USB2.0
- *Supports 1 X 2GB Onboard SSD
- *Supports 4 X COM, 9 X SATAII
- *Supports HD Audio
- *Supports 4GB Onboard DDR3L 1066/1333 MT/s

Application Industry

Security monitoring

Specifications

CPU	CPU	Intel Baytrail J1900 of 4 Cores 4 Threads, 64bit
	POWER	10W TDP
	Frequency	2GHz - 2.42GHz
Memory	Type	On Board DDR3L No ECC
	Channel	Dual
	Memory Size	4GB
Graphics	Graphics	Intel HD Graphics, 688MHz-854MHz
	Displays	2 independent Display (VGA + HDMI/HDMI +HDMI)
Audio	ALC662	x1 Audio line out
Storage	SM611GX2BA	x1 FerriSSD Single-Packaged 2GB
Ethernet	RTL8111F	x2 10/100/1000M BASET LAN
Internal Connector	SATA	x1 9*Standard SATA Connector
	USB	x2 1*4 Wafer
	COM	x2 1*3 Wafer
	GPIO	x1 2*6 Header, support 8 independent GPIO
	CPU_FAN	x1 1*3 Standard FAN connector
	SYS_FAN	x1 1*4 Wafer
I/O	AUDIO	x1 Dual RCA
	HDMI	x1 Dual HDMI
	VGA	x1 1*DB15 Standard VGA Connector
	USB	x1 1*Ports USB3.0
	RJ45	x2 Single RJ45
	ALARM1	x1 Phoenix terminal 2*5 PIN, 8*ALARMIN
	ALARM2	x1 Phoenix terminal 2*10 PIN, 8*ALARMIN, 4*Bypass, 1*RS485
BIOS	Vender	AMI
	ACPI	Supported
Power	ATX	ATX Power, Nonstandard Usage
Dimensions	PCB	127*160MM