



Description & Features

DR24060-02C is an uninterruptible din rail PSU with 2 output channels, its main output is 24-28V / 2.5A, with maximum rated output power 70W. It could be used for CCTV Surveillance / Access Control / Fire Alarm and other automation systems.

- Maximum Output Power: 70W
- High efficiency up to 87%, long life and high reliability
- Protection: input fuse / overload / over voltage / short circuit
- Multifunction LED indicators
- 100% full load burn-it test
- Din Rail Mounting
- 2 years warranty
- CE, RoHS, RCM



SPECIFICATION

INPUT	Voltage Range	190 - 265VAC	
	Frequency Range	50 - 60Hz	
OUTPUT	Voltage (AC Mode)	24-28V $\pm$ 2%	
	Rated Current	2.5A	
	Rated Power (Max.)	70W	
	Efficiency (Typ.)	>86%	
	Ripple & Noise	<240mVp-p	
	Output Channel	2 Channels	
PROTECTION	Input	2A / 250VAC fuse	
	Overload	3A $\pm$ 5%	
		Hiccup mode, recovers automatically after fault condition is removed.	
		Hiccup mode, recovers automatically after fault condition is removed.	
		PSU shuts down until AC power is reconnected	
ENVIRONMENT	Short Circuit	Hiccup mode, recovers automatically after fault condition is removed.	
	Temperature	Working: -20 - 45°C	Storage: -30 - 80°C
LED INDICATOR	Humidity	Working: 20 - 80%RH	Storage: 10 - 90%RH
	Green	On	DC OK
SAFETY & EMC	EMC Standards	EN 55022: 2010, EN 55024: 2010, EN 61000-3-2: 2014, EN 61000-3-3: 2013	
	LVD Standards	EN 62368-1-2014-A11-2017	
PLASTIC BOX & PACKING	Default Plastic Box	89.5mm x 93mm x 56mm, can pack with a 12V 7Ah Lead Acid battery externally	
	Packing	505*345*220mm / CTN, 50pcs / CTN	