



### Description & Features

SIHD122-16CB is an uninterruptible PSU with 16 output channels, its main output is 13.8V / 20A, while it also provides maximum 2A charge current. It could be used for CCTV Surveillance / Access Control / Fire Alarm and other security systems.

- High efficiency up to 85%, long life and high reliability
- Protection: input fuse / overload / over voltage / short circuit
- Multifunction LED indicators
- No delay battery boot up
- 100% full load burn-in test
- Metal box with key-lock, wall mount i
- ▲ Withstand 5000 vibration test



### SPECIFICATION

<b>INPUT</b>	<b>Voltage Range</b>	190 - 265VAC	
	<b>Frequency Range</b>	50 - 60Hz	
<b>OUTPUT</b>	<b>Voltage (AC Mode)</b>	13.8V ±2%	
	<b>Voltage (Battery Mode)</b>	Same as battery voltage	
	<b>Rated Current</b>	20A	
	<b>Rated Power (Max.)</b>	303W (with 2A charge current)	
	<b>Efficiency (Typ.)</b>	>85%	
	<b>Ripple &amp; Noise</b>	<120mVp-p	
	<b>Output Channel</b>	16 channels with 1.5A glass fuse per channel.	
	<b>CHARGING</b>	<b>Voltage</b>	13.8V ±2%
<b>Current</b>		2A Max	
<b>PROTECTI ON</b>	<b>Input</b>	6.3A / 250VAC fuse	
	<b>Overload</b>	23A ±5%	
		Hiccup mode, recovers automatically after fault condition is removed.	
	<b>Over Voltage</b>	16V ±5%	
		Hiccup mode, recovers automatically after fault condition is removed.	
	<b>Short Circuit</b>	Hiccup mode, recovers automatically after fault condition is removed.	
	<b>Battery Low Voltage</b>	10V ±2%	
PSU shuts down until AC power recovers.			
<b>Battery Reverse Connect</b>	Battery not works, no effect on main output.		
<b>ENVIRONM ENT</b>	<b>Temperature</b>	Working: -20 - 50°C	Storage: -30 - 80°C
	<b>Humidity</b>	Working: 20 - 80%RH	Storage: 10 - 90%RH
<b>LED INDICATOR</b>	<b>Red</b>	On	AC power is on
	<b>Green</b>	On	DC output is on
	<b>Yellow</b>	On	Battery is discharging / fully charged / no battery
		Flickering	Battery is charging
	<b>Red</b>	On	AC failure alarm
<b>Red</b>	On	Battery low voltage (<11V) alarm	
<b>SAFETY &amp; EMC</b>	<b>EMC Standards</b>	EN 55022: 2010, EN 55024: 2010, EN 61000-3-2: 2014, EN 61000-3-3: 2013	
	<b>LVD Standards</b>	EN 60950-1: 2006 + A11: 2009 + A1: 2010 + A12: 2011 + A2: 2013	
<b>METAL BOX &amp;</b>	<b>Metal Box</b>	395 x 285 x 165mm, fits for 2 pc 12V 17Ah battery.	
	<b>Packing</b>	51 x 31 x 32.5cm / CTN, 19kg / CTN, 3pcs / CTN	

**ANDGOOD<sup>®</sup>**  
0-1000

**Metal Box Uninterruptible 16 Channels PSU**

**SIHD122**

PACKING		
---------	--	--