



Description & Features

SPHD1203-01B is an uninterruptible PSU with 1 output, its main output is 12.3V / 3A, while it also provides maximum 400mA charge current. It could be used for CCTV Surveillance / Access Control / Fire Alarm and other security systems.

- High efficiency up to 84%, long life and high reliability
- Protection: input fuse / overload / over voltage / short circuit
- Multifunction LED indicators
- No delay battery boot up
- 100% full load burn-it test
- Metal box with key-lock, wall mount installation
- Withstand 5G vibration test
- 2 years warranty



SPECIFICATION

| | | | | |
|----------------------------------|-------------------------------|--|---|---|
| INPUT | Voltage Range | 190 - 240VAC | | |
| | Frequency Range | 50 - 60Hz | | |
| OUTPUT | Voltage (AC Mode) | 12.3V ±2% | | |
| | Voltage (Battery Mode) | Same as battery voltage | | |
| | Rated Current | 3A | | |
| | Rated Power (Max.) | 44W (with 400mA charge current) | | |
| | Efficiency (Typ.) | >84% | | |
| | Ripple & Noise | <120mVp-p | | |
| | Output Channel | 4 channels with 1A glass fuse per channel. | | |
| | CHARGING | Voltage | 12.3V ±2% | |
| Current | | 400mA (max.) | Constant Current Charging. | |
| PROTECTION | Input | 2A / 250VAC fuse | | |
| | Overload | 3.5A ±5% | Hiccup mode, recovers automatically after fault condition is removed. | |
| | | Over Voltage | 16V ±5% | Hiccup mode, recovers automatically after fault condition is removed. |
| | Battery Low Voltage | 10V ±2% | PSU shuts down until AC power recovers. | |
| | | Short Circuit | Hiccup mode, recovers automatically after fault condition is removed. | |
| ENVIRONMENT | Temperature | Working: -20 - 45°C | Storage: -30 - 80°C | |
| | Humidity | Working: 20 - 80%RH | Storage: 10 - 90%RH | |
| LED INDICATOR | Green | On | AC power is on | |
| | Blue | On | DC output is on | |
| | Red | On | Battery under-voltage | |
| | | Off | Battery is discharging | |
| | | Flickering | Battery is charging | |
| Yellow | On | Battery is fully charged or no battery | | |
| SAFETY & EMC | EMC Standards | EN 55022: 2010, EN 55024: 2010, EN 61000-3-2: 2014, EN 61000-3-3: 2013 | | |
| | LVD Standards | EN 60950-1: 2006 + A11: 2009 + A1: 2010 + A12: 2011 + A2: 2013 | | |
| PLASTIC BOX & PACKING | Default Plastic Box | 230mm x 166mm x 62mm, packed with 18650 11.1V4AH Lithium Battery Pack | | |
| | Packing | | | |