



GENESSO®

R-290

## Safety Data Sheet

# R290 PROPANE

### 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** PROPANE  
**OTHER NAME:** Liquefied Petroleum Gas (LPG)  
**USE:** Refrigerant Gas  
**DISTRIBUTOR:** LONGHIGH GROUP (HK)  
CO., LTD.  
FLAT/RM H 12/F GOLD KING INDUSTRIAL BUILDING 35-41 TAI LIN PAI ROAD KWAI  
CHUNG, HONGKONG

**FOR MORE INFORMATION CALL:**

(Monday-Friday, 8:00 am-5:00 pm)  
008602081093872

### 2. HAZARDS IDENTIFICATION

**CLASSIFICATION:** Flammable Gas, Gas under pressure, Compressed Gas  
**SIGNAL WORD:** DANGER  
**HAZARD STATEMENT(S):** Extremely flammable gas, contains gas under pressure, may explode if heated  
**SYMBOL(S):** Flames, Gas Cylinder



**PRECAUTIONARY STATEMENT(S):**

**Prevention:** Keep away from heat, sparks, open flames, and hot surfaces. No Smoking

**Response:** Leaking gas fire: Do not extinguish unless the leak can be stopped immediately. Eliminate all ignition sources if safe to do so.

**Storage:** Protect from sunlight, store in a well-ventilated place.

**EMERGENCY OVERVIEW:**

Flammable gas. Liquid under high pressure.

**POTENTIAL HEALTH EFFECTS:**

**Effects of Overexposure:**

**Eye Contact**

No known significant effects or critical hazards.

**Skin Contact**

No known significant effects or critical hazards.



GENESSO®

R-290

**Inhalation**

Acts as simple asphyxiant.

**Ingestion**

Ingestion is not a normal route of exposure for gases

---

**3. COMPOSITION / INFORMATION ON INGREDIENTS**

---

<u>INGREDIENT NAME</u>	<u>CAS NUMBER</u>	<u>WEIGHT %</u>
Propane	74-98-6	100

**COMMON NAMES and SYNONYMS**

Liquefied Petroleum Gas (LPG) R-290

There are no impurities or stabilizers that contribute to the classification of the material identified in Section 2

---

**4. FIRST AID MEASURES**

---

**SKIN:**

In case of contact, immediately flush the skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention.

**EYES:**

Immediately flush your eyes with plenty of warm water for at least 15 minutes. Get medical attention.

**INHALATION:**

Immediately remove to fresh air. If breathing has stopped, give artificial respiration. If breathing is difficult, qualified personnel may give oxygen. Get medical attention immediately.

**INGESTION:**

Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention if symptoms appear.

**PHYSICIAN ADVICE:**

No specific treatment. Contact a poison treatment specialist immediately if large amounts have been inhaled or ingested.

---

**5. FIRE-FIGHTING MEASURES**

---

**FLAMMABLE PROPERTIES**

**FLASHPOINT:**

**AUTO IGNITION TEMPERATURE:**

468 C (874 F)

**UPPER EXPLOSIVE LIMIT (volume % in air):**

9.5%

**LOWER EXPLOSIVE LIMIT (volume % in air):**

2.2%

**EXTINGUISHING MEDIA:**

These products are carbon oxides (CO, CO<sub>2</sub>).

**UNUSUAL FIRE HAZARDS:**

Extremely flammable in the presence of open flames, sparks, and static discharge of oxidizing materials.



GENESSO®

R-290

**FIRE FIGHTING INSTRUCTIONS:**

CO<sub>2</sub>, dry chemicals, water spray, or fog. If involved in a fire, shut off flow immediately if it can be done without risk. Apply water from a safe distance to cool the container and protect the surrounding area. Extremely flammable.

Gas may accumulate in confined areas, travel a considerable distance to the source of ignition, and flash back causing fire or explosion. Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full-face piece operated in positive pressure mode.

---

**6. ACCIDENTAL RELEASE MEASURES**

---

**SPILL AND LEAK PROCEDURES:**

Immediately contact emergency personnel. Keep unnecessary personnel away. Use suitable protective equipment (Section 8). Shut off the gas supply if this can be done safely. Isolate the area until the gas has dispersed. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains, and sewers.

---

**7. HANDLING AND STORAGE**

---

**NORMAL HANDLING:**

Keep the container closed. Use only with adequate ventilation. Keep away from heat, sparks, and flame. To avoid fire, minimize ignition sources. Use explosion-proof electrical (ventilating, lighting, and material handling) equipment. Do not puncture or incinerate the container. High-pressure gas. Use equipment rated for cylinder pressure. Close the valve after each use and when empty. Protect cylinders from physical damage; do not drag, roll, slide, or drop. Use a suitable hand truck for cylinder movement.

**STORAGE RECOMMENDATIONS:**

Keep the container tightly closed. Keep the container in a cool, well-ventilated area. Cylinders should be stored upright, with a valve protection cap in place, and firmly secured to prevent falling or being knocked over. Cylinder temperatures should not exceed 52°C (125°F).

---

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

---

**ENGINEERING CONTROLS:**

Use only with adequate ventilation. Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits. The engineering controls also need to keep gas, vapor or dust concentrations below any explosive limits. Use explosion-proof ventilation equipment

**PERSONAL PROTECTION:**

**SKIN PROTECTION:**

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**EYE PROTECTION:**

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.

**RESPIRATORY PROTECTION:**

Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk



GENESSO®

**R-290**

assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.



GENESSO®

R-290

The applicable standards are (US) 29 CFR 1910.134 and (Canada) Z94.4-93

**EXPOSURE GUIDELINES**

(Exposure Limits)

**INGREDIENT NAME**

Propane

**ACGIH TLV**

1000 ppm

**OSHA PEL**

1000 ppm

**OTHER LIMIT**

---

**9. PHYSICAL AND CHEMICAL PROPERTIES**

---

<b>APPEARANCE:</b>	Colorless, liquefied compressed gas
<b>PHYSICAL STATE:</b>	Gas at ambient temperature
<b>ODOR:</b>	Odorless
<b>SOLUBILITY IN WATER:</b>	0.0244 g/liter
<b>BOILING POINT:</b>	-43.2°F (-41.79°C)
<b>VAPOR PRESSURE:</b>	109 psig
<b>FLASHPOINT:</b>	-104°C (-155°F)
<b>EVAPORATION RATE:</b>	Not available
<b>FLAMMABILITY:</b>	Extremely flammable in the presence of ignition sources or oxidizing materials
<b>LEL/UEL:</b>	2.2% / 9.5%
<b>PARTITION COEFFICIENT</b>	
<b>n-OCTANOL/WATER:</b>	Log Pow: 1.09
<b>AUTO IGNITION TEMPERATURE:</b>	468 C (874 F)
<b>DECOMPOSITION TEMPERATURE:</b>	Data not available
<b>VISCOSITY:</b>	Not applicable
<b>VAPOR DENSITY:</b>	1.6 (Air=1)
<b>% VOLATILES BY VOLUME:</b>	100%
<b>DENSITY:</b>	0.116 lb / cu ft
<b>pH:</b>	Not applicable
<b>MELTING/FREEZING POINT:</b>	-302.6°F (-185.89°C)
<b>SPECIFIC VOLUME (ft<sup>3</sup>/lb):</b>	8.62069
<b>MOLECULAR FORMULA:</b>	C <sub>3</sub> H <sub>8</sub>
<b>MOLECULAR WEIGHT:</b>	44.11 g/mole
<b>BOILING/CONDENSATION POINT:</b>	-161°C / 259°F

---

**10. STABILITY AND REACTIVITY**

---

**CHEMICAL STABILITY**

The product is stable.

**REACTIVITY:**

Not reactive under normal storage conditions.

**INCOMPATIBILITY WITH OTHER MATERIALS:**

Extremely reactive or incompatible with oxidizing agents.

**CONDITIONS TO AVOID:**

Avoid all possible sources of ignition (spark or flame). Do not cut, weld, braze, solder, drill, or grind container



---

**11. TOXICOLOGICAL INFORMATION**

---

**TOXICITY DATA:**

<b>IDLH:</b>	2100 ppm
<b>Chronic effects on humans:</b>	Causes damage to the following organs: the nervous system.
<b>Acute toxic effects on humans:</b>	No specific information is available in our database regarding the other toxic effects of this material on humans.

**SPECIFIC EFFECTS:**

<b>Carcinogenic effects:</b>	No known significant effects or critical hazards.
<b>Mutagenic effects:</b>	No known significant effects or critical hazards.
<b>Reproductive toxicity:</b>	No known significant effects or critical hazards.

---

**12. ECOLOGICAL INFORMATION**

---

**DEGRADABILITY (BOD):**

**Products of degradation:** These products are carbon oxides (CO,CO<sub>2</sub>) and water.

**Toxicity of the products of biodegradation:** The product itself and its products of degradation are not toxic.

**Environmental fate:** Not available

**Environmental hazards:** No known significant effects or critical hazards.

**Toxicity to the environment:** Not available.

---

**13. DISPOSAL CONSIDERATIONS**

---

The product removed from the cylinder must be disposed of by appropriate Federal, State, and local regulations.

---

**14. TRANSPORT INFORMATION**

---

<b>US DOT ID NUMBER:</b>	UN 1978
<b>US DOT SHIPPING NAME:</b>	PROPANE
<b>US DOT HAZARD CLASS:</b>	2.1
<b>US DOT PACKING GROUP:</b>	NA

---

**15. REGULATORY INFORMATION**

---

**U.S. FEDERAL REGULATIONS:**

TSCA 8(b) inventory: Propane

SARA 302/304/311/312 extremely hazardous substances: No products were found.

SARA 302/304 emergency planning and notification: No products were found.

SARA 302/304/311/312 hazardous chemicals: Propane

SARA 311/312 MSDS distribution – chemical inventory – hazard identification: Propane: Fire hazard, Sudden Release of Pressure

Clean Water Act (CWA) 307: No products were found.

Clean Water Act (CWA) 311: No products were found.

Clean Air Act (CAA) 112 accidental release prevention: Propane

Clean Air Act (CAA) 112 regulated flammable substances: Propane

Clean Air Act (CAA) 112 regulated toxic substances: No products were found.



GENESSO®

**R-290**

**STATE REGULATIONS:**

Pennsylvania RTK: Propane: (generic environmental hazard)  
Massachusetts RTK: Propane  
New Jersey: Propane

**CANADA**

**WHMIS (Canada):** Class A: Compressed gas  
Class B-1: Flammable gas  
CEPA DSL: Propane

---

**16. OTHER INFORMATION**

---

**HAZARD RATING SYSTEMS:**

**NFPA RATINGS:**

HEALTH =1  
FLAMMABILITY =4  
INSTABILITY =0  
SPECIAL =None

**HMIS RATINGS:**

HEALTH =1  
FIRE HAZARD =4  
REACTIVITY =0  
PERSONAL PROTECTION =C

**DISCLAIMER**

National Refrigerants, Inc. believes that the information and recommendations contained herein (including data and statements) are accurate as of the date hereof). NO WARRANTY OF FITNESS OR ANY PARTICULAR PURPOSE, WARRANTY OF MERCHANTABILITY, OR ANY OTHER WARRANTY, EXPRESSED OR IMPLIED, IS MADE CONCERNING THE INFORMATION PROVIDED HEREIN. The information provided herein relates only to the specific product designated and may not be valid where such product is used in combination with any other methods of use of the product and of the information referred to herein are beyond the control of National Refrigerants. National Refrigerants expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information.