


Recommended P.C.B Layout
(Tolerance:±0.05)



Materials

Contact Material: Phosphor Bronze

Insulator : Thermoplastic High Temp UL94-V0

Specifications

Current Rating: 1Amp

Insulation Resistance: 1000MΩ Min.


Dielectric Withstanding: 300V AC/DC

Contact Resistance: 20mΩ Max.

Operating Temperature: -40°C to +105°C

635-x 1- xx x x xxxx
1 2 3 4 5 6

- 7: Green Product
- 9: Green Product High Temp
- 2: Dual rows
- 1: Single row
- No. of contacts per row
- G: Gold flash
- T: Tin plated
- B: Black Insulator
- Pinrex internal code.

			TOLERANCE			OLD PART NO.		TITLE FEMALE HEADER 1.27*1.27mm SMT TYPE, TOP ENTRY HEIGHT 3.4mm ,CAP+T/R	 頻銳科技股份有限公司 PINREX TECHNOLOGY CORP.
			.0 =±.30			DRAWER 姜文慧	CHECK 李剑		
			.00 =±.20		UNITS : mm				
			.000 =±.XXX		SCALE NONE	SHEET 1 OF 1	REV. A	APP'D 李剑	
A	RELEASE	2020/10/29	.0000=±.		SIZE A4			NEW PART NO. 635-91-xxGBE02R	DRAW NO. 635-x1-xxxxxxxx(網頁專用圖)
REV.	DESCRIPTION	DATE	ANG.=±3'						