



Recommended P.C.B Layout

1. Materials
 Contact Material: Brass
 Insulator : Thermoplastic High Temp UL94-V0
2. Specifications
 Current Rating: 2Amp
 Insulation Resistance: 1000MΩ Min.
 Dielectric Withstanding: 500VAC
 Contact Resistance: 20mΩ Max.
 Operating Temperature: -40°C to +105°C

$$62N-\frac{x}{1} \frac{2}{2} - \frac{xx}{3} \frac{x}{4} \frac{x}{5} \frac{xx}{6}$$

1. 7: Green Product
 9: Green Product High Temp
2. 1: Single row
 2: Dual rows
3. No. of contacts per row
4. G: Gold flash
 T: Tin plated
5. B: Black Insulator
 W: White Insulator
6. Pinrex internal code.



		TOLERANCE		UNITS : mm		OLD PART NO.		TITLE 2.00 FEMALE HEADER DUAL ROWS SMT TYPE SERIES		频锐科技股份有限公司 PINREX TECHNOLOGY CORP.	
		.0 =±.30		SCALE NONE		DRAWER 姜文慧		NEW PART NO. 62N-x2-xxxxxx		DRAW NO. 62N-x2-xxxxxx(網頁專用圖)	
		.00 =±.20		SIZE A4		CHECK 李剑					
		.000 =±.XXX		SHEET 1 OF 1		APP'D 李剑					
A RELEASE		2020/11/03		REV. A							
REV. DESCRIPTION		DATE		ANG.=±3'							