



MATERIAL

Insulator : PBT+30% Glass fiber UL94-V0
Contact Pin : brass

SPECIFICATION

Current Rate : 3 AMP PER PIN
Insulation Resistance : 5000MΩMin. at DC 500V
Contact Resistance : 20mΩMax. at DC 100mA
Dielectric Voltage : 500V AC for one minute
Operation Temperature : -55°C to +105°C

201-x 1- xx x x x x
1 2 3 4 5

- 7: Green Product
9: Green Product High Temp
- No. of ports (02~10)
- G: Gold flash
- B: Black Insulator
- Pinrex internal code.



						TOLERANCE				OLD PART NO.		TITLE			
						.0 =±.30						MINI JUMPER 2.54mm			
						.00 =±.20				DRAWER		CHECK			
						.000 =±.XXX				麦文慧		李剑			
A		RELEASE		2008/01/08		.0000=±.				SCALE		SIZE		SHEET	
REV.		DESCRIPTION		DATE		ANG.=±3'				NONE		A4		1 OF 1	
														REV.	
														APP'D	
														李剑	
												NEW PART NO.		DRAW NO.	
												201-x1-xxxxxxx		201-x1-xxxxxx(網頁專用圖)	

PINREX 频锐科技股份有限公司
PINREX TECHNOLOGY CORP.