



Green
Product

Detail Dimensions



Specification:

Contact Resistance: 30m Ohm Max.

Insulation Resistance: 100M Ohm Min.AT 500V DC

Rated Voltage And Current: DC12V.2A Max;AC 100V.1A Max.

Dielectric Withstanding Voltage:250V AC For 1 Minute

Durability (Life Test): 100 Cycles

Insertion Force:4.0KG Maximum.

Extraction Force:0.9KG Minimum.



	3 PIN		4 PIN		5 PIN	
6 PIN	7 PIN		8 PIN		9 PIN	

NO.	NAME	MATERIAL	FINISH	Q'TY	REMARK
1	HOUSING	PBT G.F.	BLACK	1	
2	CONTACT TERM.	PHOS. BRONZE T:0.2	GOLD-TIN PLATED	x	Gold:1~3u"; Ni:40~60u"; TIN:120u" (100% pure Tin of lead free plating)
3	GROUND TERM.	BRASS T:0.4	TIN PLATED	1	TIN:120~200u"
4	BOTTOM COVER	PBT G.F.	BLACK	1	

			TOLERANCE				OLD PART NO.		TITLE		 頻銳科技股份有限公司 PINREX TECHNOLOGY CORP.
			.0 =±.30 .00 =±.20 .000 =±.XXX .0000=± ANG.=±3°		UNITS : mm		DRAWER 麥文慧 CHECK 李劍		MINI DIN Female R/A PCB Green Product		
A	RELEASE	2020/10/13	DATE		SCALE	SIZE	SHEET	REV.	APP'D	NEW PART NO.	DRAW NO.
REV.	DESCRIPTION				NONE	A4	1 OF 1	A	李劍	983-1x-0xx7xx	983-1x-0xx7xx(網頁專用圖)