







MATERIAL

Contact Pin : Brass

Insulator : Thermoplastic High Temp UL94-V0

SPECIFICATION

Current Rate : 1 AMP

Insulation Resistance : 5000M Min. at DC 500V

Contact Resistance : 20mΩMax. at DC 100mA

Dielectric Voltage : AC 500V for one minute

220-x 2- xx x x xx
1 2 3 4 5 6

- 7: Green Product
9: Green Product High Temp
- 2: Dual rows
Plastic Height=1.5mm
7: Dual rows
Plastic Height=2.0mm
- No. of contacts per row
- G: Gold flash
S: Selective
5: Matte Tin plated
B: Black Insulator
Pinrex internal code.

POLES	DIM E	POLES	DIM E
		21	40.00
2	2.00	22	42.00
3	4.00	23	44.00
4	6.00	24	46.00
5	8.00	25	48.00
6	10.00	26	50.00
7	12.00	27	52.00
8	14.00	28	54.00
9	16.00	29	56.00
10	18.00	30	58.00
11	20.00	31	60.00
12	22.00	32	62.00
13	24.00	33	64.00
14	26.00	34	66.00
15	28.00	35	68.00
16	30.00	36	70.00
17	32.00	37	72.00
18	34.00	38	74.00
19	36.00	39	76.00
20	38.00	40	78.00



				TOLERANCE				OLD PART NO.		TITLE		 頻銳科技股份有限公司 PINREX TECHNOLOGY CORP.										
				.0 =±.30		UNITS : mm		DRAWER 姜文慧		CHECK 李劍			PIN HEADER 2.00*2.00mm									
				.00 =±.20				SCALE NONE		SIZE A4			SHEET 1 OF 1		REV. A		APP'D 李劍		NEW PART NO. 220-x2-xxxxxx		DRAW NO. 220-x2-xxxxxx (網頁專用圖)	
				.000 =±.XXX																		
A RELEASE		2020/10/26		.0000=±.																		
REV. DESCRIPTION		DATE		ANG.=±3°																		