

XAPX2.E192925 Temperature-indicating and -Regulating Equipment - Component

If you notice a change to your XAPX2 Listing Card, click here to learn more.

Page Bottom

Temperature-indicating and -Regulating Equipment - Component

See General Information for Temperature-indicating and -Regulating Equipment - Component

HONEST-WELL CO LTD E192925

4th Fl 4 Ln 560 Zhongzheng Rd Xindian District New Taipei, 23148 TAIWAN

Temperature-indicating and regulating equipment Model(s) T24Axxxxxxx-xx-TB where x can be a three digits, followed by alphanumeric, followed by C, H, R, B, D, L, K, P, X, V, F, E, A, U, M, S, G, O, N, followed by F, K, R, T or L, followed by 1, 2, 3, 5, 6, 7, 8, or 9, followed by alphanumeric characters in two digits, followed by P, T, C, followed by B, N,

Investigated to UL 873

Manual Reset, Temperature-Regulating Thermostats investigated to UL 873 Model(s) T23M followed by 050 through 220, followed by A or B, followed by A, B, C, D, H, P, R, S, X, L, K, V, F, E, U, M, G, N, or O, followed by F, K, R, T, or L, followed by 1, 2, 3, 5, 6, 7, 8, or 9, followed by 10 through 30, M5, M6, or M7

Single-Operation Devices investigated to UL 873 Model(s) T24Axxxxxxx-xx-CB where x can be a three digits, followed by alphanumeric, followed by C, H, R, B, D, L, K, P, X, V, F, E, A, U, M, S, G, O, N, followed by F, K, R, T or L, followed by 1, 2, 3, 5, 6, 7, 8, or 9, followed by alphanumeric characters in two digits, followed by P, T, C, followed by B, N,

Temperature-indicating and regulating equipment Model(s) T24Axxxxxxx-xx-CE where x can be a three digits, followed by alphanumeric, followed by C, H, R, B, D, L, K, P, X, V, F, E, A, U, M, S, G, O, N, followed by F, K, R, T or L, followed by 1, 2, 3, 5, 6, 7, 8, or 9, followed by alphanumeric characters in two digits, followed by P, T, C, followed by B, N, F

T24Axxxxxxx-xx-PB where x can be a three digits, followed by alphanumeric, followed by C, H, R, B, D, L, K, P, X, V, F, E, A, U, M, S, G, O, N, followed by F, K, R, T or L, followed by 1, 2, 3, 5, 6, 7, 8, or 9, followed by alphanumeric characters in two digits, followed by P, T, C, followed by B, N, E

T24Mxxxxxxx-xx-PB where x can be a three digits, followed by alphanumeric, followed by C, H, R, B, D, L, K, P, X, V, F, E, A, U, M, S, G, O, N, followed by F, K, R, T or L, followed by 1, 2, 3, 5, 6, 7, 8, or 9, followed by alphanumeric characters in two digits, followed by P, T, C, followed by B, N, E

T24Mxxxxxxx-xx-TB where x can be a three digits, followed by alphanumeric, followed by C, H, R, B, D, L, K, P, X, V, F, E, A, U, M, S, G, O, N, followed by F, K, R, T or L, followed by 1, 2, 3, 5, 6, 7, 8, or 9, followed by alphanumeric characters in two digits, followed by P, T, C, followed by B, N, E

Temperature-Limiting Thermostats investigated to UL 873 Model(s) T23A followed by 050 through 220, followed by A or B, followed by A, B, C, D, H, P, R, S, X, L, K, V, F, E, U, M, G, N, or O, followed by F, K, R, T, or L, followed by 1, 2, 3, 5, 6, 7, 8, or 9, followed by 10 through 30, M5, M6, or M7

Temperature-Regulating Thermostats for Use In Household Drip-Type Coffee Maker investigated to UL 873 Model(s) T24Axxxxxxx-xx-CN where x can be a three digits, followed by alphanumeric, followed by C, H, R, B, D, L, K, P, X, V, F, E, A, U, M, S, G, O, N, followed by F, K, R, T or L, followed by 1, 2, 3, 5, 6, 7, 8, or 9, followed by alphanumeric characters in two digits, followed by P, T, C, followed by B, N, E

Temperature-Indicating and Regulating Equipment Model(s) T24, followed by A or B; followed by a number up to 205; followed by alphanumeric; followed by B, C, D, H, P, R, S, X, L, K, V, F, E, U, M, G, or O; followed by F, K, R, T or L; followed by 1, 2, 6, 7, 8, or 9; followed by a number in two digits; followed by P or T; followed by B

Temperature-Regulating Thermostats for Use In Household Drip-Type Coffee Maker investigated to UL 873 Model(s) T24, followed by A; followed by a number up to 210; followed by alphanumeric; followed by B, C, D, H, P, R, S, X, L, K, V, F, E, U, M, G, or O; followed by F, K, R, T or L; followed by 1, 2, 6, 7, 8, or 9; followed by alphanumeric characters in two digits; followed by C; followed by E

Appliance thermostats Model(s) T26

Single-Operation Devices investigated to UL 873 Model(s) T24, followed by A; followed by a number up to 250; followed by alphanumeric; followed by B, C, D, H, P, R, S, X, L, K, V, F, E, U, M, G, or O; followed by F, K, R, T or L; followed by 1, 2, 6, 7, 8, or 9; followed by 35; followed by C; followed by N

Temperature-Indicating and Regulating Equipment Model(s) T24, followed by A; followed by a number up to 250; followed by alphanumeric; followed by B, C, D, H, P, R, S, X, L, K, V, F, E, U, M, G, or O; followed by F, K, R, T or L; followed by 1, 2, 6, 7, 8, or 9; followed by a number in two digits; followed by C; followed by B

T24, followed by M; followed by a number up to 205; followed by alphanumeric; followed by B, C, D, H, P, R, S, X, L, K, V, F, E, U, M, G, or O; followed by F, K, R, T or L; followed by 1, 2, 6, 7, 8, or 9; followed by alphanumeric characters in two digits; followed by P or T; followed by B

T24, followed by M; followed by a number up to 250; followed by alphanumeric; followed by B, C, D, H, P, R, S, X, L, K, V, F, E, U, M, G, or O; followed by F, K, R, T or L; followed by 1, 2, 6, 7, 8, or 9; followed alphanumeric characters in two digits; followed by C; followed by B.

Investigated to UL-60730-1, UL 60730-2-9

Temperature limiting thermostats, investigated to UL 873 Model(s) H2/22, H2/32, H2/33, H2K/11, H3/33, H4/11

Temperature regulating thermostats for household drip-type coffee makers investigated to UL 873 Model(s) H3/33

Temperature regulating thermostats, investigated to UL 873 Model(s) H2/22, H2/32, H2K/11, H2M/11, H2M/33, H4/11

Investigated to UL 873

Manual Reset, Temperature-Regulating Thermostats investigated to UL 873 Model(s) T23, followed by M; followed by 050 through 220; followed by A or B; followed by A, B, C, D, H, P, R, S, X, L, K, V, F, E, U, M, G, N, or O; followed by F, K, R, T or L; followed by 1, 2, 3, ,5, 6, 7, 8, or 9; followed by M5, M6, or M7.

Temperature limiting thermostats, investigated to UL 873 Model(s) H2/11, H2/31

Temperature-Limiting Thermostats investigated to UL 873 Model(s) T23, followed by A, or B; followed by 050 through 205,; followed by A or B,; followed by A, B, C, D, H, P, R, S, X, L, K, V, F, E, U, M, G, N, or O; followed by F, K, R, T or L,; followed by 1, 2, 3, 5, 6, 7, 8, or 9; followed by 10 through 30.

Marking: Company name or tradename "HW" , "LC" and model designation. <u>Last Updated</u> on 2017-05-06

Questions? Print this page Terms of Use Page Top

© 2018 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2018 UL LLC".