



# FEI-Zyfer

7321 Lincoln Way Garden Grove, CA tel 888-886-7465

## GPStarplus®



### GPStarplus® Model 565

GPStarplus® is a fully featured, off-the-shelf, compact time and frequency system providing a new level of price/performance. It provides accuracy within 100 nanoseconds of UTC (Coordinated Universal Time). GPStarplus tracks up to eight satellites at a time. When used as a frequency standard, GPStarplus can provide 5 E-12 frequency accuracy.

GPStarplus® is packaged in a 19" rack mount chassis that is only 1.75" high. The control and operation interface is provided via RS-232 or a front panel key pad. A 2-line by 40-character backlit LCD display reports Julian time and date, as well as informing the user if time is locked, how many satellites are being received, and other status information.

The standard power supply operates from 95 - 264 VAC at 50 - 60 Hz.

#### System Features:

- ▶ **Accuracy:**  
Within 100 ns of UTC
- ▶ **Oscillator Options:**  
Ovenized Quartz  
Rubidium Atomic
- ▶ **Simultaneous Outputs:**  
1, 5, 10 MHz
- ▶ **Time Code Output:**  
IRIG A, B or G  
Simultaneous DC Shift  
and modulated
- ▶ **Event Time Trigger**
- ▶ **Event Time Tag**

#### Rear Panel View



AC Power Supply

Event Trigger, Time Tag, 1 PPS  
Time Code, Frequency Outputs

FEI-Zyfer, Inc.

7321 Lincoln Way Garden Grove CA 92841

Toll-free 888-886-7465

E-mail: [sales@fei-zyfer.com](mailto:sales@fei-zyfer.com)

[www.fei-zyfer.com](http://www.fei-zyfer.com)

## GPStarplus® Specifications

### Output Specifications (a)

#### 1 PPS Output, Qty 1, BNC Connector:

Wave Shape:	Pulse
Pulse Width:	2 ms
Level:	TTL into 50Ω
Synchronization:	Rising edge on-time
Accuracy, Time locked:	100 ns referenced to UTC
Coasting, Rubidium Osc:	4.3 μs per day
Coasting, Quartz Osc:	10 μs per day
Jitter:	1 ns

#### Event Trigger Output, Qty 1, BNC Connector:

Wave Shape:	Pulse
Level:	TTL into 50Ω
Start Time:	To 1 year, 100 ns resolution

#### Time Tag Input, Qty 1, BNC Connector:

Input Signal:	0 to +5V into 10kΩ
Input Pulse Width:	100 ns min.
Dwell Time:	2 ms between events
Buffer Size:	256
Tag Rate:	500/second maximum

#### Rate Output, Qty 2, BNC Connectors:

1, 10, 100 PPS:	1, 10, 100 KPPS; 1, 5, 10 MPPS and others
Wave Shape:	Pulse
Level:	TTL into 50Ω
On Time Edge:	Rising or falling, selectable

#### AC Time Code, Qty 1, BNC Connector:

Signal Type:	Modulated sine wave
Code Format:	IRIG A, B or G, user selectable
Level:	3V p-p into 50Ω

#### DC Time Code, Qty 1, BNC Connector:

Signal Type:	DC Shift
Code Format:	Same as selected AC time code
Level:	TTL into 50Ω

### Power Options

AC Power:	100 - 240 VAC, 50/60 Hz, 50W max.
DC Power:	Contact Factory

### Output Specifications, cont.

#### Frequency Outputs, Qty 3, BNC Connectors

Wave Shape:	Sinusoid
Amplitude:	12 dBm +/- 0.5 dBm into 50Ω
Frequency:	1, 5 or 10 MHz, user selectable
Harmonics:	-40 dBc
Spurious Level:	-70 dBc
Accuracy:	Rubidium Osc. Quartz Osc.
Time Locked:	1E-12 5E-12
Coasting (per day):	2E-11 5E-10
Short Term Stability (1-100 SEC):	5E-11 3E-10

#### Phase Noise (dBc/Hz, typical):

1 Hz:	-80
10 Hz:	-100
100 Hz:	-105
1 kHz to 100 kHz:	-115

#### I/O Control Port/TOD Output:

Connector:	DA-15
Signal Levels:	RS-232C
I/O Control:	9600, 19200, 38400 Baud
TOD:	9600 Baud
Protocol:	1 Start bit, 8 Data bits, 1 Stop bit, No Parity

### Standard GPS Receiver - Civil C/A Code

8 Channel L1 - TNC Female Connector

### Chassis Dimensions

Height:	44 mm (1.75") (1U)
Width:	438 mm (17.25") (19" EIA Rack)
Depth:	310 mm (12.2") including connectors
Weight:	7.2 lbs. (max.)

### Environmental

Operating Temperature:	0°C to 55°C
Rate of Change:	10°C / Hour
Storage Temperature:	-40°C to +85°C
Relative Humidity:	5% to 95%, non-condensing

### Certifications



### Notes:

- (a) After 72 hours of GPS locked operation, fixed antenna location, antenna delays entered.
- (b) After constant ambient temperature.
- (c) 95.0% probability.
- (d) One day average.