

Uncontrolled document as of September 27, 2008. Refer to website for up to date specifications.

LIGHTS
1930
L1 LED



L1 1930 LED Flashlight


With a long lamp life and extended battery burn time, you won't be left in the dark with the L1 flashlight. The polycarbonate body is resistant to chemicals, water and corrosion. The convenient tail switch for constant on/momentary is easy to operate. The L1 is perfect for close quarter use. Packaged with 4 LR 44 1.5V alkaline coin cells, a break-a-way safety lanyard, and colored lens discs to preserve night vision. This handy flashlight offers a lot for its size.

Minimum Pack 12 ea.
Packaged Weight: 0.8 oz.

NSN #6230-01-491-0793

L1 1930 LED Flashlight Configurations

Cat. #	Description
1930	L1 1930 LED Flashlight (Carded)
1940C	L1 LED 1940 Knife/Lite Combo
1945C	L1 LED 1945 and Attachment System
1930M	L1 1930 LED Flashlight Merchandiser Display



L1 1930 LED Flashlight Specifications

Light Source	Tested Lumen Value	Tested Lux Value (@ 1 meter)
LED	9.0	N/A
Batteries	Battery Burn Time	Battery Pack/Charging Time
4 LR 44 Alkaline (Included)	130 hrs.	N/A
Watts	Voltage	
0.2	6	
Length	Weight w/Batteries	Weight w/o Batteries
2.64" (6.7 cm)	0.9 oz. (0.03 kg)	0.63 oz. (0.02 kg)

L1 1930 LED Flashlight Approvals



Listed 4S67/E184884 Class I, Div. 1 Gps.A,B,C,D, .



Ex ia IIC T4 IP65 IEC Ex TSA 06.0021X

L1 1930 LED Flashlight Accessories

Cat. #	Description	Sug. Retail
1939	Four 1.5V Alkaline Coin Cell Batteries	US\$6.50
1946B	L1 1930 LED Attachment Kit	US\$14.50

Pelican™ Products, Inc.

23215 Early Avenue • Torrance, CA 90505 • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
e-mail: sales@pelican.com • www.pelican.com