

Uncontrolled document as of September 27, 2008. Refer to website for up to date specifications.

CASES 1630 Transport Case



1630 Transport Case

- **Watertight, crushproof, and dust proof**
- Easy open Double Throw latches
- Open cell core with solid wall design - strong, light weight
- O-ring seal
- Automatic Pressure Equalization Valve
- Fold down handles
- Stainless steel padlock protectors
- 3 level Pick 'N' Pluck™ with convoluted lid foam
- Personalized nameplate service available
- Lifetime Guarantee of Excellence
- **Retractable extension handle**
- **4 strong polyurethane wheels with stainless steel bearings**

1630 Transport Case Configurations

Cat. #	Description
1630	1630 Transport Case
1630NF	1630 Transport Case (No foam)
1634	1630 Transport Case with Padded Dividers



Black



OD Green*



Desert Tan

*OD Green available upon request

1630 Transport Case Specifications

Exterior Dimensions (L x W x D)		Interior Dimensions (L x W x D)	
31.28" x 24.21" x 17.48" (79.4 x 61.5 x 44.4 cm)		27.70" x 20.98" x 15.50" (70.3 x 53.3 x 39.4 cm)	
<i>This case has internal wheel and/or handle wells that will reduce usable area. Please review for each application.</i>			
Lid Depth	Bottom Depth	Total Depth	
3.25" (8.3 cm)	12.14" (30.8 cm)	15.50" (39.4 cm)	
Weight with Foam	Weight without Foam	Buoyancy Max.	
36 lbs. (16.33 kg)	31 lbs. (14.06 kg)	350 lbs. (158.76 kg)	
Range Temperature	No. of Wheels		
-10 / 210° F (-23 / 99° C)	4		

Personalized Nameplate Available

1630 Transport Case Certificates

- IP67 (1 meter submersion for 30 minutes)
- Def Stan 81-41/STANAG 4280

1630 Transport Case Accessories

Cat. #	Description	Sug. Retail
1630DC	Document Container Accessory	US\$0.00
1631	5 pc. Replacement Foam Set	US\$144.95
1632	Pick 'N' Pluck™ Sections Only (set of 3)	US\$126.95
1633	Replacement O-ring	US\$8.50
1635	Padded Divider Set Only	US\$219.95

Pelican™ Products, Inc.

23215 Early Avenue • Torrance, CA 90505 • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
e-mail: sales@pelican.com • www.pelican.com