Uncontrolled document as of September 27, 2008. Refer to website for up to date specifications.







#### 1660 Case

- Watertight, crushproof, and dust proof
- Easy open Double Throw latches
- · Open cell core with solid wall design strong, light weight
- O-ring seal
- Automatic Pressure Equalization Valve
- Large 2-person fold down handles
- Stainless steel hardware and padlock protectors
- 3 level Pick 'N' Pluck™ with convoluted lid foam
- Personalized nameplate service available
- Lifetime Guarantee of Excellence
- Retractable extension handle
- 4 strong polyurethane wheels with stainless steel bearings

### **1660 Case Configurations**

| Cat. # | Description                    |
|--------|--------------------------------|
| 1660   | 1660 Case                      |
| 1660NF | 1660 Case (No foam)            |
| 1664   | 1660 Case with Padded Dividers |







OD Green\* Desert Tan
\*OD Green available upon request

## 1660 Case Specifications

Exterior Dimensions (L x W x D)

31.50" x 22.87" x 19.00" (80 x 58.1 x 48.2 cm)

This case has internal wheel and/or handle wells that will reduce usable area. Please review for each application.

 Lid Depth
 Bottom Depth
 Total Depth

 3.50" (8.9 cm)
 14.12" (35.9 cm)
 17.62" (44.7 cm)

 Weight with Foam
 Weight without Foam
 Buoyancy Max.

 42.11 lbs. (19.1 kg)
 34.17 lbs. (15.5 kg)
 350.1 lbs. (158.8 kg)

Range Temperature
No. of Wheels
-10 / 210° F
4

#### Personalized Nameplate Available

# **1660 Case Certificates**

(-23 / 99° C)

- IP67 (1 meter submersion for 30 minutes)
- Def Stan 81-41/STANAG 4280

### 1660 Case Accessories

| Cat. # | Description                              | Sug. Retail |
|--------|--|-------------|
| 1661   | 5 pc. Replacement Foam Set               | US\$156.95  |
| 1662   | Pick 'N' Pluck™ Sections Only (set of 3) | US\$131.95  |
| 1663   | Replacement O-ring                       | US\$8.80    |
| 1665   | Padded Divider Set Only                  | US\$275.95  |
| 1669   | Photo/Lid Organizer for 1660 Case        | US\$63.95   |