Uncontrolled document as of September 27, 2008. Refer to website for up to date specifications.







1690 Transport Case

- Watertight, crushproof, and dust proof
- Easy open Double Throw latches
- · Open cell core with solid wall design strong, light weight
- O-ring seal
- Automatic Pressure Equalization Valve
- Large 2-person fold down handles
- Stainless steel padlock protectors
- 3 level Pick 'N' Pluck™ with convoluted lid foam
- Personalized nameplate service available
- Lifetime Guarantee of Excellence
- Retractable extension handle
- 4 strong polyurethane wheels with stainless steel bearings

1690 Transport Case Configurations

Cat. #	Description
1690	1690 Transport Case
1690NF	1690 Transport Case (No foam)
1694	1690 Transport Case with Padded Dividers







OD Green* Desert Tan
*OD Green available upon request

1690 Transport Case Specifications

Exterior Dimensions (L x W x D)	Interior Dimensions (L x W x D)			
33.36" x 28.44" x 18.23" (84.7 x 72.2 x 46.3 cm) 30.01" x 25.02" x 15.00" (76.2 x 63.5 x 38.1 cm) This case has internal wheel and/or handle wells that will reduce usable area. Please review for each application.				
Lid Depth	Bottom Depth	Total Depth		
2.86" (7.3 cm)	12.14" (30.8 cm)	15.00" (38.1 cm)		

Weight with Foam	Weight without Foam	Buoyancy Max.
43 lbs. (19.5 kg)	34 lbs. (15.42 kg)	410 lbs. (185.97 kg)

Range Temperature	No. of Wheels
-10 / 210° F	4

Personalized Nameplate Available

1690 Transport Case Certificates

- IP67 (1 meter submersion for 30 minutes)
- Def Stan 81-41/STANAG 4280

(-23 / 99° C)

1690 Transport Case Accessories

1000 114	Too Transport Gas Accessories		
Cat. #	Description	Sug. Retail	
1691	5 pc. Replacement Foam Set	US\$219.95	
1692	Pick 'N' Pluck™ Sections Only (set of 3)	US\$175.95	
1693	Replacement O-ring	US\$9.75	
1695	Padded Divider Set Only	US\$309.95	
1699	Lid Organizer for 1690 Case	US\$66.95	