


标准型气缸/直接安装 (内置磁环) Standard Air Cylinder/ Direct Mount (Built-in Magnet) Series **KCM2R (Ø20~Ø40)**



规格 Specifications

缸径 Bore size (mm)	20	25	32	40
接管口径 Port size Rc(PT)	1/8			1/4
使用流体 Fluid	过滤洁净空气 Filtered clean air			
动作形式 Action	双动 Double acting			
保证耐压力 Proof pressure (MPa)	1.5			
使用压力范围 Operating pressure range (MPa)	0.05~1.0			
环境及流体温度 Ambient and fluid temperature	-5~60°C (未冻结 No freezing)			
活塞速度 Piston speed	50~500 mm/s			
缓冲 Cushion	橡胶缓冲 Rubber bumper			
行程公差 Stroke tolerance (mm)	+1.4 0			
* 润滑 Lubrication	不需要 Not required			

* 如需要润滑请使用透平 1 号油 ISOVG32。Please use Turbine oil 1st Grade ISOVG32 if necessary.

行程 / 磁性开关 Stroke/ Auto switch

缸径 Bore size (mm)	标准行程 Standard stroke (mm)	磁性开关 / 固定钢带 Auto switch/ Band mounting
20	25, 50, 75, 100, 125, 150	D-C73K/PBK D-Z80K/ PBC-S
25, 32	25, 50, 75, 100, 125, 150, 200	
40	25, 50, 75, 100, 125, 150, 200, 250, 300	

* 非标行程可定制。Nonstandard stroke can be customized.

型号表示方法 How to Order

KCM2R **A** **32** - **75** - **C73KL** **S**

固定类型 Mounting

A	底面固定型 Bottom mounting
B	前面固定型 Front mounting

行程 Stroke (mm)

缸径 Bore size (mm)

磁性开关数量 No. of auto switches

-	2
S	1
3	3

磁性开关 Auto switch

C73KL	D-C73KL	有接点型 Reed switch
Z80K	D-Z80K	
C73KD	D-C73KD	两线式无接点 2-wire, solid state
Z80KD	D-Z80KD	
C73KN	D-C73KN	NPN 无接点 NPN solid state output
Z80KN	D-Z80KN	
C73KP	D-C73KP	PNP 无接点 PNP solid state output
Z80KP	D-Z80KP	

