



规格 Specifications

型号 Model	KAR20
使用流体 Fluid	压缩空气 Compressed air
保证耐压力 Proof pressure	1.5 MPa
最高使用压力 Maximum operating pressure	1.0 MPa
调压范围 Regulating pressure range	0.05~1.0 MPa (标准 Standard)
环境及流体温度 Ambient and fluid temperature	5~60°C
阀型结构 Construction	带溢流型 Relieving type

型号 Model	规格 Specifications					配件 Accessories	
	* 额定流量 Flow rate (l/min)	接管口径 Port size Rc(PT)	压力表口径 Port size of gauge Rc(PT)	调压范围 Regulating pressure range (MPa)	质量 Weight (kg)	支架 Bracket	压力表 (任选) Gauge (Option)
KAR20-01	450	1/8	1/8	0.05~1.0	0.17	配置 Equipped	KG40-10-01
KAR20-01-2KG	450			0.015~0.2	0.17		KG40-02-01
KAR20-01-4KG	450			0.05~0.4	0.17		KG40-04-01
KAR20-01-7KG	450			0.05~0.7	0.17		KG40-10-01
KAR20-02	450	1/4		0.05~1.0	0.17		KG40-10-01
KAR20-02-2KG	450			0.015~0.2	0.17		KG40-02-01
KAR20-02-4KG	450			0.05~0.4	0.17		KG40-04-01
KAR20-02-7KG	450			0.05~0.7	0.17		KG40-10-01

* 额定流量指进气压力为 0.7MPa，二次侧压力设定 0.5MPa 的条件下。
Flow rate is at supply pressure 0.7 MPa and secondary pressure setting 0.5 MPa

外形尺寸图 Dimensions (mm)

