


3通直动型电磁阀 (微型) 3-Port Direct Operated Solenoid Valve (Miniature) Series KGM215



型号表示 How To Order

KGM215 – L – 10 – DC12V

接电形式 Electrical Entry

D 插座式安裝 Plug
L L型垂直插座式
90 Degree Connected
M M型平行插座式
180 Degree Connected

引线长度 Wire Length
0: 只提供簧片及插件
3: 300mm
6: 600mm
10: 1000mm

使用电压
Voltage
DC12V
DC24V




规格 Specifications

型号	Model	KGM215
工作压力范围	Operating Press. Range	0~0.7 MPa
通径	Orifice (mm)	Ø1.6
环境温度	Ambient Temperature	-5°C~50°C (未冻结 No Freezing)
最大操作频率	Max. Working Frequency	5c/sec
* 润滑	Lubrication	不需要 Not Required
响应时间	Response Time	10~12ms
额定电压	Rated Voltage	DC12V, DC24V
电压波动范围	Voltage Tolerance	-5%~+10%
功率消耗	Power Consumption	2.3w
安装螺栓	Bolt	标准供给 M3×0.5




* 若需要润滑请用透平1号油ISOVG32
Use Turbine Oil 1st-grade ISOVG32, if necessary.

外形尺寸图 Dimensions (mm)




插座式
KGM215-D



M型平行插座式
KGM215-M



L型垂直插座式
KGM215-L



汇流板外形尺寸图

Manifold Dimensions (mm)

