


ARK 3通直动型电磁阀

3 Port Direct Operated Solenoid Valve

Series KVT307



型号表示 How to Order

KVT307 - 4 GZ - 0 2

额定电压
Rated voltage
3 AC110V
4 AC220V
5 DC24V
6 DC12V

接电形式
Electric connector
GZ 直接出线带指示灯
Grommet with LED
D DIN插座式
DIN Connector
DZ DIN插座式带指示灯
DIN Connector with LED

规格 Specifications

型号 Model		KSV307
		3/2 N.C./N.O.
接管口径 Port size		Rc(PT) 1/4"
流体 Fluid		空气 Air
工作压力范围 Operating pressure range		0~0.7 MPa
环境及流体温度 Ambient and fluid temperature		-10~50°C (未冻结 No freezing)
响应时间 Response time (压力0.5MPa) (Pressure: 0.5 MPa)		≤20 ms
最大操作频率 Maximum working frequency		10 c/sec
* 润滑 Lubrication		不需要 Not required
手动方式 Manual override		无锁定按钮 Lock-free push button
额定电压 Rated voltage		AC220V, AC110V, DC24V, DC12V
容许电压波动范围 Allowable voltage fluctuation		-15%~10%额定电压 -15%~10% of rated voltage
线圈绝缘类型 Coil insulation type		等同F级 Equivalent to Class F
功率消耗 Power consumption	交流 AC	持续 Holding 5.0 VA
	直流 DC	4.0 W

* 如需要润滑请用透平1号油ISOVG32。Please use turbine oil 1st Grade ISOVG32 if necessary.

外形尺寸图 Dimensions (mm)

