

LANGOFLEX PET-HD



Mobility

Langoflex PET-HD is a braided sleeve designed to protect cables exposed to very high levels of abrasion. This product is expandable and easy to install and has high density construction.



- Mechanical & Abrasion protection
- Very high abrasion resistance
- High density construction



- **Product family:**
Expandable Sleeving
- **Construction:**
Braided
- **Materials:**
PET .010" (0.25mm) monofilament



Environments


- Interior
- Engine
- HEV/EV
- Battery
- Cooling System
- HVAC
- Brake
- Fuel

PHYSICAL PROPERTIES

Properties	Test Method	Result
Standard colors without stripe	-	Black, orange
Long term aging (3000h)	-	150°C
Short term aging (240h)	-	175°C
Abrasion resistance	MBN LV 312-3, VW 60360-3, GS 95008-3-3	class F
Flammability	FMVSS 302	0 mm/min

DIMENSIONS

Designation	Nominal A Ø (mm)	Maximum B Ø (mm)	Coverage
LANGOFLEX PET-HD 04	4	8	> 90%
LANGOFLEX PET-HD 05	5	9	
LANGOFLEX PET-HD 08	8	11	
LANGOFLEX PET-HD 10	10	13	
LANGOFLEX PET-HD 12	12	17	
LANGOFLEX PET-HD 14	14	18	
LANGOFLEX PET-HD 16	16	20	
LANGOFLEX PET-HD 18	18	26	
LANGOFLEX PET-HD 25	25	34	
LANGOFLEX PET-HD 30	30	42	
LANGOFLEX PET-HD 40	40	51	
LANGOFLEX PET-HD 70	70	80	



DELFINEN LANGOFLEX PET-HD_EN_v4.0

PACKAGING

Coils
Cut lengths upon request