



## LANGOFLEX PET/PA-D



Mobility

Langoflex PET/PA is a braided sleeve made of both Polyester and Polyamide. This product has been designed to protect cables exposed to very high levels of abrasion, his dense construction allows expandable properties and easy installation.



- Mechanical & Abrasion protection
- Very high abrasion resistance
- Dense construction



- **Product family:** Expandable Sleeving
- **Construction:** Braided
- **Materials:**  
PET .010" (0.25 mm)  
duo monofilament  
PA .015" (0.38mm)  
monofilament



### Environments

- Interior
- Engine
- HEV/EV
- Battery
- Cooling System
- HVAC
- Brake
- Fuel




## PHYSICAL PROPERTIES

Properties	Test Method	Result
Standard colors without stripe	-	Black
Long term aging (3000h)	-	150°C
Short term aging (240h)	-	175°C
Abrasion resistance	GMW 14327	Category 6
Flammability	SAE J 369	self-extinguishing

## DIMENSIONS

Designation	Nominal A Ø (mm)	Maximum B Ø (mm)
LANGOFLEX PET/PA-D 06	6	9
LANGOFLEX PET/PA-D 08	8	14
LANGOFLEX PET/PA-D 10	10	15
LANGOFLEX PET/PA-D 13	13	18
LANGOFLEX PET/PA-D 16	16	25
LANGOFLEX PET/PA-D 19	19	29
LANGOFLEX PET/PA-D 25	25	36
LANGOFLEX PET/PA-D 32	32	40
LANGOFLEX PET/PA-D 38	38	57
LANGOFLEX PET/PA-D 44	44	70
LANGOFLEX PET/PA-D 50	50	70
LANGOFLEX PET/PA-D 63	63	80



DELFINGEN\_LANGOFLEX PET/PA-D\_EN\_v4.0

Data and photos for information only. Delfingen makes no warranties as to the accuracy or completeness of this information. Delfingen reserves the right to make changes in materials or processing without notifications.

## PACKAGING

Coils  
Cut lengths upon request