


BSVR系列 Series

超小型大功率继电器
Subminiature power power relay



专利证书: ZL 2011 2 0054622.4

产品特点

- 高触点容量2A触点切换能力,产品类型结构为2C
High contact capacity 2A contact switching capability. Product type is 2C
- 超小型 (20.4×9.9×11.1) 标准印刷版引出脚
Subminiature(20.4×9.9×11.1) standard printing plate lead out pin
- 塑封型和防焊剂型可选择
plastic sealing type and anti flux type are optional
- 选择耐高温环保材料, 更好的提高产品稳定性
Select high temperature resistant and environment-friendly materials to better improve the stability of products
- 符合REACH ROHS 指令,
Comply with reach RoHS Directive,
- BSVR系列产品浪涌电压为10000V
The surge voltage of BSVR series products is 10000V

触点负载 Contact Rating	
触点形式 contact form	2C
触点材料 contact material	银合金 AgSn02
额定负载(阻性) Rated load (Resistance)	1A 125VAC 2A 30VDC
最大切换电压 Max. switching Voltage	125VAC/30VDC
最大切换电流 Max. switching Current	2A
最大切换功率 Max. switching power	125VA/60W
电耐久性 Electrical durability	5×10 ⁴ 次 1A125VAC 阻性, 室温1S ON/9S OFF
机械耐久性Mechanical	1×10 ⁷ 次 每小时10800次

备注: 1. 上述值为初始值
remarks: The above values are initial values

安规认证Safety certification

UL/CUL E332719	1A 250VAC 2A 30VDC
TUV R50262654	1A 250VA 2A 30VDC

典型用途Typical use

- 安全报警系统、医疗设备
Safety alarm system, medical equipment
- 通讯设备、办公设备、电脑周边设备
Communication equipment office equipment
Computer peripherals

性能参数Performance Parameter		
绝缘电阻 Insulation resistance		1000MΩ (500VDC)
吸合时间 (额定电压下) Operate Time		≤7ms
释放时间 (额定电压下) Release Time		≤4ms
介质耐压 Dielectric Strength	断开的触点间BOC	750VAC 50/60Hz 1分钟
	触点与线圈间BCC	1000VAC 50/60Hz 1分钟
湿度 humidity		5%~85%RH
温度范围Temperature Range		-30℃~90℃ (不结冰) NO freezing
冲击 Shock	稳定性 Error Operation	98m/s ²
	强度Endurance	980m/s ²
接触电阻 Contact Resistance		≤100mΩ (1A 6VDC)
浪涌电压 (线圈与触点间) Surge voltage (BCC)		10KV (1.2/50us)
线圈温升 Coil temperature rise		35℃ Max
振动vibration		10Hz~55Hz 1.5mm双振幅
封装方式Type of Sealing		防尘罩型The flux type
重量Weight		约5.5克 about 5.5g

BSVR系列 Seris

超小型大功率继电器
Subminiature power power relay

线圈参数Coil Specification (at 23 °C)

线圈灵敏度 Coil sensitivity	额定电压 Nominal Voltage (VDC)	额定电流 Rated current (mA)	线圈电阻 Coil Resistance (Ω ±10%)	额定功率 Rated power (w)	吸合电压 Pull-In Voltage (Max)	释放电压 Drop-Out Voltage (Min)	最大电压 Maximum Voltage (Max)
BSVR-L	3	66.6	45	约0.2W about	额定电压的 Rated voltage 75%	额定电压的 Rated voltage 10%	额定电压的 Rated voltage 130%
	5	40	125				
	6	33.3	180				
	9	22.2	405				
	12	16.6	720				
	24	8.3	2880				

备注：1. 上述值为初始值remarks:The above values are initial values

2. 最大电压是指继电器线圈在短时间内能够承受的最大值

The maximum voltage refers to the maximum value that the relay coil can withstand in a short time

订货标记Ordering Information

BSVR - SS - 2 12 L	触点形式: 无:转换型 Con tact form:NO: IO
	线圈功耗: L:高灵敏度标准直流线圈 Coil power: L:High sensitivity DC coil
	线圈电压: 03:3V, 05:5V,06:6V,09:9V Coil oltage: 12:12V,24:24V
	触点组数:2:2 组 Numbe of pole:2:2-One pole
	密封方式: SS:防焊剂型 Type of sealing: SS:The flux type
	品名: BSVR Model: BSVR

备注：

1. 在洁净环境（不含H2S、SO2、NO2、粉尘等污染物）下使用时，推荐使用防焊剂型产品
2. 在污染焊剂（含一定量的H2S、SO2、NO2粉尘等污染物）下使用时建议选用塑封产品，并请在实际使用中进行确
3. 当继电器装入PCB版焊接后，如需进行整体清洗或表面处理，请与我司联系，以便商定合适的焊接条件、合格的产品规格。


remarks:

- (1)When using in clean enbironment （without H2S SO2 NO2 dust and other pollutants), it is recommended to Use flux resistant products. When using in polluted environ ment(with a certain amount of H2 SO2 NO2dust and other pollutants), it is recom mended to use plastic encapsulated products.please confirm in act
- (2)After the relay is installed into the PCB board for welding, if it needs overall cleaning or surface treatment, please Contact me to negotiate the appropriate welding conditions and product specifications.


型号	BSVR
线圈灵敏度 Coil sensitivity	标准直流线圈 Standare DC coil 2C
防焊剂型 The flux type	BSVR-SS-2□□L

外形尺寸、接线、安装孔位图


Overall dimension, wiring and installation hole bitmap



接线图(底视图)
Installation hole
bitmap



安装孔位图(底视图)
Installation hole
bitmap






备注:

1. 产品外形图的引脚标注尺寸为沾锡前尺寸（沾锡后会变大），安装孔尺寸为推荐的PCB板孔的设计尺寸，具体PCB板孔设计尺寸可根据产品实物进行测绘、调整。
2. 产品部分外形尺寸未注尺寸公差，当外形尺寸 $\leq 1\text{mm}$ ，公差为 $\pm 0.2\text{mm}$ ；当外形尺寸在 $(1\sim 5)\text{mm}$ 之间时，公差为 $\pm 0.3\text{mm}$ ；当外形尺寸 $> 5\text{mm}$ ，公差为 $\pm 0.4\text{mm}$
3. 安装孔尺寸中未注尺寸公差为 $\pm 0.1\text{mm}$

DISCLAIMER:

1. The pin dimension in the outline drawing or the product is the dimension before dipping tin (It gets bigger when stained with tin) The size of mounting hole is the recommended design size of PCB hole The specific PCB hole design size can be mapped and adjusted according to the actual product
2. The overall dimension of the product if not marked with dimensional tolerance, when the overall dimension $\leq 1\text{mm}$ Tolerance is $\pm 0.2\text{mm}$ When the overall dimension is $(1\sim 5)\text{mm}$ Between Tolerance is $\pm 0.3\text{mm}$ When the overall dimension $> 5\text{mm}$, Tolerance is $\pm 0.4\text{mm}$
3. The dimension tolerance of mounting hole without dimension injection is $\pm 0.1\text{mm}$

性能曲线图 Performance curve



备注:

本产品规格书仅供客户使用时参考，若有更改，恕不另行通知。

对科信而言，不可能评定继电器在每个具体应用领域的所有性能参数要求，因而客户应该根据具体的使用条件，选择与之相匹配的产品。若有疑问，请与科信联系 以便获取更多的技术支持。但产品选型责任仅由客户负责。

DISCLAIMER:

This product specification is for reference only and subject to change without prior notice.

For AFE, it is not possible to assess all performance requirements for relays in each specific application area and therefore the customer should select a suitable product for each specific application, please contact AFE for additional technical support. But the responsibility of product selection is only the responsibility of the customer.