


PP FDY
Machine



Machine Design:

Design	1pos,6ends(HT)	2pos,6ends(HT)
Denier	840D	840D
Extruder Size	90mm	110mm
Capacity	1550kgs/day	3100kgs/day
Speed	2000m/min	2000m/min
Winder Size	1200mm	1200mm
Connection Load	130kva	220kva
Chiller Capacity	6000kca/h	12000kca/h
Air compressor	6M3/min 8kg	12M3/min 8kg
Power Consumption	900 kwh/ton	900 kwh/ton
Wastage	2%	2%



Application: Ropes, Belt, Protective Net&Belt,
Sewing Threading etc.
Denier Range: 300–5000D;
Tenacity: ≥7 g/d Max. ;

Model	Ends	Capacity (kg/day)	Connection Lond(kw)	Power consumption (kw)	Machine Size
HTC-140	4	1400	135	45	4150*5300*5600
HTC-240	2*4	2800	220	75	6400*7500*5800
HTC-260	2*6	4200	300	100	7400*8200*5800

Suzhou SAMEC Industries Pvt Limited

📍 No.1609, Xiangcheng Rd. R2507, Suzhou City, Jiangsu Province China
✉ info@samecind.com ☎ +86 512 69574909 🌐 www.samecind.com