

E3 SERIES CHARGING Pile

VeKON Technology
Secure your charging safety !



Product Characteristics

- With exquisite appearance, its hand-held design is in line with principles of ergonomics, easy to plug in and pull out.
- It conforms to IEC61851-1 standard.
- Optional for black and white.
- With built-in DIN rail controller and type B RCCB, safer and more stable than traditional PCBA solution.
- A new solution: type A RCD+RCMU also available upon request.
- Super low noise solution of charger available upon request.

Model Meaning

E3	T ☐	☐	32	☐
E3 series	1-American Standard; 2-European standard	2-single phase socket outlet; 4-three phase socket outlet; 1-single phase Tethered; 3-three phase Tethered	Maximum current:32A	W:white B:black

Main Technical Parameters

	E3T1132/E3T2132	E3T2332	E3T2232	E3T2432
AC power	1P+N+PE	3P+N+PE	1P+N+PE	3P+N+PE
Power supply Voltage	AC230~±10%	AC400~±10%	AC230~±10%	AC400~±10%
Rated current	10-32A	10-32A	10-32A	10-32A
Maximum power	7.4kW	22kW	7.4kW	22kW
Frequency	50-60Hz	50-60Hz	50-60Hz	50-60Hz
Cable length	5m	5m	0m	0m
Mode	Type 1/Type 2	Type 2	Type 2	Type 2
Weight	5.6Kg	6.8Kg	3.45Kg	3.7Kg
IPgrade	IP55	IP55	IP55	IP55
Working temperatur	-40°C ~45°C	-40°C ~45°C	-40°C ~45°C	-40°C ~45°C
Cooling mode	Natural cooling	Natural cooling	Natural cooling	Natural cooling

Appearance And Installation Size

