


# 1、MECHANICAL (产品外观结构)



ORDER INFORMATION:  
 SK02-G41 1 008B NL (Y/N)  
 A B C D E F

A: IT STANDS FOR THE DIFFERENT R145 DESIGNING OF COMPANY, SUCH AS "SK" STANDS FOR COMPANY BUT "XX" STANDS FOR THE SERIES NUMBER OF DIFFERENT PRODUCTS.  
 B: THE PARTS ARE SINGLE OR MULTIPORTS, SUCH AS SK01-11XXXX, IT MEANS 1X1 SINGLE PORT, SK01-21XXXX MEANS 2X1 OR 1X2, IT IS A DUAL PORTS R145 FILTERED CONNECTOR. "G" THE MEAN IS 1000BASE REQUIREMENT.  
 C: TELLS IT IS ALLEDS VERSION OR NOT, "1" MEANS WITH LEDS, "0" OR ELSE IS WITHOUT LEDS.  
 D: IT STANDS FOR THE PARTS'S SERIES NO.  
 E: NL=ROHS COMPLAINT.  
 F: CONTACT PLATING CODE: NORMAL TYPE IS NO MARK, IT STANDS THANDS THE CONTACT AREA OF CONTACT PIN IS 6U" GOLD PLATING, MORE THAN 6U" NEED MARK 15 OR 30 OR 50, ETC.

REV.	DESCRIPTION	ECN NO.	DATE
A	FIRST RELEASE		2013.09.06

## GENERAL SPECIFICATION

### DESCRIPTION

- ◆ 10/100 BASE-TX RJ45 1\*4 TAB-DOWN WITH LEDS INTEGRATED MAGNETICS CONNECTOR ICM.

### FEATURES AND BENEFITS

- ◆ ROHS PEAK WAVE SOLDER TEMPERATURE RATING 260° C.
- ◆ RJ45 1\*4 10-PIN WITH INTERNAL MAGNETIC;
- ◆ SUITABLE FOR CAT5 AND CAT6 FAST ETHERNET CABLE OR BETTER UTP.
- ◆ INTERNAL MANETICS: 100%ELECTRONICALLY TESTED FOR HI POTAND FUNCTIONALITY.

### ELECTRICAL PERFORMANCE SUMMARY

- ◆ MEETS IEEB802.3 SPECIFICATION AND 350uH MINIMUM OCL WITH 8mA BIAS CURRENT.
- ◆ HIGH PERFORMANCE FOR MAXIMUM EMI SUPPRESSION.

### TEMPERATURE PERFORMANCE

- ◆ STORAGE TEMPERATURE RANGE: -25° C TO +85° C.
- ◆ OPERATION TEMPERATURE RANGE: 0° C TO +70° C.

### MATERIAL SPECIFICATION

- ◆ SHIELD: BRASS, 0.2mm THICKNESS WITH NICKEL PLATED.
- ◆ HOUSING: PBT (30% GLASS FIBER, UL94V-0)。
- ◆ SOLDERING MATERIAL: 99.3%Sn0.3%Cu.
- ◆ CONTACT: PHOSPHOR BRONZE, 0.35mm THICKNESS, HARD GOLD PLATED OVER TIN GOLD PLATING:

- TIN GOLD PLATING:  
 3 μ " INCH  6 μ " INCH   
 15 μ " INCH  30 μ " INCH  50 μ " INCH

dimensi on	TOLERANCE RATE		
	A	B	C
0-4	±0.05	±0.10	±0.20
4-16	0.08	0.15	0.30
16-64	0.12	0.25	0.50
64-250	0.25	0.40	0.80


**CSAK**® ELECTRONICS CO., LTD

TITLE: 10/100/1000 BASE-TX 1\*4  
 TAB-DOWN RJ45 WITH LED

SIGNATURE		DATE	Page	PART NO:	
DRAWING	Li Hai	2013.09.18	1	SK02-G411008BNL	
CHECK	Li Zi Biao	2013.09.18	1		
APPROVED	SkyGuo	2013.09.18	Total 2		
				REV	DWG NO:
				A	CSAK-024G003



## 2、ELECTRONICAL (产品电子原理图)



ORDER INFORMATION:  
SK02-G41 1 008B NL -C/V/N  
A B C D E F

- A: IT STANDS FOR THE DIFFERENT RJ45 DESIGNING OF COMPANY , SUCH AS "SK" STANDS FOR COMPANY BUT "XX" STANDS FOR THE SERIES NUMBER OF DIFFERENT PRODUCTS.
- B: THE PARTS ARE SINGLE OR MULTIPORTS: SUCH AS SK01-11XXXX , IT MEANS 1X1 SINGLE PORT, SK01-21XXXX,MEANS 2X1 OR 1X2,IT IS ADUAL PORTS RJ45 FILTERED CONNECTOR. "G" THE MEAN IS 1000BASE REQUIREMENT.
- C: TELLS IT IS A LEDS VERSION OR NOT, "1" MEANS WITH LEDS, "0"OR ELSE IS WITHOUT LEDS.
- D: IT STANDS FOR THE PARTS 'S SERIES NO.
- E: NL=ROHS COMPLAINT
- F: CONTACT PLATING CODE: NORMAL TYPE IS NO MARK , IT STANDS THANDS THE CONTACT AREA OF CONTACT PINS IS 6U" GOLD PLATING, MORE THAN 6U" NEED MARK 15 OR 30 OR 50, ETC.

REV.	DESCRIPTION	ECN NO.	DATE
A	FIRST RELEASE		2013.09.06



## ELECTRICAL SPECIFICATIONS

- ◆ ALL TEST CONDITIONS@25°C UNLESS OTHERWISE NOTED.
- ◆ TURN RATIO:
  - TX, SECONDARY : PRIMARY= 1CT: 1CT ± 3%.
  - RX, SECONDARY : PRIMARY= 1CT: 1CT ± 3%.
- ◆ OCL: 350µH MIN, 8mA DC BIAS CURRENT.
- ◆ INSERTION LOSS: 1-100MHZ-1.0dB MAX.
- ◆ RETURN LOSS:
  - 1MHZ TO 10MHZ : -18dB MIN.
  - 10MHZ TO 30MHZ : -16dB MIN.
  - 30MHZ TO 60MHZ : -14dB MIN.
  - 60MHZ TO 80MHZ : -12dB MIN.
  - 80MHZ TO 100MHZ : -10dB MIN.
- ◆ CROSSTALK: 1MHZ TO 100MHZ : -35dB MIN.
- ◆ COMMON MODE REJECTION: 1-100MHZ : -35dB MIN.
- ◆ HIPOT: 1500V AC 1mA 1S.
- ◆ CAPACITOR: C=1000PF ± 20%.
- ◆ RESISTANCE: 75OHMS ± 20%.
- ◆ RESISTANCE OF COIL: 1.8OHMS MAX, 0.25OHMS MIN.
- ◆ LEFT LED COLOR: YELLOW; RIGHT LED COLOR: GREEN.

<b>CSAK</b> ® ELECTRONICS CO., LTD		TITLE: 10/100/1000 BASE-TX 1*4 TAB-DOWN RJ45 WITH LED	
SIGNATURE	DATE	Page	PART NO:
DRAWING L1 Hai	2013.09.18	2	SK02-G411008BNL
CHECK L1 Zi Biao	2013.09.18	Total	REV
APPROVED SkyGuo	2013.09.18	2	DWG NO: CSAK-024G003
			REV A