


特征 Features

- ◎ 经济塑料型
- ◎ 不锈钢滚轮，冲头及弹簧
- ◎ 特大 ± 95° 摇臂摆幅
- ◎ 导管连接器尺寸标配 M20 × 1.5
- ◎ Economical & plastic type
- ◎ Stainless steel roller, punch and spring
- ◎ Swing amplitude, extra large ± 95°
- ◎ M20x1.5 cable gland that can be equipped

接触形式 Contact form



额定值 Ratings

额定电压 Rated voltage	非电感性负载 Noninductive Load (A)				电感性负载 Inductive Load (A)			
	电阻性负载 Resistance Load		灯泡负载 Lamp Load		电感性负载 Inductive Load		马达负载 Motor Load	
	NC	NO	NC	NO	NC	NO	NC	NO
125VAC	5	5	1.5	0.7	3	3	2	1
250VAC	5	5	1	0.5	3	3	1.5	0.8
8VDC	5	5	3	3	5	4	3	3
14VDC	5	5	3	3	4	4	3	3
30VDC	5	5	3	3	4	4	3	3
125VDC	0.4	0.4						
250VDC	0.2	0.2						
突入电流 Inrush Current	N.C.:24A 以下、N.O.:12A 以下 N.C: below 24A, N.O: below 12A							

- 注：1、电感性负载之功率因素在 0.4 以上 (AC)。时间常数在 7msec 以下 (DC)。
2、灯泡负载之突入电流为稳定状态电流之 10 倍。马达负载之突入电流为稳定状态电流之 6 倍。
3、带弹簧系列产品，操作体的使用范围为从弹簧的前端到弹簧全长的 1/3 以内。

- NOTE: 1. Inductive load has a power factor of 0.4 min.(AC) and a time constant of 7 msec.max.(DC).
2. Lamp load has an inrush current of 10 times the steady-state current, while motor load has an inrush current of 6 times the steady-state current.
3. Product with spring, its usable range of operating part is within one third of the whole spring length from the front end of spring.

动作特性 Operating Characteristics

动作特性	Operating Characteristics	型号 Model	TLS	101 301	103 303	111 311	121 321	127 327	131 331	161 361	171 371	181 381	191 391
操作力	Operating force	OF 最大 (Max)		6.86N	6.86N	6.86N	4.9N	6.86N	4.9N	0.98N	0.98N	0.98N	4.9N
回弹力	Release force	RF 最小 (Min)		1.96N	1.96N	1.96N	0.98N	1.96N	0.98N	0.392N	0.392N	0.392N	0.98N
预行程	Pre-travel	PT 最大 (Max)		1.8mm	1.8mm	1.8mm	20°	20°	20°	30mm	30mm	30mm	20°
触发位置	Tripping position	TP ± 10%		2.0mm	2.0mm	2.0mm	22.5°	2.0mm	22.5°	22.5°	22.5°	22.5°	22.5°
行程移动分辨率	Movement differential	MD 最大 (Max)		1.2mm	1.2mm	1.2mm	10°	1.2mm	10°	14°	14°	14°	10°
触后行程	Over travel	OT 最小 (Min)		4.0mm	4.0mm	4.0mm	75°	4.0mm	75°	20mm	20mm	20mm	75°
累积总行程	Total travel	TT 最小 (Min)		5.8mm	5.8mm	5.8mm	95°	5.8mm	95°	50mm	50mm	50mm	95°
摇臂转换分角度	Rotary indexing						22.5°		22.5°				22.5°

外观和尺寸 Appearance and Dimension

TLS-101

TLS-131

TLS-103

TLS-161

TLS-111

TLS-171

TLS-121

TLS-181

TLS-127

TLS-191

外观和尺寸 Appearance and Dimension

