

16 Port PLC Splitter LGX



Features and Benefits:

- High Stability and Reliability
- Low-Input Polarization Sensitivity
- High-Quality Connector

PLC optical splitters reduce insertion loss and deliver high performance. These devices enable more effective monitoring and management of optical networks.

They are available as components, in our cassettes, or in custom modules and rack-mount designs.



16 Port PLC Splitter LGX

Ordering Information:

PLC - X 16 - - L

1

Select InPort Count
1xN
2xN

2

Select Connector
SA: SC/APC
SP: SC/UPC
LP: LC/UPC
WO: Without connector

3

Select Packing Type
A ABS: ABS type
L LGX: LGX type
M MINI: Mini type
R R-M: Rack-Mount type

Specifications:

Parameters		1x16 Port		
		Maximum		
Operating Wavelength		1260-1650 nm		
Insertion Loss		13.7 dB		
Insertion Loss Uniformity		1.2 dB		
Polarization Dependent Loss		0.2 dB		
Directivity		> 55 dB		
Return Loss		> 55 dB		
Operating Temperature		- 40°C to +85°C		
Storage Temperature		- 40°C to +85°C		
Shipping Package				
Packaging Dimensions:(HxWxL)mm	Mini Type	LGX Type	ABS Type	Rack Mount Type
1x16	4x12x60	50x100x130	18x80x120	43x250x430

16 Port PLC Splitter LGX



Mechanical Drawing 1x16 Splitter LGX:

