

8 Port PLC Splitter LGX



Features and Benefits:

- High Stability and Reliability
- Low-Input Polarization Sensitivity
- High-Quality Connector

PLC optical splitters reduce insertion loss and deliver high performance. These devices enable more effective monitoring and management of optical networks.

They are available as components, in our cassettes, or in custom modules and rack-mount designs.



Ordering Information:

PLC - X 8 - - L

1

Select InPort Count
1xN
2xN

2

Select Connector
SA: SC/APC
SP: SC/UPC
LP: LC/UPC
WO: Without connector

3

Select Packing Type
A ABS: ABS type
L LGX: LGX type
M MINI: Mini type
R R-M: Rack-Mount type

Specifications:

Parameters		1x8 Port		
		Maximum		
Operating Wavelength		1260-1650 nm		
Insertion Loss		10.5 dB		
Insertion Loss Uniformity		0.8 dB		
Polarization Dependent Loss		0.2 dB		
Directivity		> 55 dB		
Return Loss		> 55 dB		
Operating Temperature		- 40°C to +85°C		
Storage Temperature		- 40°C to +85°C		
Shipping Package				
Packaging Dimensions:(HxWxL)mm	Mini Type	LGX Type	ABS Type	Rack Mount Type
1x8	4x7x60	25x100x130	10x80x100	43x250x430

8 Port PLC Splitter LGX



Mechanical Drawing 1x8 Splitter LGX:

