



**Product:** [8777](#) 

Audio, Control & Instrument, #22-3pr, PO, Individ. Foil, PVC Jkt, CM

## Product Description

Audio, Control & Instrument Cable, 22 AWG stranded (7x30) tinned copper conductors, polypropylene insulation, twisted pairs individually Beldfoil® shielded (100% coverage), 22 AWG stranded tinned copper drain wire, PVC jacket.

## Technical Specifications

### Physical Characteristics (Overall)

#### Conductor

AWG	Stranding	Material	Nominal Diameter	No. of Pairs
22	7x30	TC - Tinned Copper	0.03 in	3

Conductor Count:	6
------------------	---

#### Insulation

Material	Nominal Wall Thickness
PP - Polypropylene	0.011 in

#### Color Chart

Number	Color
1	Black & Red
2	Black & White
3	Black & Green

#### Inner Shield Material

Type	Layer	Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG	Drainwire Construction n x D
Tape	1	Aluminum-Polyester	Beldfoil®	100 %	TC - Tinned Copper	22	7x30
Tape	2	Polyester		100.0 %			

#### Outer Shield Material

Material
Unshielded

#### Outer Jacket Material

Material	Nominal Diameter	Nominal Wall Thickness
PVC - Polyvinyl Chloride	0.273 in	0.034 in

### Construction and Dimensions

#### Stranding

Lay Direction	Twists
Left Hand	6.9 twist/ft

### Electrical Characteristics

#### Conductor DCR

Individual Pair Nominal Shield DCR	Nominal Conductor DCR	Nominal Outer Shield DCR
10.6 Ohm/1000ft	15 Ohm/1000ft	10.6 Ohm/km

Capacitance

Nom. Capacitance Conductor to Conductor	Nom. Capacitance Conductor to Other Conductor to Shield
30 pF/ft	55 pF/ft
10.6 pF/ft	

Inductance

Nominal Inductance
0.18 µH/ft

Impedance

Nominal Characteristic Impedance
50 Ohm

High Frequency (Nominal/Typical)

Nom. Insertion Loss
10.7 dB/100m
10.7 dB/100m

Delay

Max. Delay Skew	Nominal Velocity of Propagation (VP) [%]
66 ns/100m	66 %

Current

Max. Recommended Current [A]
2 Amps per conductor @ 25°C A

Current Table Note:	10C Temperature Rise
---------------------	----------------------

Voltage

UL Description	UL Voltage Rating
Listed type CM	300 V RMS (Listed type CM)
AWM 2919	30 V RMS (UL AWM 2919)

Temperature Range

UL Temp Rating:	80°C (UL AWM Style 2919)
Storage Temp Range:	-40°C To +80 °C
Operating Temp Range:	-20°C To +80°C

Mechanical Characteristics

Bulk Cable Weight:	39 lbs/1000ft
Max Recommended Pulling Tension:	79 lbs
Min Bend Radius/Minor Axis:	2.75 in

Dimensions (WxHxD)

Width
10.69

Standards

NEC Articles:	800
NEC/(UL) Specification:	CM
CEC/C(UL) Specification:	CM
UL AWM Style:	2919 (30 V 80°C)
CPR Euroclass:	Eca

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2004-01-01

CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

Suitability

Suitability - Hazardous Locations:	Yes
Suitability - Indoor:	Yes

Flammability, LSOH, Toxicity Testing

UL Flammability:	UL1685 UL Loading
CSA Flammability:	FT1
ISO/IEC Flammability:	IEC 60332-1-2
UL voltage rating:	300 V RMS (CM)

Plenum/Non-Plenum

Plenum (Y/N):	No
Plenum Number:	88777, 87777, 82777

Part Number

Variants

Item #	Color	UPC	Length	Footnote
8777.001000	Chrome		1,000 m	
8777.0030	Chrome		30 m	
8777.00305	Chrome		305 m	
8777.00U152	Chrome		152 m	
8777.00U305	Chrome		305 m	
8777.01152	Chrome		152 m	
8777.013048	Chrome		3,048 m	
8777 060100	Chrome	612825216087	100 ft	
8777 0601000	Chrome	612825216094	1,000 ft	C
8777 06010000	Chrome	612825216100	10,000 ft	C Y
8777 0601640	Chrome	612825216117	1,640 ft	C
8777 060250	Chrome	612825216124	250 ft	C
8777 0603280	Chrome	612825216131	3,280 ft	C
8777 060500	Chrome	612825216148	500 ft	C
8777 0605000	Chrome	612825216155	5,000 ft	C
8777 060U1000	Chrome	612825216063	1,000 ft	
8777 060U500	Chrome	612825216070	500 ft	
8777.K0305	Chrome		305 m	

Footnote:	C - CRATE REEL PUT-UP.
Footnote:	Y - FINAL PUT-UP LENGTH MAY VAR -10% TO +20% FROM LENGTH SHOWN. MAY CONTAIN 2 PIECES. MINIMUM LENGTH OF ANY ONE PIECE IS 1500'.

History

Update and Revision:	Revision Number: 0.323 Revision Date: 02-19-2020
----------------------	--

© 2020 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.