

Safety Data Sheet

Material: 60008105

ELASTOSIL® A234 WHITE CARTRIDGE

Version: 2.4 (US)

Date of print: 12/21/2020

Date of last alteration: 11/16/2019

1. Product and company identification

1.1 Identification of the substance or preparation:

Commercial product name:

ELASTOSIL® A234 WHITE CARTRIDGE

Use of substance / preparation

Industrial.

Raw material for: elastomer products .

1.2 Company/undertaking identification:

Manufacturer/distributor:

Wacker Chemie AG
Hanns-Seidel-Platz 4
81737 München
Germany

Customer information:

Wacker Chemical Corporation
3301 Sutton Road
Adrian, Michigan 49221-9397
USA

InfoLine:

Tel (517) 264-8240

Hours of operation:

Monday - Friday, 8 am to 5 pm (eastern standard time)

Corporate website: www.wacker.com**Emergency telephone no. (24h):****(517) 264-8500****Transportation emergency:**

(800) 424-9300 (CHEMTREC, USA)

(703) 527-3887 (CHEMTREC, international)

This SDS was prepared by the Regulatory Affairs and Product Safety Department (RAPS) of Wacker Chemical Corporation.

2. Hazards identification

2.1 Classification of the substance or mixture

Classification (GHS):

Hazard class	Hazard category	Route of exposure
Skin corrosion/irritation	Category 2	
Serious eye damage/eye irritation	Category 1	

2.2 Label elements

Labelling (GHS):

Pictogram(s):



Signal Word: Danger

H-Code	Hazard Statements
H315	Causes skin irritation.
H318	Causes serious eye damage.
P-Code	Precautionary Statements
P280	Wear protective gloves/protective clothing/eye protection.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor.
P302+P352	IF ON SKIN: Wash with plenty of water/soap.
P332+P313	If skin irritation occurs: Get medical advice/ attention.
P501	Dispose of contents/container to waste disposal.

Safety Data Sheet

Material: 60008105

ELASTOSIL® A234 WHITE CARTRIDGE

Version: 2.4 (US)

Date of print: 12/21/2020

Date of last alteration: 11/16/2019

2.3 Other hazards

Inhalation of aerosol spray may damage health.

The product hydrolyses under formation of methanol (CAS-Nr. 67-56-1). Methanol is classified concerning both physical and health hazards. The hydrolysis rate and consequently the relevance for the hazard profile of the product is strongly dependent on the specific conditions.

3. Composition/information on ingredients

3.1 Chemical characterization (preparation)

Chemical characteristics

Polydimethylsiloxane+auxiliary+Aminosilane

3.2 Information on ingredients:

Type	CAS No.	Substance	Content [wt. %]		Note
			Lower	Upper	
INHA	15901-40-3	Methyl tricyclohexylamino silane	>3.0	<5.0	

Type: HYD - by-product upon hydrolysis, INHA - ingredient, NEBE - by-product, MONO - residual monomer, VERU - impurity, VUL - by-product upon vulcanization. *** **Note:** C1 - IARC carcinogen, C2 - NTP carcinogen, C3 - OSHA carcinogen, NH - non-hazardous, R - reproductive toxin.

Substances listed in the Subsections "HAPS" and "California Proposition 65 Carcinogens / Reproductive Toxins" that are not listed in this section are only present at quantities below 0.1% for California Proposition 65 listed toxins or below 1% for non-carcinogenic HAPS or they are inextricably bound in the product. Specific chemical identities and/or exact percentage (concentration) of the composition may have been withheld as a trade secret.

This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57) in amounts above $\geq 0.1\%$.

4. First-aid measures

4.1 General information:

Get medical attention immediately. Remove contaminated clothing and shoes.

4.2 After inhalation

If inhaled remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult give oxygen.

4.3 After contact with the skin

For skin contact, immediately wipe away excess material. Use a waterless hand cleaner to remove as much of the remaining material as possible. Wash with soap and water.

4.4 After contact with the eyes

If contact with eyes, immediately hold eyelids apart and flush with plenty of water for at least 15 min. Continue to bathe eyes during transport to medical practitioner.

4.5 After swallowing

For ingestion, if conscious, give several glasses of water but do not induce vomiting. If vomiting does occur, give additional fluids.

4.6 Advice for the physician

Treat symptomatically.

5. Fire-fighting measures

5.1 Flammable properties:

Property:	Value:	Method:
Flash point.....	not applicable	(DIN 53213)
Boiling point / boiling range	not applicable	
Lower explosion limit (LEL)	not applicable	
Upper explosion limit (UEL).....	not applicable	
Ignition temperature	ca. 448 °C (838 °F)	(EN 14522)
NFPA Hazard Class (comb./flam.liquid).....	IIIB	

Safety Data Sheet

Material: 60008105

ELASTOSIL® A234 WHITE CARTRIDGE

Version: 2.4 (US)

Date of print: 12/21/2020

Date of last alteration: 11/16/2019

5.2 Fire and explosion hazards:

This material does not present any unusual fire or explosion hazards. Hydrolyzes on contact with moisture releasing ignitable, corrosive vapors.

5.3 Recommended extinguishing media:

carbon dioxide, dry chemical or foam-type extinguishing media .

5.4 Unsuitable extinguishing media:

water .

5.5 Special exposure hazards arising from the substance or preparation itself, combustion products, resulting gases

Hazardous decomposition products: carbon dioxide , carbon monoxide , formaldehyde , silicon dioxide , nitrogen oxides and incompletely burnt hydrocarbons .

5.6 Fire fighting procedures:

Fire fighters should wear full protective clothing including a self-contained breathing apparatus. Cool endangered containers with water.

6. Accidental release measures

6.1 Precautions:

Secure the area. Wear personal protection equipment (see section 8). Keep unprotected persons away. Avoid contact with eyes and skin. Do not inhale gases/vapours/aerosols. If material is released indicate risk of slipping. Do not walk through spilled material.

HAZWOPER PPE Level: C

6.2 Containment:

Prevent material from entering surface waters, drains or sewers and soil. Close leak if possible without risk. Contain any fluid that runs out using suitable material (e.g. earth). Retain contaminated water/extinguishing water. Dispose of in prescribed marked containers. Inform authorities if substance leaks into surface waters, sewerage or ground.

Spills of material which could reach surface waters must be reported to the United States Coast Guard National Response Center's toll free phone number (800) 424-8802.

6.3 Methods for cleaning up

Take up mechanically and dispose of according to local/state/federal regulations. Do not flush away with water. For small amounts: Absorb with a neutral (non-acidic / non-basic) liquid binding material such as diatomaceous earth and dispose of according to government regulations. For large amounts: Liquids may be recovered using suction devices or pumps. If flammable, only air driven or properly rated electrical equipment should be used. Clean any slippery coating that remains using a detergent / soap solution or another biodegradable cleaner. Silicone fluids are slippery; spills are a safety hazard. Apply sand or other inert granular material to improve traction.

6.4 Further information:

Exhaust vapours. Eliminate all sources of ignition. Consider explosion protection. Observe notes under section 7.

7. Handling and storage

7.1 Handling

Precautions for safe handling:

Ensure adequate ventilation. Must be syphoned off in situ. Spilled substance increases risk of slipping. Avoid formation of aerosols. In case of aerosol formation special protective measures are required (exhausting by suction, respiratory protection). Observe information in section 8. Keep away from incompatible substances in accordance with section 10.

Precautions against fire and explosion:

Product can separate methanol. Flammable vapors may accumulate and form explosive mixtures with air in containers, process vessels, including partial, empty and uncleared containers and vessels, or other enclosed spaces. Keep away from sources of ignition and do not smoke. Take precautionary measures against electrostatic charging. Cool endangered containers with water.

Safety Data Sheet

Material: 60008105

ELASTOSIL® A234 WHITE CARTRIDGE

Version: 2.4 (US)

Date of print: 12/21/2020

Date of last alteration: 11/16/2019

7.2 Storage

Conditions for storage rooms and vessels:

Observe local/state/federal regulations.

Advice for storage of incompatible materials:

Observe local/state/federal regulations.

Further information for storage:

Store in a dry and cool place. Protect against moisture. Store container in a well ventilated place.

Maximum temperature allowed during storage and transportation: 30 °C (86 °F)

8. Exposure controls and personal protection

8.1 Engineering controls

Ventilation:

Use only with adequate ventilation.

Local exhaust:

To maintain concentration below TLV. Local exhaust ventilation which meets the requirements of ANSI Z9.2 is recommended to control airborne contaminants at the point of use.

8.2 Associate substances with specific control parameters such as limit values

Maximum airborne concentrations at the workplace:

CAS No.	Substance	Type	mg/m ³	ppm	Dust fract.
108-91-8	Cyclohexylamine	ACGIH TWA		10.0	

8.3 Personal protection equipment (PPE)

Respiratory protection:

A NIOSH approved air purifying respirator equipped with universal multi-contaminant multi-gas/vapor cartridges is recommended if overexposure to chemical vapors could occur. If eye-irritating dusts or vapors are present, a full-face respirator should be worn.

Hand protection:

butyl rubber protective gloves .

Eye protection:

Safety glasses with side shields or chemical safety goggles. Additional eye and face protection, splash-proof goggles, hood, full-faced respirator, or face shield is recommended if splashing could occur.

Other protective clothing or equipment:

Additional skin protection, such as SARANEX coated Tyvek apron, over-sleeves, lab coat, coveralls, or protective suit should be worn if splashing could occur. Provide eye bath and safety shower.

8.4 General hygiene and protection measures:

Avoid contact with eyes, skin and clothing. Avoid breathing dust/vapor/mist/gas/aerosol. Do not eat, drink or smoke when handling. Wash thoroughly after handling.

9. Physical and chemical properties

9.1 Appearance

Physical state : liquid
Colour : white
Odour : amine like

9.2 Safety parameters

Property:	Value:	Method:
Melting point / melting range	: not applicable	
Boiling point / boiling range	: not applicable	
Flash point.....	: not applicable	
Ignition temperature	: ca. 448 °C (838 °F)	(DIN 53213) (EN 14522)
Lower explosion limit (LEL)	: not applicable	
Upper explosion limit (UEL).....	: not applicable	
Vapour pressure.....	: not applicable	

Safety Data Sheet

Material: 60008105

ELASTOSIL® A234 WHITE CARTRIDGE

Version: 2.4 (US)

Date of print: 12/21/2020

Date of last alteration: 11/16/2019

Density	1.18 g/cm ³ at 23 °C (73 °F)	(DIN 53217)
Water solubility / miscibility.....	virtually insoluble	
pH-Value	not applicable	
Viscosity (dynamic)	35000 mPa.s at 23 °C (73 °F)	(Brookfield)

9.3 Further information

Odour limit..... : no data available
Thermal decomposition.....: not applicable

10. Stability and reactivity

10.1 General information:

If stored and handled in accordance with standard industrial practices no hazardous reactions are known.

10.2 Conditions to avoid

moisture , Heat, open flames, and other sources of ignition.

10.3 Materials to avoid

Reacts with: water , basic substances and acids . Reaction causes the formation of: methanol .

10.4 Hazardous decomposition products

By hydrolysis: methanol . Measurements have shown the formation of small amounts of formaldehyde at temperatures above about 150 °C (302 °F) through oxidation.

10.5 Further information:

Hazardous polymerization cannot occur.

11. Toxicological information

11.1 Information on toxicological effects

11.1.1 Acute toxicity

Assessment:

For this endpoint no toxicological test data is available for the whole product.

Acute toxicity estimate (ATE):

ATE_{mix} (Oral): > 2000 mg/kg

11.1.2 Skin corrosion/irritation

Assessment:

Irritation of the skin must be expected. Due to a strong adherence to the skin symptoms of skin corrosion cannot be excluded after removing the substance mechanically.

Product details:

Result/Effect	Species/Test system	Source
not corrosive	Corrositex	Conclusion by analogy

11.1.3 Serious eye damage / eye irritation

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.4 Respiratory or skin sensitization

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.5 Germ cell mutagenicity

Safety Data Sheet

Material: 60008105

ELASTOSIL® A234 WHITE CARTRIDGE

Version: 2.4 (US)

Date of print: 12/21/2020

Date of last alteration: 11/16/2019

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.6 Carcinogenicity

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.7 Reproductive toxicity

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.8 Specific target organ toxicity (single exposure)

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.9 Specific target organ toxicity (repeated exposure)

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.10 Aspiration hazard

Assessment:

Based on the physical-chemical properties of the product no aspiration hazard must be expected.

11.1.11 Further toxicological information

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP. No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC. No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Other information: Hydrolysis product / impurity: Cyclohexylamine (CAS RN 108-91-8) is corrosive to skin and eyes and shows moderate toxic effects after oral administration as well as distinct toxic effects after dermal administration. Exposure to vapour causes irritation of the upper respiratory tract and the eyes. In animal experiments reproductive effects were observed.

12. Ecological information

12.1 Toxicity

Assessment:

For the product as a whole, no test data is available. According to current knowledge adverse effects on water purification plants are not expected.

12.2 Persistence and degradability

Assessment:

Silicone content: biologically not degradable. Separation by sedimentation.

12.3 Bioaccumulative potential

Assessment:

| Polymer component: Bioaccumulation is not expected to occur.

12.4 Mobility in soil

Assessment:

Silicone content: Insoluble in water.

12.5 Results of PBT and vPvB assessment

| No data available.

Safety Data Sheet

Material: 60008105

ELASTOSIL® A234 WHITE CARTRIDGE

Version: 2.4 (US)

Date of print: 12/21/2020

Date of last alteration: 11/16/2019

12.6 Other adverse effects

none known

13. Disposal considerations

13.1 Product disposal

Recommendation:

Material that cannot be used, reprocessed or recycled should be disposed of in accordance with Federal, State, and local regulations at an approved facility. Depending on the regulations, waste treatment methods may include, e.g., landfill or incineration.

13.2 Packaging disposal

Recommendation:

Completely discharge containers (no tear drops, no powder rest, scraped carefully). Containers may be recycled or re-used. Observe local/state/federal regulations. Uncleaned packaging should be treated with the same precautions as the material.

14. Transport information

14.1 US DOT & CANADA TDG SURFACE

Valuation: Not regulated for transport

14.2 Transport by sea IMDG-Code

Valuation: Not regulated for transport

14.3 Air transport ICAO-TI/IATA-DGR

Valuation: Not regulated for transport

15. Regulatory information

15.1 U.S. Federal regulations

TSCA inventory status and TSCA information:

This material or its components are listed on or are in compliance with the requirements of the TSCA Chemical Substance Inventory.

TSCA 12(b) Export Notification:

This material does not contain reportable amounts of any TSCA 12(b) listed chemicals.

CERCLA Regulated Chemicals:

This material does not contain any CERCLA regulated chemicals.

SARA 302 EHS Chemicals:

This material does not contain any SARA extremely hazardous substances.

SARA 311/312 Hazard Class:

Immediate (acute) health hazard.

SARA 313 Chemicals:

This material does not contain any SARA 313 chemicals above de minimus levels.

HAPS (Hazardous Air Pollutants):

CAS No.	Chemical	Upper limit wt. %
108-88-3	Toluene	<=0.0499
67-56-1	Methanol	<=0.0005

15.2 U.S. State regulations

California Proposition 65 (Safe Drinking Water and Toxic Enforcement Act of 1986):

This material does not contain any chemicals known to the State of California to cause cancer.

California Proposition 65 Reproductive Toxins:

108-88-3	Toluene
67-56-1	Methanol

Safety Data Sheet

Material: 60008105

ELASTOSIL® A234 WHITE CARTRIDGE

Version: 2.4 (US)

Date of print: 12/21/2020

Date of last alteration: 11/16/2019

Massachusetts Substance List:

This material contains no listed components.

New Jersey Right-to-Know Hazardous Substance List:

This material contains no listed components.

Pennsylvania Right-to-Know Hazardous Substance List:

This material contains no listed components.

15.3 Details of international registration status

Relevant information about individual substance inventories, where available, is given below.

Japan	ENCS (Handbook of Existing and New Chemical Substances): This product is listed in, or complies with, the substance inventory.
Australia	AICS (Australian Inventory of Chemical Substances): This product is listed in, or complies with, the substance inventory.
China.....	IECSC (Inventory of Existing Chemical Substances in China): This product is listed in, or complies with, the substance inventory.
Canada	DSL (Domestic Substance List): This product is listed in, or complies with, the substance inventory.
Philippines.....	PICCS (Philippine Inventory of Chemicals and Chemical Substances): This product is listed in, or complies with, the substance inventory.
United States of America (USA).....	TSCA (Toxic Substance Control Act Chemical Substance Inventory): All components of this product are listed as active or are in compliance with the substance inventory.
Taiwan	TCSI (Taiwan Chemical Substance Inventory): This product is listed in, or complies with, the substance inventory. General note: The Taiwanese chemicals regulation requires a phase 1 registration for TCSI-listed or TCSI-compliant substances if imports to Taiwan or manufacturing in Taiwan exceed the trigger quantity of 100 kg/a (for mixtures to be calculated per each ingredient). It is the duty of the importing/manufacturing legal entity to take care of this obligation.
European Economic Area (EEA).....	REACH (Regulation (EC) No 1907/2006): General note: the registration obligations for substances imported into the EEA or manufactured within the EEA by the supplier mentioned in section 1 are fulfilled by the said supplier. The registration obligations for substances imported into the EEA by customers or other downstream users must be fulfilled by the latter.
South Korea (Republic of Korea)	AREC (Act on Registration and Evaluation of Chemicals; "K-REACH"): General note: in case of registration obligations for substances or polymers imported into Korea or manufactured within Korea these are fulfilled by the supplier mentioned in section 1. The registration obligations for substances or polymers imported into Korea by customers or other downstream users must be fulfilled by the latter.

16. Other information**16.1 Additional information:**

This Safety Data Sheet (SDS) meets the requirements of the Federal OSHA Hazard Communication Standard (29 CFR 1910.1200). This information relates to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is to the best of our knowledge and belief accurate and reliable as of the date compiled. However, no representation, warranty or guarantee expressed or implied, is made as to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his own particular use. We do not accept liability for any loss or damage that may occur from the use of this information. Nothing herein shall be construed as a recommendation for uses which infringe valid patents or as extending a license under valid patents. This SDS provides selected regulatory information on this product, including its components. This is not intended to include all regulations. It is the responsibility of the user to know and comply with all applicable rules, regulations and laws relating to the product being used.

Vertical lines in the left-hand margin indicate changes compared with the previous version.

WACKER restricts the use of its products inside the human body or in contact with bodily fluids and mucosa. For further details please review our Health Care Policy on www.wacker.com. WACKER may cancel any delivery obligation(s) if the Health Care

Safety Data Sheet

Material: 60008105

ELASTOSIL® A234 WHITE CARTRIDGE

Version: 2.4 (US)

Date of print: 12/21/2020

Date of last alteration: 11/16/2019

Policy is not observed.

16.2 Glossary of Terms:

ACGIH - American Conference of Governmental Industrial Hygienists
DOT - Department of Transportation
hPa - Hectopascals
mPa*s - Milli Pascal-Seconds
OSHA - Occupational Safety and Health Administration
PEL - Permissible Exposure Limit

ppm - Parts per Million
SARA - Superfund Amendments and Reauthorization Act
STEL - Short Term Exposure Limit
TSCA - Toxic Substances Control Act
TWA - Time Weighted Average
WHMIS - Canadian Workplace Hazardous Materials Identification System

Flash point determination methods

ASTM D56.....	Tagliabue (Tag) closed cup
ASTM D92, DIN 51376, ISO 2592	Cleveland open cup
ASTM D93, DIN 51758, ISO 2719	Pensky-Martens closed cup
ASTM D3278, DIN 55680, ISO 3679	Setaflash or Rapid closed cup
DIN 51755.....	Abel-Pensky closed cup

Common name

16.3 Conversion table:

Pressure:.....: 1 hPa * 0.75 = 1 mm Hg = 1 torr; 1 bar = 1000 hPa

Viscosity:.....: 1 mPa*s = 1 centipoise (cP)