

Product Features

- Integrated 2.4GHz, IEEE 802.11b/g compatible WiFi connectivity
- Dual 8-bit 1T 8051/80390 CPU @ 80MHz
- Baud rate Range: 3600 to 921600bps, UART support RS232/RS485/RS422.
- On board ceramic chip antenna and U.FL connector for external antenna
- Max outdoor range up to 300m (984 ft.), line of sight
- Electromagnetic Compatibility: FCC, CE, ARIB
- Peak Current at 3.3V Power Input in Serial to WiFi Device Server Application about 360mA
- Security 802.11i security: WEP-64/128, TKIP(WPA-PSK) and AES (WPA2-PSK)
- Up to 13 channels. Profiles available include USA, Canada, Europe, Spain, France, Japan, China, Taiwan and "Other" (multiple countries)
- Update firmware by webpage or TFTP.
- Built-in watchdog.
- Supports 3 WiFi power saving modes in normal operation of Infrastructure mode with auto-wakeup timer for upcoming Beacon frame reception.

Applications

- Serial to WiFi Device Server
- WiFi Speaker
- WiFi Remote Control/Monitor
- Ethernet to WiFi Bridge
- WiFi Network Camera
- WiFi RFID TCP/IP and WLAN Offload




Product Description

The ATC-1000WF is a 2.4GHz 802.11b/g Wi-Fi device with U.FL connector for external antenna transceiver on board to provide a complete. The ATC-1000WF is a rail mounting device with lower-cost, pre-calibrated RF front-end and pre-certified Wi-Fi. This complete solution is preloaded with software to simplify integration and minimizes development of your application. In the simplest configuration the hardware only requires four connections (PWR, TX, RX, GND) to create a wireless data connection. The ATC-1000WF is programmed and controlled with a simple ASCII command language and webpage. Once the ATC-1000WF is setup it can scan to find an access point, associate, authenticate and connect over any Wi-Fi network.



RS-232 DB-9(Male)



PIN	RS-232
1/4/6/9	—
2	RXD (in)
3	TXD (out)
5	GND
7	CTS (out)
8	RTS (in)

RS-485/422 6-pin Terminal block

1	2	3	4	5	6
485+ (T+)	485- (T-)	R+	R-	VCC (9~24VDC)	GND

Package Checklist

- ATC-1000WF unit 1 PCS
- Documentation and software CD 1PCS
- Power adapter 9V 1PCS
- monopole Antenna (2dBi RP-SMA) 1PCS

Order Information

ATC-1000WF Wi-Fi (802.11b/g) to Serial Port Converter RS-232/422/485

Specifications

Serial Interface		
Interface Type	RS-232/485/422 3 in 1(optional)	
UART Speed	1200bps to 115200bps	
Data Bits	5, 6, 7 or 8 bits	
Parity	None, Odd, Even	
Stop Bits	1 , 1.5 or 2 bits	
Flow Control	None, Software: Xon/Xoff, Hardware: RTS/CTS	
Protocol	IP/TCP/UDP/ICMP/IGMP Checksum and ARP in hardware; TCP, UDP, ICMP, IGMP, IPv4, DHCP, BOOTP, ARP, DNS, SMTP, SNTP, UPnP, PPPoE, Telnet and HTTP in software	
Connector	RS-232	DB-9 male
	RS-485/422	6-pin Terminal block
Radio Characteristics		
Frequency	2.412 ~ 2.484 GHz	

Channels	1 - 16	
Transmit Power	802.11b: +20 dBm (Max.)	
	802.11g: +18 dBm (Max.)	
	802.11n: +15 dBm (Max.)	
Receiver Sensitivity	802.11b: -89 dBm	
	802.11g: -81 dBm	
	802.11n: -71 dBm	
Transmission rate (over the air)	IEEE 802.11b: 1, 2, 5.5 and 11 Mbps IEEE 802.11g: 6, 9, 12, 18, 24, 36, 48 and 54 Mbps Supports TX rate auto fall-back mechanism	
Wi-Fi Certified ID	WFA11474 for AXM22001-2A-B	
System		
CPU	ASIX AX22001, dual 8-bit 1T 8051/80390 CPU (MCPU/WCPU) @ 80MHz	
Memory	1M FLASH, 64K SRAM	
RF Transceiver	Airoha AL2230S	
LED Indicators	LINK	WLAN status
	ACT	It will flash when transmit the data from WLAN to serial or from serial to WLAN.
	PWR	Power indicator
Power Supply	9~24VDC	
Physical Characteristics		
Housing	Iron (1mm)	
Weight	0.5Kg	
Dimensions	100 × 86 × 26 mm(3.94 × 3.39 × 1.02 in)	
Environmental Limits		
Operating Temperature	-20 ~ 70°C	
Storage Temperature	-40 ~ 85°C	
Ambient Relative Humidity	5% to 95%(non-condensing)	
Standards and Certifications		
RoHS, CE, FCC		

Contact us

Shenzhen ATC Technology Co., Ltd

Add. Room 803, Block D, Building 16, South Station Enterprise City, Port Road Nanhai District, Foshan, China, 528251