



PLASTIC MODULAR BELTS

ZY-8000FG STRAIGHT RUNNING FLUSH GRID MODULAR BELTS




Mat.:POM/PP Pin mat.:PP/PA
Color:White/B
Open area:23%
Working load:
POM-22000N/M;PP-9000N/M




The belt standard width starts from 12" with 16.8mm increments up to 120"

ZY-8000FT STRAIGHT RUNNING FLAT TOP MODULAR BELTS




Mat.:POM/PP Pin mat.:PP/PA
Color:White/B
Open area:0%
Working load:
POM-22000N/M;PP-9000N/M



The belt standard width starts from 12" with 16.8mm increments up to 120"

ZY-8000FG/ZY-8000FT FLIGHTS




Height:32mm,50mm
76mm 100mm
Color:White
Mat.:POM/PP

ZY-8000FG/ZY-8000FT SIDE WALLS



Height:32mm,50mm
76mm 100mm
Color:White
Mat.:POM/PP

ZY-8000FG/ZY-8000FT SPROCKETS



Nb of teet h	P D	O D	Bor e
	mm	mm	mm
8	130.0	132.7	○/ □ min. 25 ○/ □ max. 40
10	161.7	164.4	
12	193.6	196.3	
14	225.9	228.3	